

	·+-3°	·±0.25		SDECIEIED	UNLESS		APPLIED CT HOLDER P/N	175133-8	20	28
SEE NOTE	-	ф Л	ММ	DIMENSIONS:		THIS DRAWING IS	APPLIED CTCONN P/N	173977-4	10	14
SEE NOTE	- ,,	1 PLC 2 PLC 4 +		TOLERANCES UNLESS		THIS DRAWING IS A CONTROLLED DOCUMENT.	MATING COUNTER	292182-8	2-292181-0	2-292181-8
ГТÌ	₩ 1			JNLESS			Н	32.4	44.4	52.4
CUSTO		1 O 8 APPLICATIO	T.SASAKI PRODUCT SPEC	APVN	CHK S.YAO	DWN 05FEB03 J.JIANG	G	38	50	ъ 8
CUSTOMER DRAWING	APPLICATION SPEC	108-60022 PLICATION SPEC	AKI				Т	31.4	43.4	51.4
AWING		22		0555803	05FEB03		П	31.8	43.8	51.8
AΖ	> SIZE						D	24.1	36.1	
CS 7.67 - 31 67 / 00 7 H	CAGE CODE DRAWING NO				— iyo Bearing		С	თ		26
	DRAWING NO		HYBRID		Ŭ		B	47	59	67
SCALE N) 0	REC ASS'Y	MINI D		Shanghai,	Tyco Elec	A	56	68	76
NTS SHEET	ן	γSS,λ	HYBRID MINI DRAWER CONN		Shanghai, P.R.China,200233	Tyco Electronics Corporation	POS ▲ (P-S)	4-8	4-20	4-28
 	RE		√N.				P,	292	2-	2-
REV B2	RESTRICTED TO						Ρ/N	292185-8	-0	 00

 \triangleright

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity: 292185-8