

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION 20  
 © COPYRIGHT 20 BY - ALL RIGHTS RESERVED.

**T.E. PROPRIETARY AND CONFIDENTIAL**  
 This drawing contains proprietary information that shall not be disclosed, duplicated nor used in whole or in part for any purpose other than to evaluate this drawing.

| LOC |     | DIST            |        | REVISIONS |      |  |  |
|-----|-----|-----------------|--------|-----------|------|--|--|
| P   | LTR | DESCRIPTION     | DATE   | DWN       | APVD |  |  |
|     | A   | INITIAL RELEASE | 180118 | PF        | AR   |  |  |



ACT 26 X X XX X X

KEYING POSITION  
 CONTACT CODE  
 P = 500 CYCLE PIN  
 S = 500 CYCLE SOCKET  
 A = LESS PIN  
 B = LESS SOCKET  
 H = 1500 CYCLE PIN  
 J = 1500 CYCLE SOCKET

INSERT ARRANGEMENT  
 SHELL SIZE  
 FINISH  
 J = OLIVE DRAB CADMIUM  
 M = NICKEL

STRAIGHT PLUG  
 GENERAL IDENTIFIER  
 ACT = ALL COMPOSITE TECHNOLOGY

| PART NUMBER | SHELL SIZE | Ø A MAX. | B THREAD          |
|-------------|------------|----------|-------------------|
| ACT26xAxxxx | 09         | .858     | M12x1.0-6g 0.100R |
| ACT26xBxxxx | 11         | .984     | M15x1.0-6g 0.100R |
| ACT26xCxxxx | 13         | 1.157    | M18x1.0-6g 0.100R |
| ACT26xDxxxx | 15         | 1.280    | M22x1.0-6g 0.100R |
| ACT26xExxxx | 17         | 1.406    | M25x1.0-6g 0.100R |
| ACT26xFxxxx | 19         | 1.516    | M28x1.0-6g 0.100R |
| ACT26xGxxxx | 21         | 1.642    | M31x1.0-6g 0.100R |
| ACT26xHxxxx | 23         | 1.768    | M34x1.0-6g 0.100R |
| ACT26xJxxxx | 25         | 1.890    | M37x1.0-6g 0.100R |

- FOR APPLICABLE KEYING DIAGRAM, SEE MIL-DTL-38999. FOR INSERT ARRANGEMENTS, SEE MIL-STD-1560. CONSULT FACTORY FOR AVAILABILITY.
- GENERAL SPECIFICATIONS: THIS CONNECTOR MEETS THE INTERMATEABILITY REQUIREMENTS OF MIL-DTL-38999 SERIES III.
- MATERIAL/FINISH  
 SHELL - COMPOSITE, PLATED.  
 COUPLING RING - COMPOSITE, UNPLATED.  
 CONTACTS - COPPER ALLOY, DEUTSCHCOAT V (H/J) OR GOLD (P/S).  
 RESILIENT INSERTS - SILICONE ELASTOMER.  
 PLASTIC INSERTS - THERMOPLASTIC.
- ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED. THREAD CALLOUT IS METRIC.

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN CRAIG BROWN 150102  
 CHK EHAB ALAWNEH 150102  
 APVD -

STE TE Connectivity

NAME ACT SERIES PLUG ENVELOPE

DIMENSIONS: INCH

TOLERANCES UNLESS OTHERWISE SPECIFIED:  
 0 PLC ±  
 1 PLC ±0.1  
 2 PLC ±0.01  
 3 PLC ±0.005  
 4 PLC ±0.0001  
 ANGLES ±  
 FINISH

PRODUCT SPEC -  
 APPLICATION SPEC -  
 WEIGHT -

SIZE A2 CAGE CODE - DRAWING NO. ACT26xxxxxx RESTRICTED TO -  
 SCALE 3.000 SHEET 1 OF 1 REV A

CUSTOMER DRAWING

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[YACT26JJ37PA000000](#)