



DESIGNED FOR USE WITH	RG-.405/U
CABLE ENTRY DIAMETER	MINIMUM
HOUSING	.161
SLEEVE	.087
CONTACT	.023

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
01 ₂	REDRAWN IN CAD PER ECN 98-0001	PATLAN 4-17-98	<i>[Signature]</i> 4/22/1998

ELECTRICAL	MECHANICAL	ENVIRONMENTAL
Nominal Impedance (Ohms) <u>50</u>	Interface Dimensions MIL-STD-348A, Fig. <u>310-2</u>	Temperature Rating <u>-65 TO 165°C</u>
Frequency Range (GHz) DC to <u>18</u>	Recommended Mating	Vibration MIL-STD-202, Method 204, Condition D
Volt Rating (VRMS MAX)	Torque <u>7-10 IN-LBS</u>	Shock MIL-STD-202, Method 213, Condition I
⊙ Sea Level <u>335</u>	Mating Characteristics:	Thermal Shock MIL-STD-202, Method 107, Condition B, Except High Temp 115°C
VSWR <u>1.07 + 0.01 F(GHz)</u>	Insertion (MAX Lbs) <u>2</u>	Moisture Resistance MIL-STD-202, Method 106
Insertion Loss (dB MAX) <u>.03 √f(GHz)</u>	Withdrawal (MIN Oz) <u>1</u>	Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray
RF Leakage (dB MIN) <u>-90</u>	Force to Engage and Disengage (In-Lbs MAX) <u>2</u>	
Corona, 70,000 Ft (VRMS MIN) <u>250</u>	Center Contact Captivation	
Dielectric Withstanding Voltage (VRMS MIN) ⊙ Sea Level <u>1,000</u>	Axial (Lbs) <u>6</u>	
Contact Resistance (Milliohms MAX)	Radial (In-Oz) <u>N/A</u>	
Center Contact <u>3.0</u>	Cable Retention	
Outer Contact <u>2.0</u>	Axial Force (Lbs) <u>30</u>	
Cable to Housing <u>0.5</u>	Torque (In-Oz) <u>16</u>	
RF High Potential ⊙ Sea Level	Weight (Grams) <u>TBD</u>	
(VRMS MIN ⊙ 5 MHz) <u>670</u>		
IR.(Megohms MIN) <u>5,000</u>		

COMPONENT	MATERIAL	FINISH
HOUSING CLAMP NUT MOUNTING NUT LOCKWASHER	STAINLESS STEEL PER ASTM-A484 AND ASTM- A582, TYPE 303	PASSIVATE PER QQ-P-35
DIELECTRIC	PTFE FLUOROCARBON PER ASTM-D-1457	N/A
CENTER CONTACT	BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204
SLEEVE	BRASS PER ASTM-B-16, HALF HARD	GOLD PLATE PER MIL-G-45204
O-RING	SILICONE RUBBER PER ZZ-R-765	N/A

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	DRAWN BY	BSS	DATE	7-03-86
	CHECKED BY	MM	DATE	7-11-86
	APP'D BY	LB	DATE	8-04-86
These drawings and specifications are the property of M/A COM Interconnect Div. and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.	USE ASSY PROCEDURE		M/A-COM a Division of AMP Incorporated 140 Fourth Avenue Waltham, MA 02154-7577	
	NO. AP.	408-04841 (20-559)	TITLE "SMA" BULKHEAD FEEDTHRU CABLE JACK-SOLDER CLAMP ATTACHMENT M39012/83-3007 CAT E	
	SIZE	B	CODE IDENT NO.	26805
SCALE	4:1		REV	01 ₂
			SHEET 1 OF 1	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[2004-8007-92](#)