2226910-1 ACTIVE

O.C.H. Micro Circular Connectors

TE Internal #: 2226910-1

O.C.H. Micro Circular Connectors, Standard Circular Connectors,

Wire-to-Wire, 6 Position, Sealable, Wire & Cable, 5A Contact

Current Rating (Max)

View on TE.com >



Connectors > Circular Connectors > Standard Circular Connectors



Connector System: Wire-to-Wire

Number of Positions: 6

Sealable: Yes

Connector & Contact Terminates To: Wire & Cable

Contact Current Rating (Max): 5 A

Features

Product Type Features

Accessory Color	Black
Prewired	No
Product Type	Connector Kit
Assembly Type	Electrical Connector
Connector System	Wire-to-Wire
Sealable	Yes
Connector & Contact Terminates To	Wire & Cable
Circular Connector Type	Plug
Shell Type	Plug

Configuration Features

Keying & Polarized Position Locations	Normal
Factory Installed Backshell	No
Keying	Triple Key
Number of Positions	6
Number of Power Positions	0
Number of Signal Positions	6
Contacts Preloaded	No



Body Features

Body Features	
Shield Rating	100 - 10000 MHz
Environmental Protection Type	Elastomer Sealed
Entry Style	Rear Insertion
Peripheral Seal Material	Fluorosilicone Elastomer
Positive Stop Ferrule	With
Environmental Protection	With
Weight	2.62 g[.006 lb]
O-Ring Material	Fluorosilicone
Fluid Type	None
Feedthrough Type	No
Feedthrough Type Shell Plating Material	No Black Zinc Nickel
Shell Plating Material	Black Zinc Nickel
Shell Plating Material Shell Base Material	Black Zinc Nickel Aluminum 6061-T6
Shell Plating Material Shell Base Material Circular Connector Insulation Material Type	Black Zinc Nickel Aluminum 6061-T6 LCP (Liquid Crystal Polymer)
Shell Plating Material Shell Base Material Circular Connector Insulation Material Type Hermetically Sealed	Black Zinc Nickel Aluminum 6061-T6 LCP (Liquid Crystal Polymer)

Contact Current Rating (Max)	5 A
Reverse Gender	No
Circular Connector Contact Type	Pin

Mechanical Attachment

Mating Alignment	With
Mating Retention Type	Push-Pull Self-Locking
PCB Mount Retention	Without
Panel Mount Feature Type	Flanged
Polarization Code	Normal
Mating Alignment Type	Keyed
Mating Retention	With

Housing Features

Alignment Keyed	Insert Clocking
Circular Connector Shell Size	6

Dimensions

Accepts wire insulation Diameter Range 1.32 mm[.03 – .034 in]	cepts Wire Insulation Diameter Range	1.32 mm[.03 – .054 in]	
---	--------------------------------------	------------------------	--



Assembly Length	25.2 mm[.99 in]
Wire Size	22 – 24 AWG
Usage Conditions	
IP Dust Sealing Level	5
Fluid Resistance	Yes
Operating Temperature Range	-10 – 70 °C
Operation/Application	
Durability Rating	2000 Cycles
Circuit Application	Signal
Shielded	Yes
Industry Standards	
UL Flammability Rating	UL 94V-0
Packaging Features	
Packaging Quantity	1
Other	
Position Locations Omitted	6
	8

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2021 (211) Candidate List Declared Against: JAN 2021 (211) SVHC > Threshold: Pb (3% in Component Part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Bromine/Chlorine - Br and Cl < 900 ppm per homogenous material. Also BFR /CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability



Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-onreach

Compatible Parts





CONTACT, PIN, CRIMPED, SIZE 23,

GND








TE Part # 2828420-2 RECEPTACLE BATTERY PCB VERSION 7 POS




Also in the Series | O.C.H. Micro Circular Connectors









Customers Also Bought
















CONTACT, PIN, CRIMPED, SIZE 23,

GND







Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2226910-1_M.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2226910-1_M.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2226910-1_M.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Datasheets & Catalog Pages

O.C.H. Micro Circular Connectors

English

Product Specifications

O.C.H. Micro Circular Connectors, Standard Circular Connectors, Wire-to-Wire, 6 Position, Sealable, Wire & Cable, 5A Contact Current Rating (Max)



Product Specification

English

Instruction Sheets

Instruction Sheet (U.S.)

English

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity: