# 4-1617785-7 ACTIVE

#### CII

TE Internal #: 4-1617785-7

Mid-Range Relays, Mid-Range Relay Contact Arrangement 4 Form C, 4PDT, 4 C/O, Tin-Lead Terminal Plating, 10A Mid-Range Relay Contact Current Rating

View on TE.com >



Relays, Contactors & Switches > Relays > Mil-Aero Relays > Mid-Range Relays



Mid-Range Relay Contact Arrangement: 4 Form C, 4PDT, 4 C/O

Coil Suppression Diode: Without

Auxiliary Contacts: Without
Terminal Plating: Tin-Lead

Mid-Range Relay Contact Current Rating: 10 A

Mid-Range Relay Contact Arrangement

**Auxiliary Contacts** 

### **Features**

## **Product Type Features**

Enclosure Type

Terminal Configuration	Solder Pins
Product Type	Relay
Relay Type	Military/Aerospace Mid-Range
Electrical Characteristics	
Vibration	20G's, 57 – 3000Hz
Shock	100G's, 6ms
Coil Suppression Diode	Without
Mid-Range Relay Coil Voltage Rating	12 VDC
Mid-Range Relay Coil Resistance	70 Ω
Mid-Range Relay Contact Switching (Max)	115/200Vac (60-400Hz)
Back EMF Suppression	Without
Coil Magnetic System	Polarized, Monostable
Actuating System	DC
Contact Features	

Hermetically Sealed

4 Form C, 4PDT, 4 C/O

Without



Terminal Plating	Tin-Lead
Mid-Range Relay Contact Current Rating	10 A
Contact Base Material	Silver Cadmium Oxide with Gold Plating
Mechanical Attachment	
Mid-Range Relay Mounting Type	Horizontal Flange Mount
Usage Conditions	
Operating Temperature Range	-70 – 125 °C

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Not Compliant
EU ELV Directive 2000/53/EC	Not Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2021 (211) Candidate List Declared Against: JAN 2021 (211) Does not contain REACH SVHC
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not lead free process capable

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

## **Compatible Parts**





## Customers Also Bought




TE Part #YDTS20F21-35JNV001 RECP ASSY



TE Part #1-1410710-3
MULTIGIG RT BP GUIDE PIN 11.60



TE Part #1410714-2 MULTIGIG RT GUIDE 7.2MM



TE Part #1484244-1 ADAPTER, TNC PLUG TO N JACK 3682 2311 02











## **Documents**

**CAD Files** 

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_4-1617785-7\_A.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_4-1617785-7\_A.3d\_igs.zip

English

Mid-Range Relays, Mid-Range Relay Contact Arrangement 4 Form C, 4PDT, 4 C/O, Tin-Lead Terminal Plating, 10A Mid-Range Relay Contact Current Rating



**Customer View Model** 

ENG\_CVM\_CVM\_4-1617785-7\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages 5-1773450-5\_sec5\_FCA-410

English

### **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

<u>TE Connectivity</u>: 4-1617785-7