

4805 (1/15)

- POSTS: .000030 GOLD IN CONTACT AREA .000100-.000200 MATTE TIN LEAD ON SOLDER TAIL, ALL OVER .000050 NICKEL
- POSTS: .000030 GOLD IN CONTACT AREA .000100-.000200 MATTE TIN ON SOLDER TAIL, ALL OVER .000050 NICKEL
- OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

∕₅\OBSOLETE	-
∕5\OBSOLETE	-
AOBSOLETE	-

7 2 1	ODOOLLIL
$\sqrt{5}$	OBSOLETE
$\sqrt{5}$	OBSOLETE
$\sqrt{5}$	OBSOLETE

$\sqrt{5}$ OBSOLETE	
SOBSOLETE	
	Γ

5 OBSOLETE 5 OBSOLETE

∕₅\OBSOLETE

∕₅\OBSOLETE

5 OBSOLETE
5 OBSOLETE
5 OBSOLETE
^

5	OBSOLETE
5	OBSOLETE
5	OBSOLETE

$\sqrt{5}$	OBSOLETE
5	OBSOLETE
5	OBSOLETE
5	OBSOLETE

5 OBSOLETE 5 OBSOLETE 5 OBSOLETE 5 OBSOLETE

S OBSOLETE

5 OBSOLETE

OBSOLETE

	·					T 75		- 407407 Z	_
OBSOLETE OBSOLETE		3.490	.190	3.800		35 34	72 70	8-103167-3 8-103167-2	1
		3.290	.190	3.600	3.300	33	68	8-103167-1	- - D
	4	3.190	.190	3.500		32	66	8-103167-0	
OBSOLETE		3.090	.190	3.400		31	64	7-103167-9	-
OBSOLETE		2.990	.190	3.300		30 29	62 60	<u>7-103167-8</u> 7-103167-7	1 1
OBSOLETE		2.890	.190	3.100		29	58	7-103167-6	1
OBSOLETE		2.690	.190	3.000	2.700	27	56	7-103167-5	
OBSOLETE	4	2.590	.190	2.900		26	54	7-103167-4	1
OBSOLETE	4	2.490	.190	2.800		25 24	52 50	7-103167-3 7-103167-2	
OBSOLETE		2.290	.190	2.700		24	48	7-103167-2	1 1
OBSOLETE		2.190	.190	2.500	2.200	22	46	7-103167-0	
OBSOLETE	4	2.090	.190	2.400		21	44	6-103167-9	
OBSOLETE	4	1.990	.190	2.300		20	42	6 - 103167 - 8	1
OBSOLETE		1.890	.190	2.200		19	40	<u>6-103167-7</u> 6-103167-6	1 1
OBSOLETE		1.690	.190			17	36	6-103167-6 6-103167-5	1
	4	1.590	.190	1.900	1.600	16	34	6-103167-4]]
OBSOLETE		1.490	.190		1.500	15	32	6-103167-3	-
OBSOLETE	4	1.390	.190		1.400	14	30 28	6-103167-2	1
UDJULIL	4	1.290	.190			12	28	<u>6-103167-1</u> 6-103167-0	1 1
		1.090	.190	1.400	1.100	1 1	24	5-103167-9	- C
		.990	.190	1.300		10	22	5-103167-8	
-		.890	.190	1.200		9	20	5-103167-7	
			.490	1.100		8	18	<u>5-103167-6</u> 5-103167-5	1 1
ľ			.390	.900	.600	6	14	5-103167-5 5-103167-4	1 1
[.290	.800	.500	5	12	5-103167-3	1
	4		.290	.700	.400	4	10	5-103167-2	
OBSOLETE	4	7 190	.190	.600 3.800	.300	3	8	5 - 103167 - 1 3 - 103167 - 3	<u> </u>
OBSOLETE		3.490	.190	3.800		35	72 70	<u>3-103167-3</u> <u>3-103167-2</u>	1 1
		3.290	.190	3.600		33	68	3-103167-1	1 1
OBSOLETE		3.190	.190	3.500	3.200	32	66	3-103167-0	1
OBSOLETE	3	3.090	.190	3.400		31	64	2-103167-9	
OBSOLETE	3	2.990	.190	3.300		30 29	62 60	2-103167-8 2-103167-7	4
OBSOLETE		2.890	.190			29	60 58	2-103167-7 2-103167-6	1 1
OBSOLETE		2.690	.190	3.000	2.700	27	56	2-103167-5	
OBSOLETE		2.590	.190	2.900	2.600	26	54	2-103167-4	
OBSOLETE	3	2.490	.190			25	52	2 - 103167 - 3	
OBSOLETE		2.390	.190		2.400	24 23	50 48	<u>2-103167-2</u> 2-103167-1	
OBSOLETE		2.290	.190			22	46	2-103167-0	
OBSOLETE		2.090	.190	2.400	2.100	21	44	1-103167-9	B
OBSOLETE	3	1.990	.190			20	42	1-103167-8	
OBSOLETE	3	1.890	.190			19	40	1 - 103167 - 7 1 - 103167 - 6	4
OBSOLETE		1.790	.190		1.800	18	38	<u>1-103167-6</u> 1-103167-5	
		1.590	.190			16	34	1-103167-4	
	3	1.490	.190		1.500	15	32	1-103167-3	
	3	1.390	.190			14	30	1 - 103167 - 2	-
OBSOLETE		1.290	.190		1.300	13	28 26	1 - 103167 - 1 1 - 103167 - 0	
ľ		1.090	.190			1 1	24	103167-9	
		.990	.190	1.300	1.000	10	22	103167-8	
	3	.890	.190	1.200		9	20	103167-7	-
OBSOLETE			.490	1.100		8	18	103167 - 6 103167 - 5	-
ŀ			.390	.900	.600	6	16	<u>103167-5</u> 103167-4	
			.290	.800	.500	5	12	103167 - 3	
			.290	.700	.400	4	10	103167-2	1
	3		.190	.600	.300	3	8	103167-1	-
	PLATING	E			B	A	NO OF Posn	ASSEMBLY PART NUMBER	A
THIS DRAWING IS	A CONTROLLED DOG	СНК	MOLL	27JUL87 28JUL87		E TE	TE	Connectivity	Γ-1
DIMENSIONS: INCHES	TOLERANCES OTHERWISE SF	SPECIFIED: APVD	ELICKER	29JUL87 NA	JAME H	- ASS	SY, MOD II, S		
$\oplus \subset$	0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± .0 4 PLC ± -	_ PRODU 005 APPLI	LICKER DUCT SPEC 			4 SID GHT ANG	DES, DR, .100 GLE, W/ .025	00X.100	
MATERIAL FLAME RETARDAN THERMOPLASTIC, COLOR : BLACK	ANGLES FINISH NT SEE TAB	± – – – – WEIGH BLE		-	4100779		03167	SHEFT OF REV	
POST:PHOS BROI		CUS	STOMER DF	RAWING			SCALE 4:1	Sheet 0F REV N5	l

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity:

5-103167-4