

4805 (1/15)

THIS	DRAWING	IS	А	С
	DIMENSIONS	5:		
	mm			
	-]
MATERIA				

2			1			
			REVISIONS			
	Ρ	LTR	DESCRIPTION	DATE	DWN	APVD
		AF1	REVISED PER ECN-23-220565	06JUL2023	RK	MF

СС	ONTROLLED DOCUMENT.	DWN 09FEB01 R BROWN	_	_	E TE	TE	Conne	ctivitv	Ltd.
	TOLERANCES UNLESS OTHERWISE SPECIFIED:	CHK 09FEB01 KWRIGHT APVD 09FEB01	NAME						
1	0 PLC ± - 1 PLC ± - 2 PLC ± 0.13[.005] 3 PLC ± -	K WRIGHT product spec 108-25034 application spec		2.54		ASSY, RTAN L, 0.64[.02 —		POST	Γ,
	4 PLC ± – ANGLES ± –	114-25026	SIZE	CAGE CODE	DRAWING NO				RESTRICTED TO
	FINISH SEE TABLE	WEIGHT	A1	00779	C- 103	3672			
		CUSTOMER DRAWING				SCALE 1.1	SHEET	1 ^{OF} C	

D

С

В

А

	8		7		6
<u> </u>	TE Connectivity. All Rights Reserved.	1		1	
/	√ .000100 BRIGHT TIN-	LEAD OVER .000050) NICKEL.		
	 point of measuremen	T FOR PLATING THICI	KNESS.		
Ĺ	THE NOTED DIMENSION		ERSECTION		
/	4 on assemblies with f		IONS.		
	TWO POLARIZATION SLO ON ASSEMBLIES WITH 1	DTS.			
	ONE POLARIZATION SLO				
L	AMP TRADEMARK MOLDE	D ON THIS SURFACE.			
	6. FOR USE WITH $1.57\pm$	0.20[.062±.008] PRI	NTED CIRCUIT BOAR	CD.	
Ĺ	A MATERIAL: HOUSING- FL POSTS- BRAS		COLOR-BLACK.		
2	▲ .000100 BRIGHT TIN OVE				<u></u>
4	A PRELIMINARY PART – NO	T RELEASED FOR PRO	DUCTION.		
Ĺ	10000100 MATTE TIN 0	VER .000050 NICKE	L.		
	11 HIGH TEMPERATURE C	ONFIGURATION			
	12 OBSOLETE PARTS: OBSOL	ETE CIS STREAMLINING	PER D.RENAUD/D.SIN	ISI	
	0.25 [.010] RECESS PER	MISSIBLE IN THIS AREA	FOR MOLD SHUT OF	F	

D

С

В

А

4805 (1/15)

REMARKS

		64.01 [2.520]	65.91 [2.595]	24	25	127-103672-4
		61.47 [2.420]	63.37 [2.495]	23	24	7-103672-3
		58.93 [2.320]	60.83 [2.395]	22	23	7-103672-2
		56.39 [2.220]	58.29 [2.295]	21	22	7-103672-1
		53.85 [2.120]	55.75 [2.195]	20	21	7 - 103672 - 0
		_ 51.31	53.21	19	20	<u>/1cl</u> 6-103672-9
		[2.020] 48.77	[2.095] 50.67	18	19	126-103672-8
		[1.920] 46.23	[1.995] 48.13	17	18	$\overline{\underline{\ }}$
		[1.820] 43.69	[1.895] 45.59			$12^{6-103672-7}$
		[1.720]	[1.795] 43.05	16	17	126-103672-6
		[1.620] 38.61	[1.695] 40.51	15	16	6-103672-5
		[1.520]	[1.595] 37.97	14	15	126-103672-4
		36.07	[1.495]	13	14	126-103672-3
	10	33.53 [1.320]	35.43 [1.395]	12	13	126-103672-2
		30.99 [1.220]	32.89 [1.295]	1 1	12	6-103672-1
		28.45 [1.120]	30.35 [1.195]	1 0	1 1	126-103672-0
		25.91 [1.020]	27.81 [1.095]	9	10	5-103672-9
		23.37 [.920]	25.27 [0.995]	8	9	5-103672-8
		20.83	22.73 [.895]	7	8	5-103672-7
		18.29 [.720]	20.19 [.795]	6	7	5-103672-6
		15.75 [.620]	17.65 [.695]	5	6	5-103672-5
		13.21 [.520]	15.11	4	5	5-103672-4
		10.67	12.57	3	4	5-103672-3
		[.420]	[.495]	2	3	5-103672-2
		[.320]	[.395]	1	2	5-103672-1
		[.220]	[.295]	1		5 100072-1
S	PLATING	С	B	A	NO. OF POSN	PART NO.
						1

4

5

11

.3

REMARKS

11

		25.91 [1.020]	27.81 [1.095]	9	10	3-103672-0	
		15.75 [.620]	17.65 [.695]	5	6	2-103672-9	
		5.59	7.493	1	2	2-103672-8	
11	8	13.21	15.11 [.595]	4	5	2-103672-7	
		10.67	12.57 [.495]	3	4	2-103672-6	
		8.13	10.03	2	3	2-103672-5	
		64.01 [2.520]	65.91 [2.595]	24	25	2-103672-4	
		61.47 [2.420]	63.37 [2.495]	23	24	2-103672-3	
		58.93	60.83 [2.395]	22	23	2-103672-2	
		56.39 [2.220]	58.29 [2.295]	21	22	2-103672-1	С
		53.85	55.75 [2.195]	20	21	2-103672-0	
		51.31 [2.020]	53.21 [2.095]	19	20	1-103672-9	
		48.77 [1.920]	50.67 [1.995]	18	19	1 - 103672 - 8	
		46.23	48.13	17	18	1 - 103672 - 7	
		43.69	45.59 [1.795]	16	17	1 - 103672 - 6	
		41.15	43.05	15	16	1-103672-5	
		38.61 [1.520]	40.51	1 4	15	1-103672-4	
		36.07 [1.420]	37.97 [1.495]	13	14	1-103672-3	
		33.53	35.43 [1.395]	12	13	1 - 103672 - 2	
<u></u>		30.99 [1.220]	32.89 [1.295]	1 1	12	<u>/ I </u>	
		28.45 [1.120]	30.35 [1.195]	10	1 1	1-103672-0	B
		25.91	27.81	9	10	103672-9	
		23.37	25.27 [0.995]	8	9	103672-8	
		20.83	22.73 [.895]	7	8	103672-7	
		18.29 [.720]	20.19	6	7	103672-6	
		15.75	17.65 [.695]	5	6	103672-5	
		13.21	15.11 [.595]	4	5	103672-4	
		10.67	12.57 [.495]	3	4	103672-3	
		8.13	10.03	2	3	103672-2	
		5.59	7.49 [.295]	1	2	103672-1	
EMARKS	PLATING	C	B	A	NO. OF POSN	PART NO.	A
THIS DRAWING	IS A CONTROLLED DOCUMEN	CHK	09FEB01 09FEB01	-E TE	I TE	E Connectivity Ltd.	
DIMENSIONS	S: TOLERANCES UNLESS OTHERWISE SPECIFIED:		O9FEBO1 NAME	HDR ASSY, RTANG, SINGLE ROW			
	$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$.005] 108-25034 WITH PLZN & HOLD DOWNS, AM			L, 0.64[.025] SQ POST, DLD DOWNS, AMPMODU MTE restricted to		
MATERIAL	ANGLES ± – FINISH SEE TABLE						
		CUSIUMER D	RAWING		4:1	2 2 AF1]

1 REVISIONS DESCRIPTION P LTR DATE DWN AP\ – SEE SHEET 1 _ _ _ _

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity: 5-103672-9