

4805 (1/15)

- HOUSING: FLAME RETARDANT, LCP, BLACK POST: BRASS
- 2 POINT OF MEASUREMENT FOR PLATING THICKNESS
- THE NOTED DIMENSIONS APPLY FROM THE BASIC DIMENSION LINE (NOT THE POST CENTERLINE) TO THE SURFACE INDICATED
- ON ASSEMBLIES WITH FOUR OR MORE POSITIONS, TWO POLARIZATION SLOTS.
 ON ASSEMBLIES WITH TWO OR THREE POSITIONS, ONE POLARIZATION SLOT.

5 FOR USE WITH .062±.008 PRINTED CIRCUIT BOARD

- 6 .000030 GOLD IN THE CONTACT AREA, .000100-.000200 MATTE TIN-LEAD ON THE SOLDER TAIL, ALL OVER .000050 NICKEL
- .000030 GOLD IN THE CONTACT AREA,

 .000100-.000200 MATTE TIN ON THE

 SOLDER TAIL, ALL OVER .000050 NICKEL
- 8 HIGH TEMPERATURE CONFIGURATION.
- 9 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI
- 10. .010 RECESS PERMISSIBLE IN THIS AREA FOR MOLD SHUT OFF

OBSOLETE 9 OBSOLETE OBSOLETE 9 8 OBSOLETE OBSOLETE OBSOLET ℅OBSOLET OBSOLETE OBSOLETE OBSOLETE SUPERCEDED BY 6-103904-2 8 REMARKS THIS DRAWING IS A DIMENSIONS: INCHES $\bigcirc \sub$ IATERIAL 1

	2.595	2.520	2.400	24	25	7-103904-4	
	2.495	2.420	2.300	23	24	7-103904-3	
	2.395	2.320	2.200	22	23	7-103904-2	
	2.295	2.220	2.100	21	22	7-103904-1	
	2.195	2.120	2.000	20	21	7-103904-0	
	2.095	2.020	1.900	19	20	6-103904-9	
	1.995	1.920	1.800	18	19	6-103904-8	
	1.895	1.820	1.700	17	18	6-103904-7	
	1.795	1.720	1.600	16	17	6-103904-6	
	1.695	1.620	1.500	15	16	6-103904-5	
	1.595	1.520	1.400	14	15	6-103904-4	
	1.495	1.420	1.300	13	14	6-103904-3	
	1.395	1.320	1.200	12	13	6-103904-2	
	1.295	1.220	1.100	1 1	12	6-103904-1	
	1.195	1.120	1.000	10	1 1	6-103904-0	
	1.095	1.020	.900	9	10	5-103904-9	
	.995	.920	.900	8	9	5-103904-8	
	.895	.920	.700	0 7	8	5-103904-8	
					7		
	.795	.720	.600	6		5-103904-6	
	.695	.620	.500	5	6	5-103904-5	
	.595	.520	.400	4	5	5-103904-4	
	.495	.420	.300	3	4	5-103904-3	
	.395	.320	.200	2	3	5-103904-2	
	.295	.220	.100	1	2	5-103904-1	
	2.595	2.520	2.400	24	25	2-103904-4	
	2.495	2.420	2.300	23	24	2-103904-3	
	2.395	2.320	2.200	22	23	2-103904-2	
	2.295	2.220	2.100	21	22	2-103904-1	
	2.195	2.120	2.000	20	21	2-103904-0	
	2.095	2.020	1.900	19	20	1-103904-9	
	1.995	1.920	1.800	18	19	1-103904-8	
	1.895	1.820	1.700	17	18	1-103904-7	
	1.795	1.720	1.600	16	17	1-103904-6	
	1.695	1.620	1.500	15	16	1 - 103904 - 5	
	1.595	1.520	1.400	14	15	1-103904-4	
	1.495	1.420	1.300	13	14		
						1-103904-3	
	1.395	1.320	1.200	12	13	1-103904-2	
	1.295	1.220	1.100	1 1	12	1-103904-1	
	1.195	1.120	1.000	10	1 1	1-103904-0	
	1.095	1.020	.900	9	10	103904-9	
	.995	.920	.800	8	9	103904-8	
	.895	.820	.700	7	8	103904-7	
	.795	.720	.600	6	7	103904-6	
	.695	.620	.500	5	6	103904-5	
	.595	.520	.400	4	5	103904-4	
	.495	.420	.300	3	4	103904-3	
	.395	.320	.200	2	3	103904-2	
	.295	.220	.100	1	2	103904-1	
		\cap		Λ	NO	ASSEMBLY	
PLATING			Ь	A	OF	PART	
					POS	NUMBER	
L Controlled d(DCUMENT.		17–93				
E. BRANDBERG CHK 5-17-93			17-93	TE TE Connectivity			
TOLERANCES OTHERWISE	UNLESS J. (SPECIFIED: APVD	GESFORD	- NAME				
_		CT SPEC		HEADER ASSY, AMPMODU MTE, RA SR, .100CL .025 SQ			
		08-25034					
		ATION SPEC	SIZE CAG	POSTS, WITH LATCH & HOLD DOWNS size cage code drawing no restricted to			
CUSTOMER DRAWING 4:1 4:1 1 1 REV							

D

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity:

6-103904-3