

SCHRACK | SCHRACK Slimline PCB Relay SNR

TE Internal #: 1956024-7

Power Relays, Standard, Monostable, DC, 176 mW Coil Power Rating DC, 20500 Ω Coil Resistance, SCHRACK Slimline PCB Relay

SNR

View on TE.com >



Relays & Contactors > Relays > Power Relays



Power Relay Type: Standard

Coil Magnetic System: Monostable, DC

Coil Power Rating DC: 176 mW

Coil Resistance: 20500Ω

Coil Special Features: UL Coil Insulation Class F

Features

Product Type Features

| Power Relay Type | Standard |
|--|----------------------------|
| Relay Connection Type | Plug-In |
| Electrical Characteristics | |
| Insulation Initial Dielectric Between Coil & Contact Class | 3500 – 4000 V |
| Insulation Initial Dielectric Between Contacts & Coil | 1000 V |
| Contact Limiting Making Current | 10 A |
| Contact Limiting Short-Time Current | 6 A |
| Contact Limiting Continuous Current | 10 A |
| Insulation Creepage Class | 5.5 – 8 mm |
| Coil Power Rating Class | 150 – 200 mW |
| Insulation Creepage Between Contact & Coil | 8 mm[.315 in] |
| Contact Limiting Breaking Current | 6 A |
| Coil Magnetic System | Monostable, DC |
| Coil Power Rating DC | 176 mW |
| Coil Resistance | 20500 Ω |
| Coil Special Features | UL Coil Insulation Class F |
| Coil Voltage Rating | 60 VDC |
| Contact Switching Load (Min) | 100mA @ 12V |



| Contact Switching Voltage (Max) | 400 VAC |
|---------------------------------|-------------------------------------|
| Contact Voltage Rating | 250 VAC |
| Body Features | |
| Insulation Special Features | Tracking Index of Relay Base PTI250 |

6 g[.2116 oz]

Contact Features

Product Weight

| Contact Plating Material | Gold |
|------------------------------|---------------|
| Contact Arrangement | 1 Form C (CO) |
| Contact Current Class | 16 A |
| Contact Current Rating (Max) | 6 A |
| Contact Material | AgSnO2 |
| Contact Number of Poles | 1 |

Mechanical Attachment

| Product Mount Type | Socket |
|--------------------|--------|
| | |

Dimensions

| Length Class (Mechanical) | 25 – 30 mm |
|---------------------------|---------------|
| Width Class (Mechanical) | 0 – 6 mm |
| Product Width | 5 mm[.196 in] |
| Product Length | 28 mm[1.1 in] |
| Product Height | 15 mm[.59 in] |

Usage Conditions

| Environmental Ambient Temperature Class | 70 – 85 °C |
|---|---------------|
| Environmental Ambient Temperature (Max) | 85 °C[185 °F] |

Packaging Features

| Packaging Method | Box & Tube, Tube |
|------------------|------------------|
|------------------|------------------|

Product Compliance

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU | Compliant |
|---|---|
| EU ELV Directive 2000/53/EC | Compliant |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold |
| EU REACH Regulation (EC) No. 1907/2006 | |



Current ECHA Candidate List: JAN 2024

(240)

Candidate List Declared Against: JAN 2024

(240)

Does not contain REACH SVHC

Halogen Content Not Low Halogen - contains Br or Cl > 900

ppm.

Solder Process Capability Wave solder capable to 260°C


Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Also in the Series | SCHRACK Slimline PCB Relay SNR



Customers Also Bought



















TE Part #8-1415547-9 RT444012P

Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1956024-7_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1956024-7_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1956024-7_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

Slim PCB Relay SNR

English

Relay Package SNR

English



Product Specifications

Definitions General Purpose Relays

English

Agency Approvals

VDE Certificate

English

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity:

1956024-7