

CII

TE Internal #: 1-1617122-0 TO-5/.100 Grid Relays, Contact Arrangement 2 Form C, DPDT, 2 C /O, 26.5VDC Input Voltage, 26.5 VDC Coil Voltage, 1560Ω Coil Resistance

View on TE.com >





Contact Arrangement: 2 Form C, DPDT, 2 C/O

Input Voltage: 26.5 VDC

Coil Voltage: 26.5 VDC

Coil Resistance: 1560 Ω

Coil Power Rating DC: 450 mW

Features

Product Type Features

Enclosure Type

Relay Options

TE connectivity

Hermetically Sealed

Coil Polarity Protection Diode, Coil Suppression Diode

PCB Solder Pins

Electrical Characteristics

Vibration Resistance	30G's, 10–3000Hz
Actuating System	DC
Coil Power Measurement	Milliwatts
Shock Resistance	75G's, 6ms
Contact Switching Voltage (Max)	28 VDC
Coil Magnetic System	Non-Polarized, Monostable
Input Voltage	26.5 VDC
Coil Voltage	26.5 VDC
Coil Resistance	1560 Ω
Coil Power Rating DC	450 mW
Contact Features	
Pin Configuration	.200" x .300" Spreader Pad
Contact Current Rating (Max)	1 A

JMACD-26XLS

TO-5/.100 Grid Relays, Contact Arrangement 2 Form C, DPDT, 2 C/O, 26.5VDC Input Voltage, 26.5 VDC Coil Voltage, 1560Ω Coil Resistance



Contact Arrangement	2 Form C, DPDT, 2 C/O
Usage Conditions	
Operating Temperature Range	-65 – 125 °C
Product Compliance	
For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Not Compliant
EU ELV Directive 2000/53/EC	Not Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024
	(240) Candidate List Declared Against: JAN 2024
	(240)
	Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per
	homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not lead free process capable

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts




Customers Also Bought

JMACD-26XLS

TO-5/.100 Grid Relays, Contact Arrangement 2 Form C, DPDT, 2 C/O, 26.5VDC Input Voltage, 26.5 VDC Coil Voltage, 1560Ω Coil Resistance







TE Part #ZPF00000000000374 006-0972-20 A

Documents

CAD Files

3D PDF

3D

Customer View Model ENG_CVM_CVM_1-1617122-0_G.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1-1617122-0_G.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-1617122-0_G.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Datasheets & Catalog Pages RELAY

English

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity:

JMACD-26XLS