

.049 [1.24] .606 [15.39] 2.312 [58.72] .029 [0.74] .586 [14.88] 2.292 [58.22]	.248 [6.30] .439 [11.15] .238 [6.05] .419 [10.64]	.683 [17.35] .653 [16.59]	.490 [12.45] .480 [12.19]	2.505 [63.63] 2.495 [63.37]	2.194 [55.73] 2.74 2.184 [55.47] 2.71	4 [69.70] 4 [68.94]	MS14004-1	104	6	1218747-6
.040 [1.02] .544 [13.82] 2.188 [55.58] .020 [0.51] .524 [13.31] 2.168 [55.07]	.248 [6.30] .439 [11.15] .238 [6.05] .419 [10.64]	.620 [15.75] .590 [14.99]	.428 [10.87] .418 [10.62]	2.411 [61.24] 2.401 [60.99]	2.069 [52.55] 2.65 2.059 [52.30] 2.62	) [67.31] ) [66.55]	MS18277-2	78	5	1218747-5
.040 [1.02] .432 [10.97] 2.282 [57.96] .020 [0.51] .412 [10.46] 2.262 [57.45]	.248 [6.30] .439 [11.15] .238 [6.05] .419 [10.64]	.509 [12.93] .479 [12.17]	.316 [8.03] .306 [7.77]	2.505 [63.63] 2.495 [63.37]	2.164 [54.97] 2.74 2.154 [54.71] 2.71		MS18276-2	62	4	1218747-4
.049 [1.24] .432 [10.97] 1.635 [41.53] .029 [0.74] .412 [10.46] 1.615 [41.02]	.248 [6.30] .439 [11.15] .238 [6.05] .419 [10.64]	.509 [12.93] .479 [12.17]	.316 [8.03] .306 [7.77]	1.857 [47.17] 1.847 [46.91]	1.516 38.51 2.10 1.506 38.25 2.07	3 [53.42]	MS18275-2	44	3	1218747-3
.040 [1.02] .432 [10.97] 1.093 [27.76] .020 [0.51] .412 [10.46] 1.073 [27.25]	.248 [6.30] .439 [11.15] .238 [6.05] .419 [10.64]	.509 [12.93] .479 [12.17]	.316 [8.03] .306 [7.77]	1.317 [33.45] 1.307 [33.20]	.976 [24.79] 1.55 .966 [24.54] 1.52	5 [39.52]	MS18274-2	26	2	1218747-2
.040 [1.02] .432 [10.97] .769 [19.53] .020 [0.51] .412 [10.46] .749 [19.02]	.248 [6.30] .439 [11.15] .238 [6.05] .419 [10.64]	.509 [12.93] .479 [12.17]	.316 [8.03] .306 [7.77]	.989 [25.12] .979 [24.87]	.648 [16.46] 1.228 .638 [16.21] 1.198	3 [31.19] 3 [30.43]	MS18273-2	15	1	1218747-1
	G F	E E	D	C	B	A A	INSERT RRANGEMENT	NO OF POS	SHELL SIZE	PART NUMBER
	· · · · ·				WING IS A CONTROLLED DOCUMEN		11-13-00 11-13-00	-21	TE	TE Connectivity
	NSIONS: CHES O PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± - 4 PLC ± - ANGLES ± - FINISH 	: APVD R.GROSS PRODUCT SPEC — APPLICATION SPEC — WEIGHT _	APVD 11-13-00 NAME   R.GROSS RECEPTACLE ASSY, AMPLIMITE, SERIES 90   SIZE 22, ZINC PLATED WITH   APPLICATION SPEC #4-40 CLINCH NUTS   SIZE CAGE CODE DRAWING NO   WEIGHT A1 00779 C=1218747							
						CUSTOMER D	RAWING		SCALE 1	:1 SHEET OF REV 1 1 B

А

1. THE CONNECTORS DES ANY PLUG CONNECTOR A MARKED WITH .047 [ FAR SIDE REFERS TO NEAR SIDE REFERS TO IF THE FRONT SHELL IS CODE, THEN SPLIT AS A. AMP PART NUMBER ON REAR SHELL, NEAR SIDE. B. "AMP" AND DATE CODE ON FRONT SHELL, NEAR SIDE.

3

Δ

—SHELL, FRONT & REAR Matl: steel per astm—a—109 or equivalent FINISH: ZINC PLATED .000200 [0.0050] MIN THICK PER ASTM-B-633; YELLOW CHROMATE MAT'L: POLYESTER PER MIL-M-24519, TYPE: GLCP-30F Color: black

2					1						
	LOC	DIST	REVISIONS								
-   -			P LTR			DESCRIPTION		DATE	DWN	APVD	
				В	REV PER ECO-	11-022285	10NOV11	ΡY	RL		
SCRIBED IN R WITH THE 1.19]062	SAME	INSE	ER	r af	RRANGEMEN	Τ.					
THE WIDE S THE NARRO	SĪDE OW S	OF T IDE C	THE DF	t Ke The	EYSTONE. E KEYSTONI	Ξ.					

В

С

## **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity: <u>1218747-6</u>