

С

В

4805 (3/11)

SEE CALLOUTS

	LOC										
			P LTR	REVISE		DESCRIPT			date 09NOV15	dwn KG	APVD CD
WITH NGEME	NT.	L		REVISE	U PER E	0-13-016	062		0910013		
SIDE R		S									
TO TH	E NAF	RROW									
CAN E	SE SP										
NLY T[] -6	□R -1	12),								
70-2.	MUST	BE D	IRDEI	RED	SEP	ARATEI	LY,				
N 204	370-2	PAC	KAGE	ID IN	N A	SEPAR	ATE				
										2	
										2/-	1
									4 PL	_C	
					+						
Ð	7			(
Ð					\oplus						
		+									
	I)IM H									
		v Z -	_7								
	VIL V	V <u> </u>									
Δ.											
5 5 5 1 2 1 2 1 2 1 2 1 2 1 2 1 2 1 2 1) PIN (CONTAC	Т								
SIZE 20 Materia	AL: COF	PPER A	LLOY				9 & MIL-		4308.		
SIZE 20 Materia	AL: COF G: GOLI	PPER A) per	LLOY				9 & MIL- Jver Ni(4308,		
SIZE 20 Materia Platin(AL: COF G: GOLI	PPER A) per	LLOY						4308.		
SIZE 20 Materia Platin(AL: COF G: GOLI	PPER A) per	LLOY						4308.		
SIZE 20 Materia Platin(AL: COF G: GOLI	PPER A) per	LLOY						4308.		
SIZE 20 Materia Platin(AL: COF G: GOLI	PPER A) per	LLOY						4308.		
SIZE 20 Materia Platin(AL: COF G: GOLI	PPER A) per	LLOY						4308.		
SIZE 20 Materia Platin(AL: COF G: GOLI	PPER A) per	LLOY						24308,		
IZE 20 1ateria Platin(AL: COF G: GOLI	PPER A) per	LLOY						24308,		
IZE 20 1ateria Platin(AL: COF G: GOLI	PPER A) per	LLOY						24308,		
IZE 20 1ATERIA 2LATINO 2ER QQ 56.31] 56.06]	AL: COF G: GOLI -N-290 2.744 2.714	PPER A D PER D, E69.70 E68.94	LLOY ASTM-					CKEL	-17578	325-	-2
IZE 20 1ATERI 2LATINO 2ER QQ 56,311 56.061 52,931 52,681	AL: COF G: GOLI -N-290 2.744 2.714 2.650 2.620	PPER A D PER D, [69.70 [68.94 [67.31 [66.55	D) M	-B-48	38 (T`)4-1	YPEII) [JVER NIC	CKEL 1			
IZE 20 ATERIA PLATINO PER QQ 56.31] 56.06] 52.93] 52.68] 52.55] 55.30]	AL: COF G: GOLI -N-290 2.744 2.714 2.650 2.620 2.744 2.714	PER A D PER D E69.70 E68.94 E67.31 E66.55 E69.70 E68.94	ASTM-	-B-48 S1400	38 (T`)4-1 77-2	YPEII> (104	JVER NIC	CKEL 1	.–17578	325-	-1
IZE 20 1ATERIA 2LATINO 2ER QQ 56.311 56.061 52.681 52.681 52.551 52.551 52.551 52.551 52.551 52.551 52.551 52.551 52.551 52.551 52.551 52.301	AL: COF G: GOLI -N-290 2.744 2.714 2.650 2.744 2.714 2.620 2.744 2.714 2.103 2.073	PER A D PER D PER	D] M D] M D] M D] M	-B-48 S1400 S1827	38 (T`)4-1 77-2 76-2	YPEII) [104 78	G G S	CKEL 1 1	.–17578	325- 325-	-1 -0
56.31 52.68 55.55 52.68 52.68 52.68 52.68 52.68 52.68 52.68 52.68 52.68 52.68 55.55 52.80 52.81 52.93 52.68 55.55 55.30	AL: COF G: GOLI -N-290 2.744 2.714 2.650 2.620 2.744 2.714 2.103 2.073 1.556 1.526	PER A D PER D PER D D E69.70 E68.94 E67.31 E66.55 E69.70 E68.94 E53.42 E53.42 E53.42 E53.42 E53.42 E53.42 E53.42	ASTM-	-B-48 S1400 S1827 S1827	38 (T`)4-1 77-2 76-2 75-2	YPEII> (104 78 62		CKEL 1 1 1 1	17578 17578 17578	325- 325- 5-9	-1 -0
56.31 52.93 55.30 52.30 52.30 52.30 52.30 52.30 52.30 52.30 52.30 52.30 52.30 52.30 52.30 52.30 52.30 52.30 52.30 52.31 52.32 55.30 52.32 55.30 52.32 55.32	AL: COF G: GOLI -N-290 2.744 2.714 2.650 2.744 2.714 2.650 2.744 2.714 2.073 1.556 1.526 1.526 1.526 1.228 1.198	PER A D PER D PER D D E69.70 E68.94 E67.31 E66.55 E69.70 E68.94 E53.42 E52.65 E39.52 E39.52 E39.52 E39.52 E39.52 E39.52 E39.52	DI M DI M DI M DI M	-B-48 S1400 S1827 S1827 S1827	38 (T`)4-1 77-2 76-2 75-2 74-2	YPEII) (104 78 62 44		CKEL 1 1 1 1 1	17578 17578 175782	325- 325- 5-9 5-8	-1 -0
IZE 20 ATERIA LATINO PLATINO PER QQ 56.31] 56.06] 52.68] 52.68] 52.68] 52.68] 55.55] 39.09] 38.84] 25.12] 7.04] 6.79] 56.31] 56.06]	AL: COF G: GOLI -N-290 2.744 2.714 2.650 2.744 2.714 2.650 2.744 2.714 2.103 2.073 1.556 1.526 1.526 1.526 1.526 1.526 1.528 1.198 2.744 2.714	PER A D PER D PER D D E69.70 E68.94 E67.31 E66.55 E69.70 E68.94 E53.42 E52.65 E39.52 E	DI M DI M DI M DI M	-B-48 S1400 S1827 S1827 S1827 S1827	38 (T))4-1 77-2 76-2 75-2 74-2 73-2	YPEII) [104 78 62 44 26		CKEL 1 1 1 1 1 1 1	-17578 -175782 75782	325- 325- 5-9 5-8 5-7	-1
TZE 20 ATERIA PLATINO PER QQ 56.311 56.061 52.681 55.551 39.091 38.841 55.371 55.301 39.091 38.841 55.371 55.301 39.091 38.841 55.371 55.3001 55.301 55.301 55.301 55.301 55.3	AL: COF G: GOLI -N-290 2.744 2.714 2.650 2.744 2.714 2.650 2.744 2.714 2.073 1.556 1.526 1.526 1.228 1.198 2.744 2.744 2.714 2.650 2.744 2.714	PER A D PER D PER	LLUY ASTM-	-B-48 S1400 S1827 S1827 S1827 S1827 S1827	38 (T))4-1)7-2 76-2 75-2 74-2 73-2)4-1	YPEII> (104 78 62 44 26 15		CKEL 1 1 1 1 1 1 1 1	-17578 -175782 .75782	325- 325- 5-9 5-8 5-7 5-6	-1
TZE 20 ATERIA PLATINO PER QQ 56.31] 56.06] 52.93] 55.55] 55.30] 39.09] 38.84] 55.55] 55.37] 55.30] 39.09] 38.84] 55.55] 55.30] 55.30] 52.93] 55.55] 52.93] 55.55] 55.30]	AL: COF G: GOLI -N-290 2.744 2.714 2.650 2.744 2.714 2.650 2.744 2.714 2.073 1.556 1.526	PER A D PER D PER	ASTM- ASTM-	-B-48 S1400 S1827 S1827 S1827 S1827 S1827 S1827	38 (T))4-1 77-2 76-2 75-2 74-2 73-2)4-1 77-2	YPEII> (104 78 62 44 26 15 104		CKEL 1 1 1 1 1 1 1 1 1 1	-175782 -175782 .75782 .75782	325- 325- 5-9 5-8 5-7 5-6 5-5	-1
SIZE 20 ATERIA PLATINO PER QQ 56.311 56.061 52.681 55.551 55.301 39.091 38.841 55.371 55.301 39.091 39.091 39.091 39.091 39.091 39.091 39.091 39.091 39.091 39.091	AL: COF G: GOLI -N-290 2.744 2.714 2.650 2.744 2.714 2.650 2.744 2.714 2.650 1.526 1.556 1.556 1.567 1.556 1.567 1.576 1	PER A PER A PER PER PER PER PER PER PER PER PER PER	ASTM- ASTM- ASTM-	-B-48 S1400 S1827 S1827 S1827 S1827 S1827 S1827 S1827 S1827	38 (T))4-1 77-2 76-2 74-2 73-2)4-1 77-2 76-2 76-2	YPEII> (104 78 62 44 26 15 104 78		CKEL	17578 17578 17578 .75782 .75782 .75782 .75782	325- 325- 5-9 5-8 5-7 5-6 5-5 5-4	-1
SIZE 20 MATERIA PLATINO PER QQ 56.311 56.061 552.681 555.301 39.091 38.841 55.371 56.311 56.361 552.681 552.681 552.681 552.681 552.551 555.55	AL: COF G: GOLI -N-290 2.744 2.714 2.650 2.744 2.714 2.650 2.744 2.714 2.650 2.744 2.714 2.650 1.526 1.526 1.526 1.526 2.744 2.714 2.650 2.744 2.714 2.650 2.744 2.714 2.650 2.744 2.714 2.650 2.744 2.714	PER A D PER D PER	ASTM- ASTM- ASTM- D M D M D M D M D M D M D M D M	-B-48 S1400 S1827 S1827 S1827 S1827 S1827 S1827 S1827 S1827	38 (T))4-1)7-2 76-2 75-2)4-1)4-1 77-2 76-2 75-2)4-1	YPEII> (104 78 62 44 26 15 104 78 62 42 62		CKEL	-17578 -175782 .75782 .75782 .75782 .75782	325- 325- 5-9 5-8 5-7 5-6 5-5 5-4 5-3	-1
TZE 20 ATERIA PLATINO PER QQ 56.311 56.061 52.681 55.551 55.551 55.551 56.061 52.681 55.551 55.551 55.551 55.551 55.551 55.551 55.551 55.551 55.551 55.551 55.551 55.551 55.551 55.551 55.551 55.551 55.301 7.041 7.041 7.041 7.041 7.041 7.041 7.041 7.041 7.041 7.041	AL: COF G: GOLI -N-290 2.744 2.714 2.650 2.744 2.714 2.650 2.744 2.714 2.650 1.526 1.526 1.526 1.526 1.526 2.744 2.714 2.714 2.650 2.744 2.714 2.714 2.650 2.744 2.714 2.714 2.650 2.744 2.714 2.650 2.744 2.714 2.714 2.650 2.744 2.714 2.714 2.650 2.744 2.714 2.714 2.650 1.526 1.526 1.526 1.526	PER A PER A PER PER PER PER PER PER PER PER PER PER	LLUY ASTM- ASTM- DI M DI M DI M DI M DI M DI M DI M DI M DI M DI M	-B-48 S1400 S1827 S1827 S1827 S1827 S1827 S1827 S1827 S1827 S1827 S1827 S1827 S1827 S1827 S1827	38 (T) 38 (T) 38 (T) 34-1 77-2 76-2 74-2 73-2 74-1 77-2 75-2 74-2 73-2 74-2 73-2 74-2 73-2 74-2 73-2	YPEII> (104 78 62 44 26 15 104 78 62 44 26 15 104 78 62 44 26 15 104 78 62 15 104 15 104 15 104 15 104 15 104 15 104 15 104 15 104 15 104 15 104 15 15 104	SVER NIC 6 5 4 3 2 1 6 5 4 3 2 1 5 4 3 2 1 1 3 2 1	CKEL	-175782 -175782 175782 .75782 .75782 .75782 .75782 .75782 .75782	325- 325- 5-9 5-8 5-7 5-6 5-5 5-4 5-3 5-2	-1
SIZE 20 MATERIA PLATINO PER QQ 56.311 56.061 55.551 55.301 39.091 38.841 55.371 56.061 55.301 39.091 38.841 55.371 55.301 55.301 55.301 39.091 38.841 55.371 55.301 39.091 38.841 55.371 55.371 55.371 25.371	AL: COF G: GOLI -N-290 2.744 2.714 2.650 2.744 2.714 2.650 2.744 2.714 2.650 1.526 1.526 1.526 1.526 1.526 2.744 2.714 2.714 2.650 2.744 2.714 2.714 2.650 2.744 2.714 2.714 2.650 2.744 2.714 2.650 2.744 2.714 2.714 2.650 2.744 2.714 2.714 2.650 2.744 2.714 2.714 2.650 1.526 1.526 1.526 1.526	PER A PER A PER PER PER PER PER PER PER PER PER PER	ASTM- ASTM- ASTM-	-B-48 S1400 S1827 S1827 S1827 S1827 S1827 S1827 S1827 S1827 S1827 S1827 S1827 S1827	38 (T) 38 (T) 38 (T) 38 (T) 34-1 77-2 76-2 74-2 73-2 74-2 73-2 74-2 73-2 74-2 73-2 74-2 73-2 74-2 73-2 74-2 73-2 73-2	YPEII) (104 78 62 44 26 15 104 78 62 44 26 44 26 44 26	SVER NIC 6 5 4 3 2 1 6 5 4 3 2 1 6 5 4 3 2 1 5 4 3 2 1 1 6 5 4 3 2 2 1	CKEL	-175782 -175782 175782 .75782 .75782 .75782 .75782 .75782 .75782 .75782 .75782	325- 325- 5-9 5-8 5-7 5-6 5-5 5-4 5-3 5-2 5-1	-1
SIZE 20 MATERIA PLATINO PER QQ 56.311 56.061 52.931 55.551 55.301 39.091 38.841 25.371 56.061 52.931 55.551 55.301 39.091 38.841 55.371 55.301 39.091 38.841 55.371 55.301 39.091 38.841 55.371 55.301 39.091 38.841 55.371 55.301 39.091 38.841 55.371 55.301 39.091 38.841 55.371 55.371 55.301 39.091 38.841 55.371 55.301 39.091 38.841 55.371 55.301 39.091 38.841 55.371	AL: COF G: GOLI -N-290 2.744 2.714 2.650 2.744 2.714 2.650 2.744 2.714 2.650 2.744 2.714 2.650 2.744 2.714 2.650 2.744 2.714 2.650 2.744 2.714 2.650 2.744 2.714 2.650 2.744 2.714 2.650 2.744 2.714 2.650 2.744 2.714 2.650 2.744 2.714 2.650 2.744 2.714 2.650 2.744 2.714 2.650 2.744 2.714 2.714 2.714 2.714 2.714 2.714 2.714 2.756 1.556 1.556 1.526	PER A PER A PER PER PER PER PER PER PER PER	LLUY ASTM- ASTM- DI M DI M	-B-48 S1400 S1827 S1877 S1777 S1777 S1777 S1777 S1777 S1777 S1777 S1777 S1777 S1777 S1777 S1777 S17777 S17777 S17777 S17777 S177777 S17777777777	38 (T) 38 (T) 38 (T) 34-1 77-2 76-2 74-2 73-2 74-2 73-2 74-2 73-2 74-2 73-2 74-2 73-2 74-2 73-2 74-2 73-2 74-2 73-2	YPEII) (104 78 62 44 26 15 104 78 62 44 26 15 104 78 62 44 26 15 104 78 62 44 26 15 ND DF	SHELL SIZE	CKEL	17578 17578 17578 175782 .75782 .75782 .75782 .75782 .75782 .75782 .75782 .75782 .75782 .75782 .75782	325- 325- 5-9 5-8 5-7 5-6 5-7 5-6 5-2 5-1 MBEF	-1
SIZE 20 MATERIA PLATINO PER QQ 56.311 56.363 55.301 39.091 38.841 25.371 56.311 56.311 55.301 39.091 38.841 55.301 39.091 38.841 55.301 39.091 38.841 55.301 39.091 38.841 55.301 39.091 38.841 25.371 7.041 6.791 38.841 25.371 7.041 6.791 38.841 25.371 7.041 6.791	AL: COF G: GOLI -N-290 2.744 2.714 2.650 2.744 2.714 2.650 2.744 2.714 2.650 2.744 2.714 2.650 2.744 2.714 2.650 2.744 2.714 2.650 2.744 2.714 2.650 2.744 2.714 2.650 2.744 2.714 2.650 2.744 2.714 2.650 2.744 2.714 2.650 2.744 2.714 2.650 2.744 2.714 2.650 2.744 2.714 2.650 2.744 2.714 2.714 2.714 2.714 2.714 2.714 2.714 2.756 1.556 1.556 1.526	PER A PER A PER A PER PER PER PER PER PER PER PER	L L I Y A S T M- A S T M- D M D M D M D M D M D M D M D M D M D M D M D M D M D M D M D M D M D M D M M </td <td>-B-48 S1400 S1827 S1877 S1777 S1777 S1777 S1777 S1777 S17777 S17777 S17777 S17777 S17777 S1777777 S17777777777</td> <td>38 (T) 38 (T)</td> <td>YPEII> (104 78 62 44 26 15 104 78 62 44 26 15 104 78 62 44 26 15 ND DF PDS</td> <td>JVER NIG 6 5 4 3 2 1 6 5 4 3 2 1 6 5 4 3 2 1 5 4 3 2 1 SHELL SIZE</td> <td>CKEL 1 1 1 1 1 1 1 1 1 1 1 1 1</td> <td>17578 17578 17578 17578 </td> <td>325- 325- 5-9 5-8 5-7 5-6 5-5 5-4 5-3 5-2 5-1 MBEF</td> <td>-1</td>	-B-48 S1400 S1827 S1877 S1777 S1777 S1777 S1777 S1777 S17777 S17777 S17777 S17777 S17777 S1777777 S17777777777	38 (T) 38 (T)	YPEII> (104 78 62 44 26 15 104 78 62 44 26 15 104 78 62 44 26 15 ND DF PDS	JVER NIG 6 5 4 3 2 1 6 5 4 3 2 1 6 5 4 3 2 1 5 4 3 2 1 SHELL SIZE	CKEL 1 1 1 1 1 1 1 1 1 1 1 1 1	17578 17578 17578 17578 	325- 325- 5-9 5-8 5-7 5-6 5-5 5-4 5-3 5-2 5-1 MBEF	-1
IZE 20 ATERIA PLATINO PER QQ 56.311 56.311 56.363 55.301 39.091 38.841 25.371 56.311 56.363 55.301 39.091 38.841 25.371 56.301 39.091 38.841 55.301 39.091 38.841 25.371 56.301 39.091 38.841 25.371 56.301 39.091 38.841 25.371 57.371 57.371 57.371 39.091 38.841 25.371 7.041 6.791 NTROLLED OTHERMISE 1 1 2	AL: COF G: GOLI -N-290 2.744 2.714 2.650 2.744 2.714 2.650 2.744 2.714 2.650 2.744 2.714 2.073 1.556 1.526 1.228 1.198 2.744 2.714 2.650 2.744 2.714 2.714 2.650 2.744 2.714 2.714 2.650 2.744 2.714 2.714 2.756 1.526 1.56	PER A PER A PER PER PER PER PER PER PER PER	LL I Y ASTM- ASTM- DI M M DI M M	-B-48 S1400 S1827 S1877 S1777 S1777 S1777 S1777 S1777 S1777 S1777 S1777 S1777 S1777 S1777 S1777 S1777 S1777 S17777 S17777 S17777 S17777 S177777 S17777777777	38 (T) 38 (T)	YPEII) (104 104 78 62 44 26 15 104 78 62 44 26 15 104 78 62 44 26 15 104 78 62 44 26 15 104 78 62 44 26 15 104	JVER NIG 6 5 4 3 2 1 6 5 4 3 2 1 6 5 4 3 2 1 SHELL SIZE	CKEL CKEL 1 1 1 1 1 1 1 1 1 1 1 1 1		325- 325- 5-9 5-8 5-7 5-6 5-5 5-4 5-3 5-2 5-1 MBEF	-1
SIZE 20 MATERIA PLATINO PER QQ SEC 31 SEC 31	AL: COF G: GOLI -N-290 2.744 2.714 2.650 2.744 2.714 2.650 2.744 2.714 2.650 2.744 2.714 2.073 1.556 1.526 1.228 1.198 2.744 2.714 2.650 2.744 2.714 2.714 2.650 2.744 2.714 2.714 2.650 2.744 2.714 2.714 2.756 1.526 1.56	PER A PER A PER A PER PER PER PER PER PER PER PER	L L I Y A S T M- A S T M- D M D M D M D M D M D M D M D M D M D M M	-B-48 S1400 S1827 S1877 S1777 S1777 S1777 S1777 S1777 S1777 S1777 S1777 S1777 S1777 S1777 S1777 S1777 S1777 S17777 S17777 S17777 S17777 S177777 S17777777777	38 (T) 38 (T)	YPEII> [104 78 62 44 26 15 104 78 62 44 26 15 104 78 62 44 26 15 N□ □F P□S AMPLIMI SER AMPLIMI	JVER NIG 6 5 4 3 2 1 6 5 4 3 2 1 6 5 4 3 2 1 SHELL SIZE	CKEL CKEL 1 1 1 1 1 1 1 1 1 1 1 1 1		325- 325- 5-9 5-8 5-7 5-6 5-5 5-4 5-2 5-1 MBEF	-1

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity: 1757825-3