



## **Product Description**

Security & Sound Cable, Plenum-CMP 8-22 AWG stranded bare copper conductors with Flamarrest® insulation, Flamarrest® jacket with ripcord

## **Technical Specifications**

## **Product Overview**

| Suitable Applications: | Security System, Intercom/PA, Audio/Speaker, Power-Limited Controls |  |
|------------------------|---|--|

## **Physical Characteristics (Overall)**

#### Conductor

| AWG   | Stranding   | Material         | No. of Conductors |
|-------|-------------|------------------|-------------------|
| 22    | 7x30        | BC - Bare Copper | 8                 |
| Condu | ctor Count: |                  | 8                 |

#### Insulation

| Material                 | Material Trade Name | Nominal Wall Thickness |
|--------------------------|---------------------|------------------------|
| PVC - Polyvinyl Chloride | Flamarrest®         | 0.009 in               |

## Color Chart

| Color  |  |
|--------|--|
| Black  |  |
| Red    |  |
| White  |  |
| Green  |  |
| Brown  |  |
| Blue   |  |
| Orange |  |
| Yellow |  |
|        |  |

#### **Outer Shield Material**

Material No Shield

## Outer Jacket Material

| Material                 | Material Trade Name | Nominal Diameter | Nominal Wall Thickness | Ripcord |
|--------------------------|---------------------|------------------|------------------------|---------|
| PVC - Polyvinyl Chloride | Flamarrest®         | 0.186 in         | 0.015 in               | Yes     |

## **Electrical Characteristics**

#### Conductor DCR

Nominal Conductor DCR 16.2 Ohm/1000ft

## Capacitance

Nom. Capacitance Conductor to Shield

25 pF/ft

#### Current

| Max. Recommended Current [A] |
|------------------------------|
| 2 Amps per Conductor at 25°C |

#### Voltage

UL Voltage Rating 300 V RMS

#### **Temperature Range**

| Operating Temp Range: | 0°C To +75°C |
|-----------------------|--------------|
|                       |              |

## **Mechanical Characteristics**

| Bulk Cable Weight:          | 28.7 lbs/1000ft |
|-----------------------------|-----------------|
| Max. Pull Tension:          | 72.8 lbs        |
| Min Bend Radius/Minor Axis: | 1.8 in          |

#### Standards

| NEC/(UL) Compliance:  | СМР |
|-----------------------|-----|
| CEC/C(UL) Compliance: | CMP |

## **Applicable Environmental and Other Programs**

| EU Directive 2000/53/EC (ELV):          | Yes                                  |
|---|--------------------------------------|
| EU Directive 2003/96/EC (BFR):          | Yes                                  |
| EU Directive 2011/65/EU (ROHS II):      | Yes                                  |
| EU Directive 2012/19/EU (WEEE):         | Yes                                  |
|   |                                      |
| EU Directive Compliance:                | EU Directive 2003/11/EC (BFR)        |
| EU Directive Compliance:<br>EU CE Mark: | EU Directive 2003/11/EC (BFR)<br>Yes |
|   | Yes                                  |

### Flammability, LS0H, Toxicity Testing

| C(UL) Flammability: | FT6                                |
|---------------------|------------------------------------|
| UL Flammability:    | NFPA 262 Plenum Flame Test (UL910) |
| UL voltage rating:  | 300 V RMS                          |

#### Plenum/Non-Plenum

| Plenum (Y/N):      | Yes    |
|--------------------|--------|
| Part Number        |        |
| Non-Plenum Number: | 5506UE |

#### Variants

|   | rananto         |         |              |
|---|-----------------|---------|--------------|
|   | ltem #          | Color   | UPC          |
| ľ | 6506UE 8771000  | Natural | 612825178002 |
| ľ | 6506UE 877U1000 | Natural | 612825177982 |
| ľ | 6506UE 877U500  | Natural | 612825177999 |
| Ì | Footnote:       |         |              |
| l | , council.      |         |              |

#### **History**

Update and Revision:

Revision Number: 0.217 Revision Date: 06-24-2020

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.

# **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Belden Wire & Cable: <u>6506UE 8771000</u>