0

	1 2		3	4			
		wall thickness	length of cut-out	width of cut-out			
	recommended cut-out for snap-in fixing	0.75 to 1.25	30.0 -0.1	11 +0.1			
Α	(edge opposite to snap-in direction)	1.25 to 2 2 to 3	30.2 -0.1 30.6 -0.1	11 +0.1 11 +0.1			
		2 10 3	30.0 -0.1	11 70.1			
	\ ⁷²		11 ±	±0.1			
В		A 41	ا م				
		4.0					
	71	- N		16.35			
	1a 1	1b .	붜				
			→	<u> </u>			
	9.5	Ą	terminal /	_			
	 • • 		6.3-0.8	.7			
C	27.2						
		\					
		red transp.					
	47						
-	Marking:	black					
	1830. 31.5	Diack					
D	10(8)/250~5E4						
	20(4)/250~ T85/55 5/120A 250V~						
	5/12UA 25UV~	10					
		¹ _———		1:1			
	16A 250V AC) - 1b					
	1HP R142 91 (B)	1					
SPST Neon lamp with Rv for 230V ac							
	Suitab	ole for appliances of					
	Code of manufacture: place/year/week			Die			
	piace/yeai/week						
			-	1830.3112-XX			
	Figure Type		Customer Part No.	Art.NoPI Document number Index			
	Angle ± 2 ° Length 0-6 ± 0.2 ±	Radii Sheet	01				
•	Snape and Fdgg talorongs >6-30 ± 0.4 ±		jection Scale K	18303112 f			

-	20701			Edited by		Zg.gl.Nr.v.28.03.1994			MARQUARDT			
С	23781	1996-01-22		GRH		Replacement of		f				
d	32181	2001-08-09		GRH		Oystelli NA V 1072		012	(M)			
е	47286	2006-04-27		HHE		are in millimetres System NX V1872		872				
f	138244	2021-08-06		MATHPATIR				es				
		<u>±</u>	±		<u>±</u>	All dimensions			Appliance Switch			
⊚ =		<u>†</u>	<u>±</u>		<u>±</u>	1 / \ 7	7 \$		Annlianaa Owitah			
		<u>±</u>	<u>±</u>		<u>±</u>	A4		1:1		<u> </u>		1
location	ii Luge tolerance	>30 <u>±</u> 0.6	<u>+</u>	>30	± 0.6	DIN	Trojection	Julie	'			'
Shape ar location		>6-30 ± 0.4	<u>±</u>	>6-30	± 0.4	Format	Projection	Scale	cale K	18303112	l f	
	Angle ± 2 °	Length 0-6 ± 0.2 ±		0-6	Radii 0-6 ± 0.2		Sheet 01					
						0.1			ldent. D		cument number	Index
Figur	re	Туре					Custor			ustomer Part No. Art.NoPI		
-									-		1830.3112-XX	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Marquardt: 01830.3112-02