(0)

	,			I		T		
	1 2				3		4	
A	recommended cut-out for snap-in fixing (edge opposite to snap-in direction)			thickness	length of cu	ut-out	width of cut-out	
				75 to 1.25	30.0 -0.1		11 +0.1	
				25 to 2	30.2 -0.	.1	11 +0.1	
			2 to 3	30.6 -0.	.1	11 +0.1		
		\7	11 ±0.1					
В			<u> </u>	41		= ہ	<u>-</u> n	
	#	/II — —	6.4					
	~1	(N-)	- <i> </i>)				16.35	
			1	H	→ ₩			
					•			
		U 0.	.8		4	•	<u> </u>	
		9.5			Ø2.4			
С								
		27.2						
			_					
		∕— wh	nite 🕏	/				
	-							
	14							
	Marking:		29.	— black				
	marking.	31.5						
l d l	4004	ال ال						

1831. 10(8)/250~5E4 20(4)/250~ T105/55 5/120A 250V~

16A 125-250V AC 1/3 HP 125V AC 1 HP 250V AC

10 LR R11 Code of manufacture: place/year/week



SPST Suitable for appliances of class II



								-		1831.0114-XX			
Figure	е	Туре							Customer Part No.		Art.NoPI	Art.NoPI	
						01			ldent.		cument number	Index	
	Angle ± 2 °			Radii	Sheet	Sheet 01							
Shape an location	d	0-6 ± 0.2 >6-30 ± 0.4 >30 ± 0.6	± ± ±	0-6 >6-30 >30	± 0.2 ± 0.4 ± 0.6	Format DIN	Projection	Scale	K	18310114		С	
		± ± ± ±	± ± ±		± ± ±	A4	A4 1:1		Appliance Switch				
		<u>†</u>	<u>±</u> ±		<u>±</u> ±	All dimensions are in millimetres							
С	138244	2021-08-06		MATHPATIR		System NX V1872		872					
b	47099	2006-04-18		HHE		Oystom NA VIUIZ		012	' (M)				
а	23781	1996-01-29		GRH		Replacement of		ıf					
Index	MEC-No.	Date (YYYY-MM-DD)		Edited by		Zg.gl.Nr.v.25.09.1995		995	MARQUARDT				
	•				· ·					•			

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Marquardt: 01831.0114-02