

Switchtec PFX-L Fanout-Lite PCIe Gen3 Switch Family

PM8566, PM8565, PM8564, PM8563, PM8562, and PM8561

The Switchtec PFX-L Fanout-Lite PCIe Gen3 Switch Family is composed of PCIe Base Specification 3.1-compliant switches supporting up to 96 lanes, six virtual switch partitions, two non-transparent bridges (NTBs), six hot-plug controllers, and comprehensive diagnostics and debug capabilities.

Typical applications for the PFX-L include data center equipment, defense and industrial servers, workstations, test equipment, video production and broadcasting equipment, cellular infrastructure, access networks, metro networks, and core networking.

Features

High-Performance Non-Blocking Switches

- Up to 174 GB/s switching capacity
- 96-lane, 80-lane, 64-lane, 48-lane, 32-lane, and 24-lane variants
- Ports bifurcate to x4/x8/x16 lanes
- Up to two NTBs assignable to any port
- Logical non-transparent (NT) interconnect allows for larger topologies
- Supports 1+1 and N+1 failover mechanisms
- NT address translation using direct windows and multiple sub-windows per BAR
- Supports multicast groups per port

Error Containment

- Advanced Error Reporting (AER) on all ports
- Hot-plug controllers
- GPIOs configurable for different cable/connector standards

PCIe Interfaces


- Passive, managed, and optical cables
- SHPC-enabled slot and edge connectors

Diagnostics and Debug

- Transaction Layer Packet (TLP) generator for testing and debugging of links and error handling
- Real-time eye capture
- Any-to-any port mirroring for debug purposes
- External loopback at PHY and TLP layers
- Errors, statistics, performance, and TLP latency counters

Peripheral I/O Interfaces

- Up to two (master/slave) two-wire interfaces (TWIs) with SMBus support
- Up to 78 parallel GPIO pins
- 1 UART
- 1 QSPI with optional inline ECC
- JTAG and EJTAG interface



Highlights

- Hot-plug controllers, end-to-end data integrity protection, high-quality, and low-power fifth-generation SERDES
- Comprehensive diagnostics and debugging: PCIe generator and analyzer, per-port performance and error counters, multiple loopback modes, and real-time eye capture
- Up to 24 ports, two NTBs, and six virtual switch partitions
- Flexible x4, x8, and x16 port bifurcation with no restrictions on configuring ports as either upstream or downstream, or on mapping ports to NTBs

Switchtec PFX-L Fanout-Lite PCIe Gen3 Switch Family

PM8566, PM8565, PM8564, PM8563, PM8562, and PM8561

High-Speed I/O

- PCIe Gen3 8 GT/s
- Supports PCIe-compliant link training and manual PHY configuration

Power Management

- Active State Power Management (ASPM)
- Software controlled power management

Chiplink Diagnostic Tools

- Extensive debug, diagnostics, configuration, and analysis tools with an intuitive GUI
- Access to configuration data, management capabilities, and signal integrity analysis tools (such as real-time eye capture)
- Connects to device over in-band PCIe or sideband signals (UART, TWI, and EJTAG)

Evaluation Kit


The evaluation kit is a device evaluation environment supporting multiple host and SSD interfaces. The following kits are available for evaluating PFX, PSX, and PFX-L features using the populated PSX 96xG3 device on the PM5461-KIT and the PSX 48xG3 device on the PM5462-KIT:

- PM5461-KIT — PSX/PFX/PFX-L 96/80/64xG3, 1-Slot, 16 HD Evaluation Kit (PMC-2151996)
- PM5462-KIT — PSX/PFX/PFX-L 48/32/24xG3, 3-Slot Evaluation Kit (PMC-2151645)

Ordering Information

Product	Lanes	Ports/NTBs	Virtual Switch Partitions	Hot-Plug Controllers	Package	Ordering Number
PFX-L 96xG3	96	24/2	6	6	37.5 mm × 37.5 mm	PM8566B-FEI
PFX-L 80xG3	80	20/2	6		37.5 mm × 37.5 mm	PM8565B-FEI
PFX-L 64xG3	64	16/2	6		37.5 mm × 37.5 mm	PM8564B-FEI
PFX-L 48xG3	48	12/2	6		27 mm × 27 mm	PM8563B-F3EI
PFX-L 32xG3	32	8/2	4		27 mm × 27 mm	PM8562B-F3EI
PFX-L 24xG3	24	6/2	3		27 mm × 27 mm	PM8561B-F3EI

Example Application



Microsemi Corporate Headquarters
 One Enterprise, Aliso Viejo, CA 92656 USA
 Within the USA: +1 (800) 713-4113
 Outside the USA: +1 (949) 380-6100
 Fax: +1 (949) 215-4996
 Email: sales.support@microsemi.com
 www.microsemi.com

Microsemi Corporation (Nasdaq: MSCC) offers a comprehensive portfolio of semiconductor and system solutions for aerospace & defense, communications, data center and industrial markets. Products include high-performance and radiation-hardened analog mixed-signal integrated circuits, FPGAs, SoCs and ASICs; power management products; timing and synchronization devices and precise time solutions, setting the world's standard for time; voice processing devices; RF solutions; discrete components; enterprise storage and communication solutions, security technologies and scalable anti-tamper products; Ethernet solutions; Power-over-Ethernet ICs and midspans; as well as custom design capabilities and services. Microsemi is headquartered in Aliso Viejo, California and has approximately 4,800 employees globally. Learn more at www.microsemi.com.

Microsemi makes no warranty, representation, or guarantee regarding the information contained herein or the suitability of its products and services for any particular purpose, nor does Microsemi assume any liability whatsoever arising out of the application or use of any product or circuit. The products sold hereunder and any other products sold by Microsemi have been subject to limited testing and should not be used in conjunction with mission-critical equipment or applications. Any performance specifications are believed to be reliable but are not verified, and Buyer must conduct and complete all performance and other testing of the products, alone and together with, or installed in, any end-products. Buyer shall not rely on any data and performance specifications or parameters provided by Microsemi. It is the Buyer's responsibility to independently determine suitability of any products and to test and verify the same. The information provided by Microsemi hereunder is provided "as is, where is" and with all faults, and the entire risk associated with such information is entirely with the Buyer. Microsemi does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other IP rights, whether with regard to such information itself or anything described by such information. Information provided in this document is proprietary to Microsemi, and Microsemi reserves the right to make any changes to the information in this document or to any products and services at any time without notice.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Microsemi:](#)

[PM8561B-F3EI](#) [PM8562B-F3EI](#)