


# LOW-PROFILE DUAL WIPE SOCKET

(1.27 mm) .050" PITCH • CLP SERIES



CLP Mates:

FTSH, FTS, FW

### **SPECIFICATIONS**

Insulator Material: Black Liquid Crystal Polymer
Contact Material: Phosphor Bronze
Plating:
Sn or Au over
50 µ" (1.27 µm) Ni
Current Rating (CLP/FTSH):
3.4 A per pin

3.4 A per pin

Voltage Rating: 280 VAC/395 VDC Operating Temp Range: -55 °C to +125 °C Insertion Depth:

Top Entry = (1.40 mm) .055" minimum (1.40 mm) .055" minimum Bottom Entry = (2.41 mm) .095" minimum plus board thickness DH Entry = (2.31 mm) .091"to (2.67 mm) .105" Normal Force: 60 grams (0.59 N) average

**Max Cycles:** 100 with 10 μ" (0.25 μm) Au

#### **PROCESSING**

Lead-Free Solderable:

Yes SMT Lead Coplanarity: (0.10 mm) .004" max (02-35) (0.15 mm) .006" max (36-50)\* \*(.004" stencil solution may be available; contact ipg@samtec.com)

## ALSO AVAILABLE MOQ Required

Single row Other platings



PER ROW

02 thru 50

**PLATING** OPTION

-F Gold flash on contact, Matte Tin

on tail

**-L** = 10 μ" (0.25 μm) Gold on contact, Matte Tin on tail

-G = 10 µ" (0.25 µm) Gold (-D only)

**ROW** OPTION

-D = Double Row -DH

= Double Horizontal (Requires FTSH-04 lead style)

-BE = Bottom Entry (Required for bottom entry applications)

**OTHER** 

**OPTIONS** 

-A

= Alignment Pin (Not available with -PA option) (05, 06, 07, 08, 10, 12, 15, 20, 25, 30, 40 positions only) (-DH option and other sizes. Contact Samtec.)


= (4.00 mm) .157" DIA Polyimide film Pick & Place Pad (3 positions minimum)


= Pick & Place Pad (5 positions min. –D only) (Not always necessary for auto placement. See Flex Processing.)

-PA = Pick & Place Pad with Alignment Pin
(-D only)
(Not available with -A option)

> -TR = Tape & Reel


-FR = Full Reel Tape & Reel (must order maximum quantity per reel; contact Samtec for quantity breaks)







Some lengths, styles and options are non-standard, non-returnable.



If odd pins/row, alignment pins are on middle position on centerline of the part. If even pins/row, then alignment pins are between middle two positions.



-PA OPTION



-P OPTION

### **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Samtec:

CLP-136-02-F-D-P