

RS 16AIO DP SD Z**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



Similar to illustration

The analogue interfaces are equipped with SubD connectors. Thus they offer sufficient shielding for analogue signal transmission. They are also equipped with very useful isolators and test sockets for measuring voltage or current.

General ordering data

| | |
|------------|---|
| Version | Interface, RS, 2-wire, Tension-clamp connection |
| Order No. | 1308270000 |
| Type | RS 16AIO DP SD Z |
| GTIN (EAN) | 4050118110623 |
| Qty. | 1 pc(s). |

Creation date January 22, 2022 11:56:11 AM CET

Catalogue status 14.01.2022 / We reserve the right to make technical changes.

RS 16AIO DP SD Z

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

| | | | |
|------------|--------|-----------------|------------|
| Depth | 72 mm | Depth (inches) | 2.835 inch |
| Height | 87 mm | Height (inches) | 3.425 inch |
| Width | 205 mm | Width (inches) | 8.071 inch |
| Net weight | 351 g | | |

Temperatures

| | | | |
|---------------------|-------------|-----------------------|-------------|
| Storage temperature | -40...60 °C | Operating temperature | -20...50 °C |
|---------------------|-------------|-----------------------|-------------|

Environmental Product Compliance

| | |
|------------|----------------|
| REACH SVHC | Lead 7439-92-1 |
|------------|----------------|

General data

| | | | |
|--------------------------------|--------|----------------------------------|---|
| LED status display per channel | No | Disconnection per channel | No |
| Voltage point of measurement | No | Current-measuring testpoint | No |
| Type of test point | No | LED status of the supply voltage | No |
| Power supply fuse | 3.15 A | Common pole polarity | Positive or negative can be selected using jumper |

Connection data

| | | | |
|-----------------------------|--------------------------------------|--------------------------------|---|
| Connection (field side) | LMNZF 5.08mm | Connection on control side | D-sub connectors, acc. to IEC 60807 / DIN 41652 |
| Connection supply | LMNZF 5.08mm | Number of poles (control side) | 37-pole plug |
| Protective earth connection | Shielding in SUB-D plug-in connector | Wiring system | 2-wire |

Ratings data

| | | | |
|--------------------------|---------------------|------------------------------|--------|
| Operating voltage | ≤ 25 V AC / 50 V DC | Max. current for common pole | 3.15 A |
| Max. current per channel | 0.5 A | | |

Insulation coordination (EN50178)

| | | | |
|-------------------------------|--------------|--------------------------|-----------|
| According to | DIN EN 50178 | Rated insulation voltage | < 50 V AC |
| Surge voltage category | III | Pollution severity level | 2 |
| Pulse voltage test (1,2/50µs) | 0.8 kV | Insulation test voltage | 0.35 kVAC |

Connection field

| | | | |
|----------------------------------|--------------------------|------------------------------|----------------------|
| Clamping range, max. | 2.5 mm ² | Clamping range, min. | 0.13 mm ² |
| Flexible with sleeve, max. | 2.5 mm ² | Flexible with sleeve, min. | 0.5 mm ² |
| Flexible, max. H05(07) V-K | 4 mm ² | Flexible, min. H05(07) V-K | 0.5 mm ² |
| Max. wire cross-section, AWG | AWG 12 | Min. wire cross-section, AWG | AWG 26 |
| Sleeve with plastic collar, max. | 2.5 mm ² | Solid, max. H05(07) V-U | 6 mm ² |
| Solid, min. H05(07) V-U | 0.5 mm ² | Stripping length | 6 mm |
| Tightening torque, max. | 0.6 Nm | Tightening torque, min. | 0.5 Nm |
| Type of connection | Tension-clamp connection | | |

RS 16AIO DP SD Z

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Supply connection

| | | | |
|------------------------------|--------------------------|-----------------------------------|----------------------|
| Type of connection | Tension-clamp connection | Clamping range, min. | 0.13 mm ² |
| Clamping range, max. | 2.5 mm ² | Solid, min. H05(07) V-U | 0.5 mm ² |
| Solid, max. H05(07) V-U | 6 mm ² | Flexible, min. H05(07) V-K | 0.5 mm ² |
| Flexible, max. H05(07) V-K | 4 mm ² | Flexible with sleeve, max. | 2.5 mm ² |
| Flexible with sleeve, min. | 0.5 mm ² | Ferrule with plastic collar, max. | 2.5 mm ² |
| Wire cross-section, min. AWG | AWG 26 | Wire cross-section, max. AWG | AWG 12 |
| Tightening torque, min. | 0.5 Nm | Tightening torque, max. | 0.6 Nm |
| Stripping length | 6 mm | | |

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 6.0 | EC002780 | ETIM 7.0 | EC002780 |
| ETIM 8.0 | EC002780 | ECLASS 9.0 | 27-14-11-52 |
| ECLASS 9.1 | 27-14-11-52 | ECLASS 10.0 | 27-14-11-52 |
| ECLASS 11.0 | 27-14-11-52 | | |

Approvals

Approvals



ROHS

Conform

Downloads

Approval/Certificate/Document of Conformity

[Declaration of Conformity](#)

Catalogues

[Catalogues in PDF-format](#)


Brochures

RS 16AIO DP SD Z

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Weidmuller:](#)

[1308270000](#)