
# PCI-1747U

## 250 kS/s, 16-bit, 64-ch Analog Input Universal PCI Card



#### **Features**

- 64-ch single-ended or 32-ch differential or a combination of analog input
- 16-bit A/D converter, with up to 250 kHz sampling rate
- Auto calibration
- Onboard FIFO memory (1,024 samples)
- PCI-Bus mastering data transfer
- Universal PCI Bus (support 3.3 V or 5 V PCI bus signal)
- BoardID<sup>™</sup> switch

ROHS FCC CE

### Introduction

PCI-1747U is a high-resolution, high-channel-count analog input card for the PCI bus. Its sampling rate is up to 250 kS/s and 16-bit resolution provides the resolution needed for most data acquisition applications. PCI-1747U provides 64 single-ended, 32 differential analog input channels or a combination of these. It also has built in a 1,024 FIFO buffer for analog input data.

## **Specifications**

#### **Analog Input**

• **Channels** 64 single-ended, 32 differential, or combination

Resolution 16 bits
Max. Sampling Rate 250 kS/s
FIFO Size 1,024 samples
Overvoltage Protection 30 Vp-p

■ Input Impedance  $100 \text{ M}\Omega/10 \text{ pF (Off)}; 100 \text{ M}\Omega/100 \text{ pF (On)}$ ■ Sampling Modes Software and onboard programmable pacer

Input Range (V, software programmable)

(,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,					
Unipolar	N/A	0 ~ 10	0 ~ 5	0 ~ 2.5	0 ~ 1.25
Bipolar	±10	±5	±2.5	±1.25	±0.625
Accuracy (% of FSR ±1LSB)	0.03	0.02	0.02	0.03	0.04

#### General

Bus Type
Universal PCI V2.2

I/O Connector
Dimensions (L x H)
1 x 68-pin SCSI female connector
175 x 100 mm (6.9" x 3.9")

■ **Power Consumption** Typical: 5 V @ 850 mA, 12 V @ 600 mA

Max.: 5 V @ 1 A, 12 V @ 700 m A

• Operating Temperature  $0 \sim 60^{\circ}$  C (32  $\sim 140^{\circ}$  F) (refer to IEC 68-2-1, 2)

• Storage Temperature  $-20 \sim 70^{\circ} \text{ C } (-4 \sim 158^{\circ} \text{ F})$ 

■ **Storage Humidity** 5 ~ 95% RH, non-condensing (refer to IEC 68-2-3)

## **Ordering Information**

■ **PCI-1747U** 250 kS/s, 16-bit, 64-ch Al Universal PCI Card

#### **Accessories**

ADAM-3968 68-pin DIN-rail SCSI Wiring Board
PCL-10168-1 68-pin SCSI Shielded Cable, 1 m
PCL-10168-2 68-pin SCSI Shielded Cable, 2 m

## **Pin Assignments**

AI8 01IA AI14 AGND AI15 AGND AI16 AI23 AT31 AI32 AI36 AI38 AI40 AI44 AI46 AI47 AGND AI49 AGND AI48 AI50 AI51 AI52 AI53 AI55 AI54 AI57 AI59 AI61 B5IA AI60

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Advantech: PCI-1747U-AE