

- 1. MATERIAL & FINISH:
- 1.1 BODY: NICKEL PLATED BERYLLIUM COPPER
- 1.2 COUPLING SLEEVE & CRIMP BUSHING: NICKEL PLATED BRASS
- 1.3 INSULATOR & DIELECTRIC: PTFE (TEFLON)
- 1.4 INTERMEDIATE CONTACT: GOLD PLATED BERYLLIUM COPPER
- 1.5 CENTER CONTACT: GOLD PLATED BRASS
- 1.6 GASKET: SILICONE RUBBER
- 2. ELECTRICAL:
- 2.1 FREQUENCY (MAX): 500 MHz
- 2.2 IMPEDANCE: NON-CONSTANT
- 3. TESTED PER TT-09 I.A.W. TCS-70
- 4. ASSEMBLE PER TAI-166.
- 5. EXAMPLE OF COMPLETE MODEL NUMBER:

5-0033 S-XXX

CABLE GROUP (SEE TABLE)

S = SAFETY W IRE AS REQUIRED

BASE MODEL NUMBER

5-0033S-201 SHOW N

cinch	3RD ANGLE PROJECTION	TROMPETER
NOTICE: The information in this drawing is PROPRIETARY and must not be used without the permission of	RoHS2 ✓ 2015/863/EU	TRT PLUG, TOOL CRIMP
Cinch Connectivity Solutions. It may contain data whose export is restricted. Verify status prior to exporting.	.XX ±.02	5-0033-XXX
INTERPRET DRAWING IN ACCORDANCE WITH ASME 714 5-2018	.XXX ±.010	Size A DO NOT SCALE Date: 12/1/2021 Sheet 1 OF 1

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Cinch Connectivity Solutions:

5-0033-201