Attenuators


SMA Miniature Type


| DC - 4.0 GHz | 238 Series | Model Numbers |
|--|--------------------|--------------------|
| Male/Female | Female/Female | Male/Male |
| ATT-0238-XX-SMA-02 | ATT-238F-XX-SMA-02 | ATT-238M-XX-SMA-02 |
| XX = Attenuation Value: Select 01-30dB in 1dB increments (.5 dB increments available) HIGH PERFORMANCE | | |

| DC - 2.0 GHz | 208 Series | Model Numbers |
|--|--------------------|--------------------|
| Male/Female | Female/Female | Male/Male |
| ATT-0208-XX-SMA-02 | ATT-208F-XX-SMA-02 | ATT-208M-XX-SMA-02 |
| XX = Attenuation Value: Select 01-60dB in 1dB increments (.5 dB increments available) | | |
| HIGH PERFORMANCE | | |


Low Cost - Inexpensive Types

| DC - 18.0 GHz | 333 Series | Model Numbers |
|--|--------------------|--------------------|
| Male/Female | Female/Female | Male/Male |
| ATT-0333-XX-SMA-02 | ATT-333F-XX-SMA-02 | ATT-333M-XX-SMA-02 |
| XX = Attenuation Value: Select 01-60dB in 1dB increments | | |
| LOW COST | | |





| Attenuation Value | Length A |
|-------------------|----------|
| 1-20 dB | 1.07 |
| 21-60 dB | 1.36 |



| DC - 8.0 GHz | 334 Series | Model Numbers |
|--|--------------------|--------------------|
| Male/Female | Female/Female | Male/Male |
| ATT-0334-XX-SMA-02 | ATT-334F-XX-SMA-02 | ATT-334M-XX-SMA-02 |
| XX = Attenuation Value: Select 01-60dB in 1dB increments | | |
| LOW COST | | |

| DC - 2.0 GHz | 335 SerieS | Model Numbers |
|--|--------------------|--------------------|
| Male/Female | Female/Female | Male/Male |
| ATT-0335-XX-SMA-02 | ATT-335F-XX-SMA-02 | ATT-335M-XX-SMA-02 |
| XX = Attenuation Value: Select 01-60dB in 1dB increments | | |
| LOW COST | | |

SPECIFICATIONS - LOW COST

| Attenuation | | | |
|---------------------|--------------------------------------|------------------|--|
| | <u>DC - 12.4 GHz</u> | | |
| 1-4 dB | <u>+</u> 0.75 dB | <u>+</u> 0.75 dB | |
| 5-8 dB_ | <u>+</u> 0.75 dB | <u>+</u> 1.00 dB | |
| 9-12 dB | <u>+</u> 1.00 dB | <u>+</u> 1.25 dB | |
| 13-20 dB | <u>+</u> 1.50 dB | <u>+</u> 1.50 dB | |
| 21-40 dB | <u>+</u> 2.00 dB | <u>+</u> 2.00 dB | |
| 41-60 dB | <u>+</u> 2.50 dB | <u>+</u> 2.50 dB | |
| VSWR: | Frequency (GHz) | | |
| 1.25 max | DC - 4. | DC - 4.0 | |
| 1.45 max | 4.0 - 12 | 4.0 - 12.4 | |
| 1.65 max | 12.4 - 1 | 12.4 - 18.0 | |
| | tts Average @ 25C de watts @ 125C | rated linearly | |
| Peak Power: | 200 Watts | | |
| Operating Te | emperature Range: | -65 to +125C | |
| Finish: Passi | vated Stainless Steel | | |
| Dimensions: | Same as 263 Series | | |
| | | | |



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Cinch Connectivity Solutions: ATT-0238-30-SMA-02