# Attenuators


## SMA Miniature Type


DC - 4.0 GHz	238 Series	Model Numbers
Male/Female	Female/Female	Male/Male
ATT-0238-XX-SMA-02	ATT-238F-XX-SMA-02	ATT-238M-XX-SMA-02
XX = Attenuation Value: Select 01-30dB in 1dB increments (.5 dB increments available) HIGH PERFORMANCE		

DC - 2.0 GHz	208 Series	Model Numbers
Male/Female	Female/Female	Male/Male
ATT-0208-XX-SMA-02	ATT-208F-XX-SMA-02	ATT-208M-XX-SMA-02
XX = Attenuation Value: Select 01-60dB in 1dB increments (.5 dB increments available)		
HIGH PERFORMANCE		


### Low Cost - Inexpensive Types

DC - 18.0 GHz	333 Series	Model Numbers
Male/Female	Female/Female	Male/Male
ATT-0333-XX-SMA-02	ATT-333F-XX-SMA-02	ATT-333M-XX-SMA-02
XX = Attenuation Value: Select 01-60dB in 1dB increments		
LOW COST		





Attenuation Value	Length A
1-20 dB	1.07
21-60 dB	1.36



DC - 8.0 GHz	334 Series	Model Numbers
Male/Female	Female/Female	Male/Male
ATT-0334-XX-SMA-02	ATT-334F-XX-SMA-02	ATT-334M-XX-SMA-02
XX = Attenuation Value: Select 01-60dB in 1dB increments		
LOW COST		

DC - 2.0 GHz	335 SerieS	Model Numbers
Male/Female	Female/Female	Male/Male
ATT-0335-XX-SMA-02	ATT-335F-XX-SMA-02	ATT-335M-XX-SMA-02
XX = Attenuation Value: Select 01-60dB in 1dB increments		
LOW COST		

#### SPECIFICATIONS - LOW COST

Attenuation			
	<u>DC - 12.4 GHz</u>		
1-4 dB	<u>+</u> 0.75 dB	<u>+</u> 0.75 dB	
5-8 dB_	<u>+</u> 0.75 dB	<u>+</u> 1.00 dB	
9-12 dB	<u>+</u> 1.00 dB	<u>+</u> 1.25 dB	
13-20 dB	<u>+</u> 1.50 dB	<u>+</u> 1.50 dB	
21-40 dB	<u>+</u> 2.00 dB	<u>+</u> 2.00 dB	
41-60 dB	<u>+</u> 2.50 dB	<u>+</u> 2.50 dB	
VSWR:	Frequency (GHz)		
1.25 max	DC - 4.	DC - 4.0	
1.45 max	4.0 - 12	4.0 - 12.4	
1.65 max	12.4 - 1	12.4 - 18.0	
	tts Average @ 25C de watts @ 125C	rated linearly	
Peak Power:	200 Watts		
<b>Operating Te</b>	emperature Range:	-65 to +125C	
Finish: Passi	vated Stainless Steel		
Dimensions:	Same as 263 Series		



## **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Cinch Connectivity Solutions: ATT-0333-08-SMA-02