HellermannTyton

Specification Sheet

Part Number: TAGPP2-788C



Clear polyester has a smooth surface, allowing for the highest resolution and print contrast.

The acrylic-based adhesive bonds to a wide variety of substrates and resists abrasion.

LaserTags are sheet fed for easy loading and fast printing.

LaserTags are made of high-temperature materials to withstand the high heat of laser printing.

Laser Tag Label, .66" x .31", 360 Per Sheet, PET, Clear, 1000/pkg

Article Number	594-00002
Туре	TAGPP2
Color	Clear (CL)
Quantity Per	pack
Product Description	HellermannTyton transparent/clear polyester labels are ideal for marking products where the visibility of the label needs to be minimized, such as consumer products, where the color of the housing needs to remain as clean looking as possible. The clear material allows the surface color to blend in with the printed text. These labels can also be used as an over-laminate to provide further protection for printed text in extreme environments.

Short Description	Laser Tag Label, .66" x .31", 360 Per Sheet, PET, Clear, 1000/pkg	
Global Part Name	TAGPP2-788C-CL	
Width W (Imperial)	0.66	
Width W (Metric)	16.7	
Thickness T (Metric)	64.0	
Height H (Imperial)	0.33	
Height H (Metric)	8.38	
Material	Type 788C, Polyester, clear (788C)	
Material Shortcut	788C	
Adhesive	Acrylic	
Halogen Free	Νο	
Adhesive Operating Temperature	-40°F to +302°F (-40°C to +150°C)	
Operating Temperature	-40°F to +199°F (-40°C to +93°C)	
Reach Compliant (Article 33)	Yes	

Package Quantity (Imperial)	1000
Package Quantity (Metric)	1000
Customs Number	3919905060
Labels per Column	30
Labels per Row	12

Yes

ROHS Compliant

© 2022 HellermannTyton. All Rights Reserved. Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

HellermannTyton: TAGPP2-788C