	Data Sheet
Central™	BC237, A, B BC238, A, B, C BC239, B, C
Semiconductor Corp. 145 Adams Avenue, Hauppauge, NY 11788 USA Tel: (631) 435-1110 • Fax: (631) 435-1824	NPN SILICON TRANSISTOR
Manufacturers of World Class Discrete Semiconductors	TO-92-18R CASE (CBE)
DESCRIPTION The CENTRAL SEMICONDUCTOR BC237, BC238, BC239 series transistors manufactured by the epitaxial planar proc amplifier applications.	
MAXIMUM RATINGS (T _A =25°C unless otherwise noted)	

	SYMBOL	BC237	<u>BC238</u>	<u>BC239</u>	UNIT			
Collector-Base Voltage	Vсво	50	30	30	V			
Collector-Emitter Voltage	VCES	50	30	30	V			
Collector-Emitter Voltage	VCEO	45	20	20	V			
Emitter-Base Voltage	VEBO	6.0	5.0	5.0	V			
Collector Current	۱c		100		mA			
Collector Current (PEAK)	ICM		200		mA			
Power Dissipation	PD		300		mW			
Operating and Storage Junction Temperature	TJ, TSTG	-	65 T0 +150		°C			
Thermal Resistance	ΘJA		420		°C/W			
ELECTRICAL CHARACTERISTICS (TA=25°C unless otherwise noted)								

<u>Leton dia dia dia dia dia dia dia dia dia dia</u>								
		BC237		BC238		BC239		
SYMBOL	TEST CONDITIONS	MIN	MAX	MIN	MAX	MIN	MAX	UNIT
ICES	V _{CE} =Rated V _{CES}		15		15		15	nA
CES	VCE=Rated VCES, TA=125°C		4.0		4.0		4.0	μA
BVCEO	IC=2.0mA	45		20		20		V
BVEBO	IE=1.0μA	6.0		5.0		5.0		V
VCE(SAT)	IC=10mA, IB=0.5mA		0.25		0.25		0.25	. V
VCE(SAT)	IC=100mA, IB=5.0mA		0.60		0.60		0.60	V
VBE(SAT)	IC=10mA, IB=0.5mA		0.83		0.83		0.83	• V
VBE(SAT)	IC=100mA, IB=5.0mA		1.05		1.05		1.05	V
VBE(ON)	VCE=5.0V, IC=2.0mA	0.55	0.70	0.55	0.70	0.55	0.70	V
						MIN	MAX	
hFE	VCE=5.0V, IC=2.0mA (BC237A, BC238A)					120	220	
hFE	VCE=5.0V, IC=2.0mA (BC237B, BC238B,		B)			180	460	
hFE	VCE=5.0V, IC=2.0mA (BC238C, BC239C)				· · ·	- 380	800	
		BC	237	BC	238	BC	239	
		MIN	MAX	MIN	MAX	MIN	MAX	UNIT
fŢ	VCE=5.0V, IC=10mA, f=100MHz	150		150		150		MHz
Cob	VCB=10V, IE=0, f=1.0MHz	-	4.5		4.5		4.5	pF
Cib	VEB=0.5V, IC=0, f=1.0MHz	8.0	TYP	8.0	TYP	8.0	TYP	pF
NF	VCE=5.0V, IC=0.2mA, RGK=2.0kΩ,					-		
	f=1.0kHz		10		10		10	dB

OUTSTANDING SUPPORT AND SUPERIOR SERVICES

PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- Consolidated shipping options

DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free guick ship samples (2nd day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- · Environmental regulation compliance
- Customer specific screening
- · Up-screening capabilities

· Custom product packing

Custom bar coding for shipments

- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- · Application and design sample kits
- · Custom product and package development

REQUESTING PRODUCT PLATING

- If requesting Tin/Lead plated devices, add the suffix "TIN/LEAD" to the part number when 1. ordering (example: 2N2222A TIN/LEAD).
- 2. If requesting Lead (Pb) Free plated devices, add the suffix " PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

CONTACT US

Corporate Headquarters & Customer Support Team

Central Semiconductor Corp. 145 Adams Avenue Hauppauge, NY 11788 USA Main Tel: (631) 435-1110 Main Fax: (631) 435-1824 Support Team Fax: (631) 435-3388 www.centralsemi.com

Worldwide Field Representatives: www.centralsemi.com/wwreps

Worldwide Distributors: www.centralsemi.com/wwdistributors

For the latest version of Central Semiconductor's LIMITATIONS AND DAMAGES DISCLAIMER. which is part of Central's Standard Terms and Conditions of sale, visit: www.centralsemi.com/terms



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Central Semiconductor: BC237B BC237B TIN/LEAD