



All dimensions are in mm; tolerances according to ISO 2768 m-H

Interface

According to IEC 60169-15, EN 122110, MIL-STD-348

Documents

N/A

Material and plating

Connector parts

Center contact
Outer contact
Dielectric
Coupling nut
Gasket
Substrate

Material

Brass
Stainless steel
PTFE
Stainless steel
Silicone
Al₂O₃

Plating

Gold, min. 1.27 μm, over chemical nickel
Passivated
Passivated

Electrical data

Impedance	50 Ω ± 5%
Frequency	DC to 18 GHz
Return loss	≥ 32.2 dB @ DC to 8 GHz ≥ 26.4 dB @ 8 GHz to 12.4 GHz ≥ 19.1 dB @ 12.4 GHz to 18 GHz
Center contact resistance	≤ 3 mΩ
Outer contact resistance	≤ 2 mΩ
Impulse Power (1μs, 1%)	100 Watts at 25°C environment temperature
Power handling (at 25 °C, sea level)	≤ 1 W derated linearity to 0 Watts at 125°C

Mechanical data

Mating cycles	≥ 500
Coupling nut retention	≥ 270 N
Coupling test torque	≤ 1.7 Nm
Recommended torque	0.8 Nm to 1.1 Nm

Environmental data

Temperature range	-55 °C to +155 °C
RoHS	compliant

Tooling

N/A

Suitable cables

N/A

Weight

2.3 g/pce

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
Martin Moder	18.03.16	J_Krautenbacher	15.07.16	b00	15-1629	I_Wallner	15.07.16

Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.de				Tel. : +49 8684 18-0 Email : info@rosenberger.de		Page 2 / 2
--	--	--	--	---	--	---------------

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Rosenberger:](#)

[32S15B-1.0S3](#)