


Dual Port 10/100 PoE Transformer

Dual Port 10/100BASE-TX PoE and PoE+ Isolation Modules



Product Features:


- Dual 10/100 PoE/PoE+ Transformer/Choke
- IEEE802.3au/af/at Compliant
- UL/EN60950 Recognized
- 100% Electrical Testing
- 1500Vrms Hi-Pot
- Patented Open Frame Construction

Part Number	Circuit	Package	Temp. Range	PoE	1-40MHz	Return Loss (min) 60MHz	80MHz	100MHz	RoHS ¹
TG111-S112NYLF	A	NY	0 to 70°C	PoE	-18dB	-14dB	-12dB	-10dB	Pb-Free
TG111-S112NYRL	A	NY	0 to 70°C	PoE	-18dB	-14dB	-12dB	-10dB	RoHS (7a)
TG111-E112NYLF	A	NY	-40 to +85°C	PoE	-18dB	-14dB	-12dB	-10dB	Pb-Free
TG111-E112NYRL	A	NY	-40 to +85°C	PoE	-18dB	-14dB	-12dB	-10dB	RoHS (7a)
TG1G-S012NZLF	A	NZ	0 to 70°C	PoE	-18dB	-14dB	-12dB	-10dB	Pb-Free
TG1G-S012NZRL	A	NZ	0 to 70°C	PoE	-18dB	-14dB	-12dB	-10dB	RoHS (7a)
TG1G-E012NZLF	A	NZ	-40 to +85°C	PoE	-18dB	-14dB	-12dB	-10dB	Pb-Free
TG1G-E012NZRL	A	NZ	-40 to +85°C	PoE	-18dB	-14dB	-12dB	-10dB	RoHS (7a)
TG111-HP3NZLF ²	A	NZ	0 to 70°C	PoE+	-18dB	-14dB	-12dB	-10dB	Pb-Free
TG111-HP3NZRL ²	A	NZ	0 to 70°C	PoE+	-18dB	-14dB	-12dB	-10dB	RoHS (7a)
TG111-HPE3NZLF ²	A	NZ	-40 to +85°C	PoE+	-18dB	-14dB	-12dB	-10dB	Pb-Free
TG111-HPE3NZRL ²	A	NZ	-40 to +85°C	PoE+	-18dB	-14dB	-12dB	-10dB	RoHS (7a)
TG110-RP06NJLF	B	NJ	0 to 70°C	PoE	-18dB	-14dB	-12dB	-10dB	Pb-Free
TG110-RP06NJRL	B	NJ	0 to 70°C	PoE	-18dB	-14dB	-12dB	-10dB	RoHS (7a)


Notes:

1. Pb-Free parts are RoHS 6/6 compliant. RoHS (7a) parts contain lead per exemption 7a which is set to expire in July 2016.
2. Pins 13 - 24 must be located on the line side for PoE+ applications.
3. For the smallest dual port 10/100BASE-TX PoE/PoE+ transformer contact the factory about the proprietary GEmini™ series.
4. Please contact the factory or representative for individual datasheets or additional information.

Circuit A




Circuit B



For additional information contact your [local representative](#), or HALO's support staff at (650) 903-3800 or info@haloelectronics.com


HALO Dual Port 10/100 Family of Ethernet Transformers

NZ Package




Dimensions: inch [mm]
Co-Planarity: 0.004 [0.10]

NY Package



Dimensions: inch [mm]

NJ Package



Dimensions: inch [mm]

US Patent Numbers:

5,656,985 6,297,721 B1
6,297,720 B1 6,320,489 B1
6,344,785 B1 6,662,431 B1

HALO
ELECTRONICS, INC.

2880 Lakeside Drive #116
Santa Clara, CA 95054
(650) 903-3800

www.halo-electronics.com

HALO® Electronics is a leading supplier of high quality communication magnetics including signal transformers, filters, CMR chokes, PoE power transformers, DC/DC isolation modules, and integrated Ethernet connectors. HALO's high quality and competitively priced leading edge technology solutions are manufactured in ISO9001 and ISO14001 factories.

© Copyright 2015 HALO Electronics, Inc. All rights reserved.

Revised 8/2015REV2. Download the latest version at www.halo-electronics.com/pdf/discrete-dualpoe-100baset.pdf

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[HALO Electronics:](#)

[TG110-RP06NJLF](#) [TG110-RP06NJLFTR](#) [TG111-HP3NZLF](#) [TG111-HP3NZLFTR](#) [TG111-HPE3NZLFTR](#) [TG111-S112NYLFTR](#) [TG111-S112NYRLTR](#) [TG111-HPE3NZRLTR](#)