## Safety Data Sheet



Revision Number: 004.0

**1. PRODUCT AND COMPANY IDENTIFICATION** 

 Product name:
 LOCTITE STYCAST EE 4154

 Product type/use:
 Epoxy resin

 Restriction of Use:
 None identified

 Company address:
 Henkel Corporation

 One Henkel Way
 Rocky Hill, Connecticut 06067

IDH number:

2069094

Region:United StatesContact information:Telephone: +1 (860) 571-5100MEDICAL EMERGENCY Phone: Poison Control Center1-877-671-4608 (toll free) or 1-303-592-1711TRANSPORT EMERGENCY Phone: CHEMTREC1-800-424-9300 (toll free) or 1-703-527-3887Internet: www.henkelna.com

# 2. HAZARDS IDENTIFICATION

	EMERGENCY OVERVIEW
DANGER:	CAUSES SKIN IRRITATION.
	MAY CAUSE AN ALLERGIC SKIN REACTION.
	CAUSES SERIOUS EYE IRRITATION.
	SUSPECTED OF CAUSING GENETIC DEFECTS.
	SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN CHILD.
	CAUSES DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED
	EXPOSURE.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
EYE IRRITATION	2A
SKIN SENSITIZATION	1
GERM CELL MUTAGENICITY	2
REPRODUCTIVE TOXICITY	2
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE	1



#### **Precautionary Statements**

Prevention:	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe vapors, mist, or spray. Wash affected area thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, clothing, eye and face protection.
Response:	F ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing.
Storage:	Store locked up.
Disposal:	Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Quartz (SiO2), <1% respirable	14808-60-7	30 - 60
Epoxy resin	Proprietary	30 - 60
butyl glycidyl ether	2426-08-6	5 - 10
Limestone	1317-65-3	1 - 5

\* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES		
Inhalation:	Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.	
Skin contact:	Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and footwear. If symptoms develop and persist, get medical attention. Wash clothing before reuse.	
Eye contact:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.	
Ingestion:	Do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention.	
Symptoms:	See Section 11.	
5. F	IRE FIGHTING MEASURES	
Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.	
Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. In case of fire, keep containers cool with water spray.	
Unusual fire or explosion hazards:	Closed containers may rupture (due to build up of pressure) when exposed to extreme heat.	
Hazardous combustion products:	Oxides of carbon. Toxic and irritating vapors.	
6. ACCIDENTAL RELEASE MEASURES		

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

clean up.

Environmental precautions:	Do not allow product to enter sewer or waterways.
Clean-up methods:	Ensure adequate ventilation. Isolate area. Keep unnecessary personnel away. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Store in a partly filled, closed container until disposal. Refer to Section 8 "Exposure Controls / Personal Protection" prior to

## 7. HANDLING AND STORAGE

Handling:

Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Refer to Section 8.

Storage:

Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Quartz (SiO2), <1% respirable	0.025 mg/m3 TWA Respirable fraction.	0.05 mg/m3 TWA (Respirable dust.) (Respirable dust.) 0.025 mg/m3 OSHA_ACT (Respirable dust.) 0.05 mg/m3 PEL Respirable dust. 2.4 MPPCF TWA Respirable. 0.1 mg/m3 TWA Respirable.	None	None
Epoxy resin	None	None	None	None
butyl glycidyl ether	3 ppm TWA (SKIN) (Dermal sensitization)	50 ppm (270 mg/m3) PEL	None	None
Limestone	10 mg/m3 TWA Total dust.	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust.	None	None

Engineering controls:

**Respiratory protection:** 

Eye/face protection:

Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

Use a NIOSH approved air-purifying respirator if the potential to exceed established exposure limits exists.

Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available.

Skin protection:

Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Liquid

Red

Physical state: Color: Odor: Odor threshold: pH: Vapor pressure: Boiling point/range: Boeifing point/range: Specific gravity: Vapor density: Flash point: Flammable/Explosive limits - lower:

Aromatic Not available. Not available. 2.0 mm hg Not available. Not available. 1.6 3.8 (Air = 1) > 93.3 °C (> 199.94 °F) ; Estimated Not available. Flammable/Explosive limits - upper: Autoignition temperature: Flammability: Evaporation rate: Solubility in water: Partition coefficient (n-octanol/water): VOC content: Viscosity: Decomposition temperature: Not available. Not available. Not applicable < 1.0 Not available. Not available. 0 %; 0 g/l Estimated Not available. Not available.

## **10. STABILITY AND REACTIVITY**

Stability:	Stable under normal conditions of storage and use.	
Hazardous reactions:	None under normal processing. Polymerization may occur at elevated temperature or in the presence of incompatible materials.	
Hazardous decomposition products:	Oxides of carbon. Irritating vapors.	
Incompatible materials:	Strong oxidizing agents. Strong acids and strong bases. Amines.	
Reactivity:	Not available.	
Conditions to avoid:	Store away from incompatible materials. Heat, flames, sparks and other sources of ignition. Direct sunlight.	

## 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure:

Skin, Inhalation, Eyes, Ingestion

#### Potential Health Effects/Symptoms

Inhalation: Skin contact:	May cause respiratory tract irritation. Causes skin irritation. May cause allergic skin reaction. May be harmful if absorbed through skin. Sensitization.
Eye contact:	Causes serious eye irritation.
Ingestion:	May cause gastrointestinal tract irritation if swallowed. May be harmful if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects	
Quartz (SiO2), <1% respirable	None	Immune system, Lung, Some evidence of carcinogenicity	
Epoxy resin	None	Allergen, Irritant	
butyl glycidyl ether	Oral LD50 (Rat) = 2,000 mg/kg Oral LD50 (Rat) = 2.05 g/kg Oral LD50 (Mouse) = 1.53 g/kg Dermal LD50 (Rabbit) = 0.788 g/kg	Irritant, Allergen, Central nervous system, Liver, Mutagen	
Limestone	None	Nuisance dust	

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Quartz (SiO2), <1% respirable	Known To Be Human Carcinogen.	Group 1	Yes
Epoxy resin	No	No	No
butyl glycidyl ether	No	No	No
Limestone	No	No	No

## **12. ECOLOGICAL INFORMATION**

**Ecological information:** 

Not available.

13. DISPOSAL CONSIDERATIONS				
Information provided is for unused product only.				
<b>Recommended method of disposal:</b> Follow all local, state, federal and provincial regulations for disposal.				
Hazardous waste number:	Not a RCRA hazardous waste.			
14. TRANSPORT INFORMATION				
The transport information provided in th package/configuration.	is section only applies to the material/formulation itself, and is not specific to any			
U.S. Department of Transportation Grou	nd (49 CFR)			
Proper shipping name: Hazard class or division: Identification number: Packing group:	Not regulated None None None			
International Air Transportation (ICAO/I/				
Proper shipping name: Hazard class or division:	Environmentally hazardous substance, liquid, n.o.s.			
Identification number:	UN 3082			
Packing group:	III			
Water Transportation (IMO/IMDG)				
Proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol-A Epichlorhydrin resin)			
Hazard class or division:	9			
Identification number:	UN 3082			
Packing group: Marine pollutant:	III Bisphenol-A Epichlorhydrin resin			
15.	REGULATORY INFORMATION			
d States Regulatory Information				
TSCA 8 (b) Inventory Status:	Il components are listed or are exempt from listing on the Toxic Substances Control Act			

CEPA DSL/NDSL Status:	All components are listed on or are exempt from listing on the Canadian Domestic Substances List.
Canada Regulatory Information	
California Proposition 65:	This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.
CERCLA/SARA Section 302 EHS: CERCLA/SARA Section 311/312: CERCLA/SARA Section 313:	None above reporting de minimis. Immediate Health, Delayed Health None above reporting de minimis.
TSCA 12 (b) Export Notification:	None above reporting de minimis
TSCA 8 (b) Inventory Status:	All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

# 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 2,3,8,11,16

#### Prepared by: Product Safety and Regulatory Affairs

Issue date: 10/21/2019

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.

# **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Loctite:

2069094