



- ↳ Hybrid SAD-GDT Technology
- ↳ UL497B LISTED
- ↳ 20kA I_{max} (1x 8/20us)
- ↳ 5kA I_{mp} (2x 10/350us)
- ↳ 5kA I_n (10x 8/20us)
- ↳ Modular
- ↳ 2W+SHIELD+G

	Electrical Characteristics																																																																
<p>G: 3-electrode gas tube Gb: 2-electrode gas tube R: Resistor D: Clamping diode</p>	<table border="1"> <tr><td>Network</td><td></td><td>4-20 mA</td></tr> <tr><td>Max. DC operating voltage</td><td>U_c</td><td>28 Vdc</td></tr> <tr><td>Max. frequency</td><td>f max.</td><td>> 3 MHz</td></tr> <tr><td>Insertion loss</td><td></td><td>< 1 dB</td></tr> <tr><td>Max. load current @25°C</td><td>I_L</td><td>300 mA</td></tr> <tr><td>Impulse current 2 x 10/350µs Test - D1 Category</td><td>I_{imp}</td><td>5 kA</td></tr> <tr><td>Nominal Discharge Current, X-C (Line/Earth) 8/20µs Test x 10 - C2 Category</td><td>I_n L/PE</td><td>5 kA</td></tr> <tr><td>Line resistance (± 10%)</td><td></td><td>4.7 Ohm</td></tr> <tr><td>DATA SPD TYPE</td><td></td><td>UL497B LISTED</td></tr> <tr><td>VOLTS</td><td>(V)</td><td>24</td></tr> <tr><td>WIRES</td><td></td><td>2W+SHIELD+G</td></tr> <tr><td>LINE CURRENT MAX</td><td>(A)</td><td>0.3</td></tr> <tr><td>AMBIENT MIN</td><td>(C)</td><td>-50</td></tr> <tr><td>AMBIENT MAX</td><td>(C)</td><td>+85</td></tr> <tr><td>RESIDUAL VOLTAGE</td><td>(V)</td><td>40</td></tr> <tr><td>MCOV</td><td>(V)</td><td>28</td></tr> <tr><td>I_N 10 impulses 8/20µs</td><td>(kA)</td><td>5</td></tr> <tr><td>I_{MAX} 8/20µs</td><td>(kA)</td><td>20</td></tr> <tr><td>I_{imp} 10/350µs</td><td>(kA)</td><td>5</td></tr> <tr><td>DATA SPEED</td><td>(Mbps)</td><td>10/100</td></tr> <tr><td>INSERTION LOSS (@ FREQ)</td><td>(db)</td><td>< 1</td></tr> </table>		Network		4-20 mA	Max. DC operating voltage	U _c	28 Vdc	Max. frequency	f max.	> 3 MHz	Insertion loss		< 1 dB	Max. load current @25°C	I _L	300 mA	Impulse current 2 x 10/350µs Test - D1 Category	I _{imp}	5 kA	Nominal Discharge Current, X-C (Line/Earth) 8/20µs Test x 10 - C2 Category	I _n L/PE	5 kA	Line resistance (± 10%)		4.7 Ohm	DATA SPD TYPE		UL497B LISTED	VOLTS	(V)	24	WIRES		2W+SHIELD+G	LINE CURRENT MAX	(A)	0.3	AMBIENT MIN	(C)	-50	AMBIENT MAX	(C)	+85	RESIDUAL VOLTAGE	(V)	40	MCOV	(V)	28	I _N 10 impulses 8/20µs	(kA)	5	I _{MAX} 8/20µs	(kA)	20	I _{imp} 10/350µs	(kA)	5	DATA SPEED	(Mbps)	10/100	INSERTION LOSS (@ FREQ)	(db)	< 1
Network		4-20 mA																																																															
Max. DC operating voltage	U _c	28 Vdc																																																															
Max. frequency	f max.	> 3 MHz																																																															
Insertion loss		< 1 dB																																																															
Max. load current @25°C	I _L	300 mA																																																															
Impulse current 2 x 10/350µs Test - D1 Category	I _{imp}	5 kA																																																															
Nominal Discharge Current, X-C (Line/Earth) 8/20µs Test x 10 - C2 Category	I _n L/PE	5 kA																																																															
Line resistance (± 10%)		4.7 Ohm																																																															
DATA SPD TYPE		UL497B LISTED																																																															
VOLTS	(V)	24																																																															
WIRES		2W+SHIELD+G																																																															
LINE CURRENT MAX	(A)	0.3																																																															
AMBIENT MIN	(C)	-50																																																															
AMBIENT MAX	(C)	+85																																																															
RESIDUAL VOLTAGE	(V)	40																																																															
MCOV	(V)	28																																																															
I _N 10 impulses 8/20µs	(kA)	5																																																															
I _{MAX} 8/20µs	(kA)	20																																																															
I _{imp} 10/350µs	(kA)	5																																																															
DATA SPEED	(Mbps)	10/100																																																															
INSERTION LOSS (@ FREQ)	(db)	< 1																																																															
	Mechanical Characteristics																																																																
	<table border="1"> <tr><td>Technology</td><td></td><td>GDT+Clamping diode</td></tr> <tr><td>Connection to Network</td><td></td><td>By screw terminal: cross section 0.5-2.5mm²</td></tr> <tr><td>Format</td><td></td><td>Plug-in DIN box</td></tr> <tr><td>Failsafe mode</td><td></td><td>Short-circuit</td></tr> <tr><td>With line cut-off in case of removal plug-in module</td><td></td><td>Yes</td></tr> <tr><td>TECHNOLOGY</td><td></td><td>SAD-GDT</td></tr> <tr><td>NETWORK CONFIGURATION</td><td></td><td>1 pair</td></tr> <tr><td>CONNECTION METHOD</td><td></td><td>Screw Terminal</td></tr> <tr><td>DISCONNECTION</td><td></td><td>Line disconnect with module removal</td></tr> <tr><td>MOUNTING</td><td></td><td>DIN RAIL</td></tr> <tr><td>MATERIAL</td><td></td><td>Thermoplastic UL94-V0</td></tr> <tr><td>NEMA RATING (IP RATING)</td><td></td><td>NEMA 2 (IP20)</td></tr> <tr><td>DIMENSIONS</td><td></td><td>See diagram</td></tr> <tr><td>WEIGHT</td><td></td><td>0.30 lbs</td></tr> <tr><td>SPARE PART</td><td></td><td>DLAWM-24D3</td></tr> </table>		Technology		GDT+Clamping diode	Connection to Network		By screw terminal: cross section 0.5-2.5mm ²	Format		Plug-in DIN box	Failsafe mode		Short-circuit	With line cut-off in case of removal plug-in module		Yes	TECHNOLOGY		SAD-GDT	NETWORK CONFIGURATION		1 pair	CONNECTION METHOD		Screw Terminal	DISCONNECTION		Line disconnect with module removal	MOUNTING		DIN RAIL	MATERIAL		Thermoplastic UL94-V0	NEMA RATING (IP RATING)		NEMA 2 (IP20)	DIMENSIONS		See diagram	WEIGHT		0.30 lbs	SPARE PART		DLAWM-24D3																		
Technology		GDT+Clamping diode																																																															
Connection to Network		By screw terminal: cross section 0.5-2.5mm ²																																																															
Format		Plug-in DIN box																																																															
Failsafe mode		Short-circuit																																																															
With line cut-off in case of removal plug-in module		Yes																																																															
TECHNOLOGY		SAD-GDT																																																															
NETWORK CONFIGURATION		1 pair																																																															
CONNECTION METHOD		Screw Terminal																																																															
DISCONNECTION		Line disconnect with module removal																																																															
MOUNTING		DIN RAIL																																																															
MATERIAL		Thermoplastic UL94-V0																																																															
NEMA RATING (IP RATING)		NEMA 2 (IP20)																																																															
DIMENSIONS		See diagram																																																															
WEIGHT		0.30 lbs																																																															
SPARE PART		DLAWM-24D3																																																															
	Standards																																																																
	<table border="1"> <tr><td>UL STANDARD</td><td></td><td>UL497B</td></tr> <tr><td>UL CATEGORY</td><td></td><td>QVQG</td></tr> <tr><td>UL FILE NUMBER</td><td></td><td>E184939</td></tr> <tr><td>STANDARDS</td><td></td><td>IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993</td></tr> <tr><td>ENVIRONMENTAL STANDARDS</td><td></td><td>ROHS</td></tr> </table>		UL STANDARD		UL497B	UL CATEGORY		QVQG	UL FILE NUMBER		E184939	STANDARDS		IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993	ENVIRONMENTAL STANDARDS		ROHS																																																
UL STANDARD		UL497B																																																															
UL CATEGORY		QVQG																																																															
UL FILE NUMBER		E184939																																																															
STANDARDS		IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993																																																															
ENVIRONMENTAL STANDARDS		ROHS																																																															
	Part number																																																																
	640803																																																																



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Citel:](#)

[DLAW-24D3](#)