г	6 5 4	3 2 1	
		used for: FILTER ADAPTER	-
н		POS. A -0.76 B1-0.25 B2+0.25 C D -0.3 Part NO.	н
		9 31.19 16.46 16.79 25.00 * ⁰¹² / ₁₃ 6.12 243A12920X	
		15 39.52 24.79 25.12 33.30 $^{+0.15}_{-0.1}$ 6.12 243A12930X 25 53.42 38.50 38.84 47.04 $^{\pm0.13}$ 5.99 243A12940X	
	A	37 69.70 54.96 55.30 63.50 ±0.13 5.99 243A12950X	Ц
	L=		
G			G
	10°		
F			F
		8.23*0.25	
E			E
	╵┝╡╽╢┊∖╵╚╝		
		5 8 02+0	
	<u>4-40 UNC</u> \ <u>SEE NOTE 9</u>		
		6	
D	B2		D
	10,0		
			Π
۲		NOTES: 1. METALSHELLS: STEEL; min. 320µ" TIN	C
		2. INSULATORS: PBT GF UL 94 V-0, BLACK	
		3. CONTACTS: COPPER ALLOY PLATING: 8µ" HARD GOLD OVER min. 50µ" NICKEL	
		4. THREADED INSERT: COPPER ALLOY; min. 200µ" TIN over 80µ" NICKEL	
		5. COLLAR: COPPER ALLOY; min. 200µ" TIN over 80µ" NICKEL 6. CAPACITANCE: 1300pF ±20%	
		7. DIELECTRIC WITHSTANDING VOLTAGE: 424 VDC	
B	Directive 2002/95/EC	8. MAXIMUM TORQUE VALUE FOR THREAD: 6" LBS	B
	"RoHS" Compliant	9. CONNECTOR IS PART MARKED: PART-NO. CONEC_ABC 10 = CHECK DIMENSION	
		tolerance scale: 2:1	-
	APPROVAL # FREIGABE # DEBLOCAGE # AUTOR/ZACION # APPROVAL LIOPHINE NAME: TITLE: DO DIAN MAY APPROVAL # FREIGABE # DEBLOCAGE # AUTOR/ZACION # APPROVAL APPROVAL # FREIGABE # DEBLOCAGE # AUTOR/ZACION # APPROVAL		
		2006 date name title: drawn 15.02. Lehmenkühler FULL METAL LC-FILTER ADAPTER	,]
		appd. 15.02. Mickenbecker PLUG / SOCKET 9-37pos.	
^	ERGAND AND A THE CONTRACT OF C	d-old dwg no: AutoCAD 2004 DIN-A	^
	COMPANY NAME: COMPANY NAME: COMPAN	24K1A767 3 sh: 1/1	
	APPROVAL © FREIGABE © DEBLOCAGE © AUTOR/ZACION © APPROVAL © C 문 문 문 문 문 문 문 문 문 문 문 문 문 문 문 문 문 문	date name	4
-			-

scription

5

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

CONEC: 243A12930XE