

Low Voltage, Branch Circuit Rated Fuses

Plug fuses

Low Voltage
Branch
Circuit
Fuses

W Series

Specifications

Description: Fast-acting plug fuse.

Dimensions: Edison base plug.

Construction: Brass threads with ceramic body.

Ratings:

Volts — 125Vac
Amps — ½-12A
IR — 10,000A RMS Sym.

Agency Information: CE, Std. 248-11, UL Listed, Guide JEFV, File E12112.

Features and Benefits

- Dependable, fast-acting circuit protection with 10,000A interrupting rating for added safety when applied to existing plug fuse systems and 125-volt single-phase control circuits.

Typical Applications

- Replacement only in existing systems.
- For general purpose circuit protection
- Use for lighting and other non-motor circuits

Catalog Numbers* (Amps)

W-½	W-2 ½	W-6	W-10
W-1	W-3	W-6 ½	W-12
W-1 ½	W-4	W-7	
W-2	W-5	W-8	

*W-15, W-20, W-25, and W-30 plug fuses obsoleted. Suggest replacing with either T-(Amp) or TL-(Amp) plug fuses.

Data Sheet: 1036

Recommended Fuse Holders For W Series Plug Fuses

- See page 10



SL and TL Series

Specifications

Description: Time-delay, loaded link plug fuse.

Dimensions:

SL — Rejection base

TL — Edison base

Construction:

SL — Ceramic base with rejection threads

TL — Brass threads with ceramic body

Ratings:

Volts — 125Vac
Amps — 15-30A
IR — 10,000A RMS Sym.

Agency Information: CE, Std. 248-11, UL Listed, Guide JEFV, File E12112.

Features and Benefits

- Time-delay loaded link TL Series Edison base plug fuses pass motor overload starting currents without opening and allow closer sizing to motor load for added protection.
- Time-delay loaded link SL Series fuses provide a rejection feature (when used alone or with Fustat adapters to retrofit Edison base holders) to help prevent overfusing.

Typical Applications

- Small motor and inductive load circuits with high in-rush current levels.
- Used with box cover units to provide equipment protection.
- Applications benefiting from fuse rejection (SL Series only)

Catalog Numbers (Amps)

Type SL	Type TL
SL-15	TL-15
SL-20	TL-20
SL-25	TL-25
SL-30	TL-30

Data Sheets: 1033 (SL) & 1035 (TL)

Recommended Fuse Holders For SL & TL Series Plug Fuses

- See page 10
- See page 38 for Fustat adapters for use with SL Series



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Eaton:](#)

[W-6](#) [W-1](#) [W-5](#) [W-2-1/2](#) [W-2](#) [TL-25](#) [W-8](#) [W-6-1/2](#) [W-1-8/10](#) [W-12](#) [W-4](#) [W-7](#) [W-1/2](#)