

HHB

1/4" x 7/8" to 1/4" x 1 1/4" In-line fuse holder





Product features


- For 1/4" x 7/8" to 1/4" x 1 1/4" fuses
- Accepts #16 to #12 AWG copper wire
- Simple crimp assembly
- "Snap-Lock" feature provides strong positive
- High visibility yellow color (except for HHB-RED)
- Recommended crimp tools:
- Thomas & Betts ERG-2001
- Channellock No. 909
- General Electric U.S. & Metric Electrical Terminal Tool
- The recommended crimp pressure range is 160 MPa ~ 210 MPa, the preferred pressure is 180 MPa
- UL flammability rating 94 V2

Product specifications

| Part number | Voltage rating (V) | Ampere rating (A) | Body material | Crimp material |
|----------------|--------------------------|-------------------------|------------------|-------------------|
| HHB-R | 32 | 30 | Nylon | Copper tin plated |

Dimensions-Inches

Drawing not to scale



| Fuse length | "L" with fuse installed | | | |
|-------------|-------------------------|--|--|--|
| 7/8" | 2.10" | | | |
| 1" | 2.25" | | | |
| 1 1/4" | 2.42" | | | |

Ordering codes

Specificy the packaging code prefix before the part number and option code suffix after the part number. Drop the -R when using the option codes (i.e. BK-HHB-R, BK-HHB-Y408)

Packaging prefixes

- Blank (10 parts in a carton)
- BK- (1000 parts in a cardboard shelf package)

Option code suffixes

- -RED (Red housing color, no leads)
- -Y408*# (#14 AWG insulated wire with 8 inch yellow leads)
- -R408# (#14 AWG insulated wire with 8 inch red leads)
- -B408*# (#14 AWG insulated wire with 8 inch black leads)
- -Y419*# (#14 AWG insulated wire with 19 inch yellow leads)
- -R419*# (#14 AWG insulated wire with 19 inch red
- -B419*# (#14 AWG insulated wire with 19 inch black leads)
- Not available in RoHS compliant construction

Life Support Policy: Eaton does not authorize the use of any of its products for use in life support devices or systems without the express written approval of an officer of the Company. Life support systems are devices which support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

Eaton reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Eaton also reserves the right to change or update, without notice, any technical information contained in this bulletin

Eaton Electronics Division

1000 Eaton Boulevard Cleveland, OH 44122 www.eaton.com/electronics

© 2019 Eaton All Rights Reserved Printed in USA Publication No. 2103 BU-MC19092 August 2019

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information

















[#] Drop -R when ordering

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Eaton:

<u>BK/HHB BK/HHB-R HHB-1K0187 HHB-R BK-HHB-R408 BK-HHB-B408 BK-HHB-B419 BK-HHB-R419 BK-HHB-R419 BK/HHB-R419 BK/HHB-Y419 BK/HHB-B419 BK/HHB-B419 BK/HHB-R419 BK/HHB-Y419 BK/HHB-Y419 BK/HHB-Y419 BK/HHB-Y419 BK/HHB-Y419 BK/HHB-Y408 BK/HHB-Y419 BK/HB-Y419 BK/HB-Y419</u>