



# Down-Angle Cat6 Gigabit Molded UTP Ethernet Cable (RJ45 Right-Angle Down M to RJ45 M), Blue, 15 ft. (4.57 m)

#### MODEL NUMBER: N204-015-BL-DN











Cat6 cable connects Gigabit Ethernet network components like routers, servers, and switches in highdensity data centers.

#### **Features**

Down-Angle Cat6 UTP Cable Connects Equipment in Data Centers and VoIP Networks This Cat6 Ethernet cable is ideal for connecting network components, such as printers, computers, copiers, routers, servers, modems and switches, in high-density data centers. Designed for fast transmission and excellent signal quality, this RJ45 cable ensures data transfer speeds up to 1 Gbps throughout your Gigabit Ethernet or VoIP network.

**Down-Angle RJ45 End Makes Connecting and Disconnecting Easier**One RJ45 connector is designed at a 90-degree down angle, which prevents excessive bending and reduces stress on the cable. This makes the space-saving cable easy to plug into patch panels, switches and other devices located in a confined area or behind a desk.

Color-Coded to Avoid Misidentification That Can Cause Costly DowntimeThis long Ethernet cable features a blue PVC jacket and molded blue ends. The color-coding allows easy, fast identification in a crowded rack or workstation and helps prevent the cable from becoming inadvertently disconnected.

#### **Highlights**

- Cat6 Ethernet patch cable delivers fast transmission speeds up to 1 Gbps in your I AN
- Down-angle RJ45 connector is easy to plug into switch or panel pressed against a wall
- Designed for home or office 10/100/1000Base-T Gigabit Ethernet networks
- Color-coded blue for fast, easy identification in a crowded rack or workstation

#### **Applications**

- Build a Gigabit Ethernet or VoIP network through the connection of routers, modems, switches and servers in a high-density data center
- Connect a workstation computer to the company server to gain access to printers, scanners and copiers
- Combine with other Tripp Lite patch cables to set up a colorcoded system in a crowded rack
- Create a connection in a tight space, such as a repurposed server room or behind furniture

#### Package Includes

 N204-015-BL-DN Down-Angle Cat6 Ethernet Cable - 15 ft., M/M, Blue

### **Specifications**

OVERVIEW		
UPC Code	037332252005	
Technology	Cat6	
CONNECTIONS		
PoE Capability	30W (802.3at)	
Side A - Connector 1	RJ45 (MALE)	





Crossover Writing         No           Contact Plating         Gold           POE Type         Type 2 POE+ (30W, IEEE 802-3at)           Connector Type         Moided           Writing Configuration         EA/TTA 668B           Angled Cornector         Yes           PHYSICAL           Cable Jacket Color         Blue           Cable Jacket Material         PVC           Cable Jacket Rating         CM           Cable Jacket Rating         UTP           Cable Jacket Rating         UTP           Cable Cuter Diameter (OD)         6.0 mm           Number of Conductors         4 Pair           Conductor Material         Strandad Copper           Conductor Material         Strandad Copper           Conductor Material         Strandad Copper           Coable Length (tr.)         15           Cable Length (tr.)         15           Cable Length (tr.)         180           Cable Length (m)         457           Shipping Dimensions (two / rm.)         10,00 x 8.00 x 0.50           Shipping Dimensions (two / rm.)         25.40 x 2.03 x x 1.27           Shipping Weight (tb.)         0.41           Shipping Weight (tb.)         0.19 <tr< th=""><th>Side B - Connector 1</th><th>RJ45 (MALE) - DOWN ANGLE</th></tr<>	Side B - Connector 1	RJ45 (MALE) - DOWN ANGLE	
Contact Plating         Gold           PoE Type         Type 2 PoE+ (30W, IEEE 802.3at)           Connector Type         Molded           Wiring Configuration         EIA/TIA 668B           Angled Connector         Yes           PHYSICAL           Cable Jacket Color         Blue           Cable Jacket Material         PVC           Cable Jacket Rating         CM           Cable Jacket Rating         UTP           Cable Shielding         UTP           Cable Longet Retring         S.0 mm           Number of Conductors         4 Pair           Canductor Material         Stranded Copper           Conductor Gauge         24 AWG           Cable Length (th.)         15           Cable Length (m)         4.57           Cable Length (m)         4.57           Cable Length (m)         4.52           Shipping Dimensions (twd / cm)         25.40 x 20.32 x 1.27           Shipping Dimensions (twd / cm)         25.40 x 20.32 x 1.27           Shipping Weight (bs.)         14 to 122°F (-10° to 50°C)           Storage Temperature Range         5* to 140°F (-15° to 50°C)           Storage Temperature Range         5* to 140°F (-15° to 50°C)			
POE Type         Type 2 PoE+ (30W, IEEE 802.3at)           Connector Type         Molded           Wring Configuration         EIATTA 568B           Angled Connector         Yes           PHYSICAL           Cable Jacket Color         Blue           Cable Jacket Material         PVC           Cable Jacket Material         CM           Cable Jacket Rating         CM           Cable Jacket Rating         UTP           Cable Shielding         UTP           Cable Jacket Rating         UTP           Cable Jacket Rating         UTP           Cable Jacket Rating         Standed Copper           Conductor Material         Stranded Copper           Conductor Gauge         24 AWG           Cable Langth (m)         4.57           Cable Langth (m)         4.57           Cable Langth (m)         4.57.2           Shipping Dimensions (kmd / km)         10.00 x 8.00 x 0.50           Shipping Dimensions (kmd / km)         2.540 x 20.32 x 1.27           Shipping Weight (kba)         0.41           Environmental Range         14* to 122*F (-10* to 50*C)           Environmental Range         14* to 122*F (-10* to 50*C)           Relative Humidity<	_		
Connector Type         Moldied           Wiring Configuration         ELATIA 568B           Angled Connector         Yes           PHYSICAL           Cable Jacket Color         Blue           Cable Jacket Marial         PVC           Cable Jacket Marial         UTP           Cable Jacket Marial         UTP           Cable Shielding         UTP           Cable Cuter Diameter (OD)         6.0 mm           Number of Conductors         4 Pair           Conductor Material         Stranded Copper           Conductor Gauge         24 AWG           Cable Length (R)         15           Cable Length (R)         15           Cable Length (m)         457           Cable Length (m)         457.2           Shipping Dimensions (hwd / in.)         10.00 x 8.00 x 0.50           Shipping Weight (bs.)         0.41           Shipping Weight (bs.)         0.41           Shipping Weight (bs.)         0.44           Shipping Temperature Range         14*to 122*F (-10* to 50*C)           Storage Temperature Range         5*to 140*F (-15* to 60*C)           Relative Humidity         0% to 90% RH, Non-Condensing           Storage Humidity Range         0% to 90% RH, Non-Condens			
Wring Configuration         EIA/TIA 668B           Angled Connector         Yes           PHYSICAL           Cable Jacket Color         Blue           Cable Jacket Material         PVC           Cable Jacket Rating         CM           Cable Jacket Rating         CM           Cable Shielding         UTP           Cable Outer Diameter (OD)         6.0 mm           Number of Conductors         4 Pair           Conductor Material         Stranded Copper           Conductor Material         5 tranded Copper           Cable Length (It)         15           Cable Length (It)         15           Cable Length (In)         457           Cable Length (In)         457.2           Shipping Dimensions (Itw/d / In)         10.0 x 8.00 x 0.50           Shipping Dimensions (Itw/d / In)         25.40 x 20.32 x 1.27           Shipping Weight (Its)         0.41           Shipping Weight (Kg)         0.19           ENVIRONMENTAL           Operating Temperature Range         5* to 140°F (-15* to 60°C)           Storage Temperature Range         5* to 140°F (-15* to 60°C)           Relative Humidity         0% to 90% RH, Non-Condensing           Storage Humidity Range			
PHYSICAL           Cable Jacket Color         Blue           Cable Jacket Material         PVC           Cable Jacket Rating         CM           Cable Shielding         UTP           Cable Shielding         UTP           Cable Outer Diameter (OD)         6.0 mm           Number of Conductors         4 Pair           Conductor Material         Stranded Copper           Conductor Gauge         24 AWG           Cable Length (It)         15           Cable Length (m)         4.57           Cable Length (m)         457.2           Shipping Dimensions (mvf / m)         10.0 x 8.00 x 0.50           Shipping Dimensions (mvf / cm)         25.40 x 20.32 x 1.27           Shipping Weight (lbs.)         0.41           Shipping Weight (kg)         0.19           ENVIRONMENTAL           Deperating Temperature Range         14" to 122" F (-10" to 50" C)           Storage Temperature Range         5" to 140" F (-15" to 60" C)           Relative Humidity         0% to 90% RH, Non-Condensing           Operating Humidity Range         0% to 90% RH, Non-Condensing           Storage Humidity Range         0% to 90% RH, Non-Condensing           Communications         50% to 90% RH, Non-Condensing <t< td=""><td></td><td></td></t<>			
PHYSICAL           Cable Jacket Color         Blue           Cable Jacket Material         PVC           Cable Jacket Rating         CM           Cable Shielding         UTP           Cable Journal Diameter (OD)         6.0 mm           Number of Conductors         4 Pair           Conductor Material         Stranded Copper           Conductor Gauge         24 AWG           Cable Length (ft.)         15           Cable Length (in.)         4.57           Cable Length (in.)         180           Cable Length (in.)         457.2           Shipping Dimensions (hwd / in.)         10.00 x 8.00 x 0.50           Shipping Weight (ib.s.)         0.41           Shipping Weight (ib.s.)         0.49           ENVIRONMENTAL           Operating Temperature Range         5" to 140"F (-15" to 60"C)           Storage Temperature Range         5" to 140"F (-15" to 60"C)           Relative Humidity         0% to 90% RH, Non-Condensing           Storage Humidity Range         0% to 90% RH, Non-Condensing           Communications         5           Bandwidth per TIA Standard         250 MHz           Maximum Bandwidth as Tested         500 MHz			
Cabie Jacket Color         Blue           Cabie Jacket Material         PVC           Cabie Jacket Rating         CM           Cabie Shielding         UTP           Cabie Outer Diameter (OD)         6.0 mm           Number of Conductors         4 Pair           Conductor Material         Stranded Copper           Conductor Gauge         24 AWG           Cabie Length (ft.)         15           Cabie Length (m)         457           Cabie Length (m)         457.2           Shipping Dimensions (hwd / in.)         10.00 x 8.00 x 0.50           Shipping Dimensions (hwd / cm)         25.40 x 20.32 x 1.27           Shipping Weight (lbs.)         0.41           Shipping Weight (kg)         0.19           ENVIRONMENTAL           Operating Temperature Range         14" to 122°F (-10° to 50°C)           Storage Temperature Range         5" to 140°F (-15° to 60°C)           Relative Humidity         0% to 90% RH, Non-Condensing           Operating Humidity Range         0% to 90% RH, Non-Condensing           Communications         50 MHz           Bandwidth per TIA Standard         250 MHz	- J		
Cable Jacket Material         PVC           Cable Jacket Rating         CM           Cable Shielding         UTP           Cable Outer Diameter (OD)         6.0 mm           Number of Conductors         4 Pair           Conductor Material         Stranded Copper           Conductor Gauge         24 AWG           Cable Length (It.)         15           Cable Length (m)         4.57           Cable Length (In.)         180           Cable Length (In.)         10.00 x 8.00 x 0.50           Shipping Dimensions (hwd / in.)         10.00 x 8.00 x 0.50           Shipping Dimensions (hwd / or.)         25.40 x 20.32 x 1.27           Shipping Weight (Ibs.)         0.41           ENVIRONMENTAL           Operating Temperature Range         14* to 122*F (-10* to 50*C)           Storage Temperature Range         5* to 140*F (-15* to 60*C)           Relative Humidity         0% to 90% RH, Non-Condensing           Operating Humidity Range         0% to 90% RH, Non-Condensing           Communications         0% to 90% RH, Non-Condensing           Communications         250 MHz	PHYSICAL		
Cable Jacket Rating         CM           Cable Shielding         UTP           Cable Outer Diameter (OD)         6.0 mm           Number of Conductors         4 Pair           Conductor Material         Stranded Copper           Conductor Gauge         24 AWG           Cable Length (ft.)         15           Cable Length (m)         4.57           Cable Length (cm)         457.2           Cable Length (cm)         457.2           Shipping Dimensions (hwd / in.)         10.00 x 8.00 x 0.50           Shipping Dimensions (hwd / cm.)         25.40 x 20.32 x 1.27           Shipping Weight (lbs.)         0.41           Shipping Weight (kg)         0.19           ENVIRONMENTAL           Operating Temperature Range         14° to 122°F (-10° to 50°C)           Storage Temperature Range         5° to 140°F (-16° to 60°C)           Relative Humidity         0% to 90% RH, Non-Condensing           Operating Humidity Range         0% to 90% RH, Non-Condensing           COMMUNICATIONS           Bandwidth per TIA Standard         250 MHz           Maximum Bandwidth as Tested         500 MHz	Cable Jacket Color	Blue	
Cable Shielding         UTP           Cable Outer Diameter (OD)         6.0 mm           Number of Conductors         4 Pair           Conductor Material         Stranded Copper           Conductor Gauge         24 AWG           Cable Length (ft.)         15           Cable Length (m)         4.57           Cable Length (cm)         457.2           Shipping Dimensions (hwd / in.)         10.00 x 8.00 x 0.50           Shipping Dimensions (hwd / cm)         25.40 x 20.32 x 1.27           Shipping Weight (lbs.)         0.41           Shipping Weight (kg)         0.19           ENVIRONMENTAL           Operating Temperature Range         14° to 122°F (-10° to 50°C)           Storage Temperature Range         5° to 140°F (-15° to 60°C)           Relative Humidity         0% to 90% RH, Non-Condensing           Operating Humidity Range         0% to 90% RH, Non-Condensing           Storage Humidity Range         0% to 90% RH, Non-Condensing           COMMUNICATIONS           Bandwidth per TIA Standard         250 MHz           Maximum Bandwidth as Tested         500 MHz	Cable Jacket Material	PVC	
Cable Outer Diameter (OD)         6.0 mm           Number of Conductors         4 Pair           Conductor Material         Stranded Copper           Conductor Gauge         24 AWG           Cable Length (ft.)         15           Cable Length (m)         4.57           Cable Length (m)         457.2           Shipping Dimensions (hwd / in.)         10.00 x 8.00 x 0.50           Shipping Dimensions (hwd / cm)         25.40 x 20.32 x 1.27           Shipping Weight (lbs.)         0.41           Shipping Weight (kg)         0.19           ENVIRONMENTAL           Operating Temperature Range         14° to 122°F (-10° to 50°C)           Storage Temperature Range         5° to 140°F (-15° to 60°C)           Relative Humidity         0% to 90% RH, Non-Condensing           Operating Humidity Range         0% to 90% RH, Non-Condensing           Storage Humidity Range         0% to 90% RH, Non-Condensing           COMMUNICATIONS           Bandwidth per TIA Standard         250 MHz           Maximum Bandwidth as Tested         500 MHz	Cable Jacket Rating	CM	
Number of Conductors         4 Pair           Conductor Material         Stranded Copper           Conductor Gauge         24 AWG           Cable Length (ft.)         15           Cable Length (m)         4.57           Cable Length (in.)         180           Cable Length (rm)         457.2           Shipping Dimensions (hwd / in.)         10.00 x 8.00 x 0.50           Shipping Dimensions (hwd / cm)         25.40 x 20.32 x 1.27           Shipping Weight (lbs.)         0.41           Shipping Weight (kg)         0.19           ENVIRONMENTAL           Operating Temperature Range         14° to 122°F (-10° to 50°C)           Storage Temperature Range         5° to 140°F (-15° to 60°C)           Relative Humidity         0% to 90% RH, Non-Condensing           Operating Humidity Range         0% to 90% RH, Non-Condensing           Storage Humidity Range         0% to 90% RH, Non-Condensing           COMMUNICATIONS           Bandwidth per TIA Standard         250 MHz           Maximum Bandwidth as Tested         500 MHz	Cable Shielding	UTP	
Conductor Material         Stranded Copper           Conductor Gauge         24 AWG           Cable Length (ft.)         15           Cable Length (im.)         4.57           Cable Length (cm)         457.2           Shipping Dimensions (hwd / in.)         10.00 x 8.00 x 0.50           Shipping Dimensions (hwd / cm)         25.40 x 20.32 x 1.27           Shipping Weight (lbs.)         0.41           Shipping Weight (kg)         0.19           ENVIRONMENTAL           Operating Temperature Range         14° to 122°F (-10° to 50°C)           Storage Temperature Range         5° to 140°F (-15° to 60°C)           Relative Humidity         0% to 90% RH, Non-Condensing           Operating Humidity Range         0% to 90% RH, Non-Condensing           Storage Humidity Range         0% to 90% RH, Non-Condensing           COMMUNICATIONS           Bandwidth per TIA Standard         250 MHz           Maximum Bandwidth as Tested         500 MHz	Cable Outer Diameter (OD)	6.0 mm	
Conductor Gauge         24 AWG           Cable Length (ft.)         15           Cable Length (m)         4.57           Cable Length (in.)         180           Cable Length (cm)         457.2           Shipping Dimensions (hwd / in.)         10.00 x 8.00 x 0.50           Shipping Dimensions (hwd / cm)         25.40 x 20.32 x 1.27           Shipping Weight (lbs.)         0.41           Shipping Weight (kg)         0.19           ENVIRONMENTAL           Operating Temperature Range         14° to 122°F (-10° to 50°C)           Storage Temperature Range         5° to 140°F (-15° to 60°C)           Relative Humidity         0% to 90% RH, Non-Condensing           Operating Humidity Range         0% to 90% RH, Non-Condensing           Storage Humidity Range         0% to 90% RH, Non-Condensing           COMMUNICATIONS           Bandwidth per TIA Standard         250 MHz           Maximum Bandwidth as Tested         500 MHz	Number of Conductors	4 Pair	
Cable Length (ft.)         15           Cable Length (m)         4.57           Cable Length (in.)         180           Cable Length (cm)         457.2           Shipping Dimensions (hwd / in.)         10.00 x 8.00 x 0.50           Shipping Dimensions (hwd / cm)         25.40 x 20.32 x 1.27           Shipping Weight (lbs.)         0.41           Shipping Weight (kg)         0.19           ENVIRONMENTAL           Operating Temperature Range         14° to 122°F (-10° to 50°C)           Storage Temperature Range         5° to 140°F (-15° to 60°C)           Relative Humidity         0% to 90% RH, Non-Condensing           Operating Humidity Range         0% to 90% RH, Non-Condensing           Storage Humidity Range         0% to 90% RH, Non-Condensing           COMMUNICATIONS           Bandwidth per TIA Standard         250 MHz           Maximum Bandwidth as Tested         500 MHz	Conductor Material	Stranded Copper	
Cable Length (m)         4.57           Cable Length (in.)         180           Cable Length (cm)         457.2           Shipping Dimensions (hwd / in.)         10.00 x 8.00 x 0.50           Shipping Dimensions (hwd / cm)         25.40 x 20.32 x 1.27           Shipping Weight (lbs.)         0.41           Shipping Weight (kg)         0.19           ENVIRONMENTAL           Operating Temperature Range         14° to 122°F (-10° to 50°C)           Storage Temperature Range         5° to 140°F (-15° to 60°C)           Relative Humidity         0% to 90% RH, Non-Condensing           Operating Humidity Range         0% to 90% RH, Non-Condensing           Storage Humidity Range         0% to 90% RH, Non-Condensing           COMMUNICATIONS           Bandwidth per TIA Standard         250 MHz           Maximum Bandwidth as Tested         500 MHz	Conductor Gauge	24 AWG	
Cable Length (in.) 180  Cable Length (cm) 457.2  Shipping Dimensions (hwd / in.) 10.00 x 8.00 x 0.50  Shipping Dimensions (hwd / cm) 25.40 x 20.32 x 1.27  Shipping Weight (lbs.) 0.41  Shipping Weight (kg) 0.19  ENVIRONMENTAL  Operating Temperature Range 14° to 122°F (-10° to 50°C)  Storage Temperature Range 5° to 140°F (-15° to 60°C)  Relative Humidity 0% to 90% RH, Non-Condensing  Operating Humidity Range 0% to 90% RH, Non-Condensing  Storage Humidity Range 0% to 90% RH, Non-Condensing  COMMUNICATIONS  Bandwidth per TIA Standard 250 MHz  Maximum Bandwidth as Tested 500 MHz	Cable Length (ft.)	15	
Cable Length (cm) 457.2  Shipping Dimensions (hwd / in.) 10.00 x 8.00 x 0.50  Shipping Dimensions (hwd / cm) 25.40 x 20.32 x 1.27  Shipping Weight (lbs.) 0.41  Shipping Weight (kg) 0.19  ENVIRONMENTAL  Operating Temperature Range 14° to 122°F (-10° to 50°C)  Storage Temperature Range 5° to 140°F (-15° to 60°C)  Relative Humidity 0% to 90% RH, Non-Condensing  Operating Humidity Range 0% to 90% RH, Non-Condensing  Storage Humidity Range 0% to 90% RH, Non-Condensing  COMMUNICATIONS  Bandwidth per TIA Standard 250 MHz  Maximum Bandwidth as Tested 500 MHz	Cable Length (m)	4.57	
Shipping Dimensions (hwd / in.) 10.00 x 8.00 x 0.50 Shipping Dimensions (hwd / cm) 25.40 x 20.32 x 1.27 Shipping Weight (lbs.) 0.41 Shipping Weight (kg) 0.19  ENVIRONMENTAL Operating Temperature Range 14° to 122°F (-10° to 50°C) Storage Temperature Range 5° to 140°F (-15° to 60°C) Relative Humidity 0% to 90% RH, Non-Condensing Operating Humidity Range 0% to 90% RH, Non-Condensing Storage Humidity Range 0% to 90% RH, Non-Condensing  COMMUNICATIONS  Bandwidth per TIA Standard 250 MHz Maximum Bandwidth as Tested 50.0 MHz	Cable Length (in.)	180	
Shipping Dimensions (hwd / cm)  25.40 x 20.32 x 1.27  Shipping Weight (lbs.)  0.41  Shipping Weight (kg)  0.19  ENVIRONMENTAL  Operating Temperature Range  14° to 122°F (-10° to 50°C)  Storage Temperature Range  5° to 140°F (-15° to 60°C)  Relative Humidity  0% to 90% RH, Non-Condensing  Operating Humidity Range  0% to 90% RH, Non-Condensing  Storage Humidity Range  0% to 90% RH, Non-Condensing  COMMUNICATIONS  Bandwidth per TIA Standard  250 MHz  Maximum Bandwidth as Tested  50.0 MHz	Cable Length (cm)	457.2	
Shipping Weight (lbs.)  Shipping Weight (kg)  0.19  ENVIRONMENTAL  Operating Temperature Range 14° to 122°F (-10° to 50°C) Storage Temperature Range 5° to 140°F (-15° to 60°C)  Relative Humidity 0% to 90% RH, Non-Condensing  Operating Humidity Range 0% to 90% RH, Non-Condensing  Storage Humidity Range 0% to 90% RH, Non-Condensing  COMMUNICATIONS  Bandwidth per TIA Standard 250 MHz  Maximum Bandwidth as Tested 500 MHz	Shipping Dimensions (hwd / in.)	10.00 x 8.00 x 0.50	
Shipping Weight (kg)  ENVIRONMENTAL  Operating Temperature Range 14° to 122°F (-10° to 50°C)  Storage Temperature Range 5° to 140°F (-15° to 60°C)  Relative Humidity 0% to 90% RH, Non-Condensing  Operating Humidity Range 0% to 90% RH, Non-Condensing  Storage Humidity Range 0% to 90% RH, Non-Condensing  COMMUNICATIONS  Bandwidth per TIA Standard 250 MHz  Maximum Bandwidth as Tested 500 MHz	Shipping Dimensions (hwd / cm)	25.40 x 20.32 x 1.27	
ENVIRONMENTAL  Operating Temperature Range 14° to 122°F (-10° to 50°C)  Storage Temperature Range 5° to 140°F (-15° to 60°C)  Relative Humidity 0% to 90% RH, Non-Condensing  Operating Humidity Range 0% to 90% RH, Non-Condensing  Storage Humidity Range 0% to 90% RH, Non-Condensing  COMMUNICATIONS  Bandwidth per TIA Standard 250 MHz  Maximum Bandwidth as Tested 500 MHz	Shipping Weight (lbs.)	0.41	
Operating Temperature Range 14° to 122°F (-10° to 50°C)  Storage Temperature Range 5° to 140°F (-15° to 60°C)  Relative Humidity 0% to 90% RH, Non-Condensing  Operating Humidity Range 0% to 90% RH, Non-Condensing  Storage Humidity Range 0% to 90% RH, Non-Condensing  COMMUNICATIONS  Bandwidth per TIA Standard 250 MHz  Maximum Bandwidth as Tested 500 MHz	Shipping Weight (kg)	0.19	
Storage Temperature Range 5° to 140°F (-15° to 60°C)  Relative Humidity 0% to 90% RH, Non-Condensing  Operating Humidity Range 0% to 90% RH, Non-Condensing  Storage Humidity Range 0% to 90% RH, Non-Condensing  COMMUNICATIONS  Bandwidth per TIA Standard 250 MHz  Maximum Bandwidth as Tested 500 MHz	ENVIRONMENTAL		
Relative Humidity	Operating Temperature Range	14° to 122°F (-10° to 50°C)	
Operating Humidity Range 0% to 90% RH, Non-Condensing  Storage Humidity Range 0% to 90% RH, Non-Condensing  COMMUNICATIONS  Bandwidth per TIA Standard 250 MHz  Maximum Bandwidth as Tested 500 MHz	Storage Temperature Range	5° to 140°F (-15° to 60°C)	
Storage Humidity Range 0% to 90% RH, Non-Condensing  COMMUNICATIONS  Bandwidth per TIA Standard 250 MHz  Maximum Bandwidth as Tested 500 MHz	Relative Humidity	0% to 90% RH, Non-Condensing	
COMMUNICATIONS  Bandwidth per TIA Standard 250 MHz  Maximum Bandwidth as Tested 500 MHz	Operating Humidity Range	0% to 90% RH, Non-Condensing	
Bandwidth per TIA Standard 250 MHz  Maximum Bandwidth as Tested 500 MHz	Storage Humidity Range	0% to 90% RH, Non-Condensing	
Maximum Bandwidth as Tested 500 MHz	COMMUNICATIONS		
+	Bandwidth per TIA Standard	250 MHz	
Network Compatibility 1 Gbps (Gigabit)	Maximum Bandwidth as Tested	500 MHz	
	Network Compatibility	1 Gbps (Gigabit)	





IEEE Standards Supported	802.3an; 802.3at	
FEATURES & SPECIFICATIONS		
Antibacterial	No	
IP68 Rated	No	
Snagless Connector	No	
STANDARDS & COMPLIANCE		
Product Certifications	UL Listed; cUL Listed	
Product Compliance	CE (Europe); RoHS; IEEE 802.3an 10GBase-T; IEEE 802.3at PoE+; REACH; UKCA	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

1000 Eaton Boulevard Cleveland, OH 44122 United States https://tripplite.eaton.com © 2024 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Tripp Lite:

N204-015-BL-DN