



The N252-P48-WH is designed specifically to be used in PoE applications. It does not add PoE power to a Cat6 signal not already transmitting both data and power.

48-Port Cat6 Patch Panel - 4PPoE Compliant, 110/Krone, 568A/B, RJ45 Ethernet, 2U Rack-Mount, White, TAA

MODEL NUMBER: N252-P48-WH











PoE+-compliant 48-port patch panel manages and organizes Cat6 data/power cable connections in your high-density network.

Features

48-Port Patch Panel Manages and Organizes High-Density Cat6 Network Cabling

This patch panel enables quick, easy cable patching. Just plug Cat6 cables into its 48 front RJ45 ports, and use a 110 or Krone punch-down tool (do not use a 4/5 pair 110 punch-down tool) to terminate color-coded connections in the rear. Both the front and rear connectors are clearly numbered and the front ports have blank labels to help you identify individual cable runs. The N252-P48-WH supports EIA/TIA 568A and 568B wiring standards and is compatible with all network applications.

Specifically Designed for Use in Type 4 Power over Ethernet Plus (PoE++) Applications

This Power over Ethernet patch panel maximizes performance with Type 4 PoE++ (4PPoE) applications in which you can power connected devices without the need for a secondary power supply. It prevents spark-gap erosion that degrades the plug and jack contacts over time and can affect data and/or power transmission capabilities. The N252-P48-WH is designed to handle the frequent mating and unmating of surveillance cameras, VoIP phone systems, wireless access points and other PoE and PoE+ devices under electrical load.

Mounts in 2U of Space in Your 19 in. Enclosure or Open Frame Rack

The high-density patch panel supports mounting in 2U of space in EIA-standard 19-inch racks. Included cable ties and a removable cable management bracket help organize your connections, cut down on cord clutter and maintain stable performance.

TAA-Compliant for GSA Schedule Purchases

The N252-P48-WH is compliant with the Federal Trade Agreements Act (TAA), which makes it eligible for GSA (General Services Administration) Schedule and other federal procurement contracts.

Specifications

OVERVIEW

Highlights

- Type 4 PoE++ patch panel prevents spark-gap erosion that can affect transmission
- 48 RJ45 and punchdown ports numbered/labeled/color-coded for immediate cable ID
- Mounts easily into 2U of space in your EIA-standard 19 in. rack for immediate use
- Krone and 110 punchdown provide flexibility for both North American and European installations
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Package Includes

- N252-P48-WH 48-Port Cat6 Patch Panel
- · Cable management bracket
- (16) Cable ties
- Quick Start Guide





Product Type	UPC Code	037332284778
CONNECTIONS	Product Type	Punchdown
Number of Ports 48 PoE Capability 100W (802.3bt) PoE Power Budget (Watts) 100 Side A - Connector 1 110 IDC: KRONE IDC Side B - Connector 1 (48) RJ45 (FEMALE) PoE Type Type 4 High-Power (100W, IEEE 802.3bt) PHYSICAL Color White Material of Construction PANEL: SPCC, PLASTIG FRAME: ABS+PC, UL94V-0 Rack Height 2U Shipping Dimensions (hwd / in.) 1.77 x 20.08 x 3.78 Shipping Weight (kg) 1.00 Unit Dimensions (hwd / in.) 1.73 x 20.88 x 4.380 Unit Dimensions (hwd / cm) 4.4 x 47.98 x 11.13 Rack Units 2 Panel Style Punchdown ENVIRONMENTAL Operating Temperature Range 14" to 140"F (-10" to 60"C) Storage Temperature Range 40" to 154"F (-40" to 68"C) Relative Humidity 10% to 90% RH, Non-Condensing Operating Humidity Range 10% TO 90% RH, NON-CONDENSING FEATURES & SPECIFICATIONS Recommended Category Cable Cat6 La	Technology	Cat5/5e; Cat6
PoE Capability 100W (802.3bt) PoE Power Budget (Watts) 100 Side A - Connector 1 110 IDC; KRONE IDC Side B - Connector 1 (48) RJ46 (FEMALE) PoE Type Type Type Type 4 High-Power (100W, IEEE 802.3bt) PHYSICAL Color White Material of Construction PANEL: SPCC, PLASTIC FRAME: ABS+PC, UL94V-0 Rack Height 2U Shipping Dimensions (twd /in.) 1.77 x 20.08 x 3.78 Shipping Weight (kg) 1.00 Unit Dimensions (twd /in.) 1.73 x 18.890 x 4.380 Unit Dimensions (twd /or.) 4.4 x 47.98 x 11.13 Rack Units 2 Panel Style Punchdown ENVIRONMENTAL Operating Temperature Range 14° to 140°F (-10° to 60°C) Storage Temperature Range 10% TO 90% RH, Non-Condensing Operating Humidity Range 10% TO 90% RH, NON-CONDENSING Storage Humidity Range 10% TO 90% RH, NON-CONDENSING FEATURES & SPECIFICATIONS Recommended Category Cable Cate Labeled Ports Verifications UL94; UL Listed; cUL Listed Floudut Certifications	CONNECTIONS	
Poer Power Budget (Watts) 100 110 DC; KRONE DC Side A - Connector 1 110 DC; KRONE DC Side B - Connector 1 (48) RJ45 (FEMALE) Poe Type	Number of Ports	48
Side A - Connector 1 110 IDC; KRONE IDC Side B - Connector 1 (48) RJ45 (FEMALE) PoE Type Type 4 High-Power (100W, IEEE 802.3bt) PHYSICAL Color White Material of Construction PANEL: SPCC, PLASTIC FRAME: ABS+PC, UL94V-0 Rack Height 2U Shipping Dimensions (hwd / in.) 1.77 x 20.08 x 3.78 Shipping Weight (kg) 1.00 Unit Dimensions (hwd / in.) 1.730 x 18.890 x 4.380 Unit Dimensions (hwd / orn) 4.4 x 47.98 x 11.13 Rack Units 2 Panel Style Punchdown ENVIRONMENTAL Operating Temperature Range 14° to 140°F (-10° to 60°C) Storage Temperature Range 14° to 140°F (-10° to 60°C) Relative Humidity 10% to 90% RH, NON-Condensing Operating Humidity Range 10% to 90% RH, NON-CONDENSING Storage Humidity Range 10% TO 90% RH, NON-CONDENSING Storage Humidity Range 10% TO 90% RH, NON-CONDENSING Storage Humidity Range 10% TO 90% RH, NON-CONDENSING Execution Recommended Category Cable Cate Labeled Ports	PoE Capability	100W (802.3bt)
Side B - Connector 1	PoE Power Budget (Watts)	100
PHYSICAL Color White Material of Construction PANEL: SPCC, PLASTIC FRAME: ABS+PC, UL94V-0 Rack Height 2U Shipping Dimensions (hwd / in.) 1.77 x 20.08 x 3.78 Shipping Weight (kg) 1.00 Unit Dimensions (hwd / in.) 1.730 x 18.890 x 4.380 Unit Dimensions (hwd / cm) 4.4 x 47.98 x 11.13 Rack Units 2 Panel Style Punchdown ENVIRONMENTAL Operating Temperature Range 14" to 140"F (-10" to 60"C) Storage Temperature Range 4-0" to 154"F (-40" to 68"C) Relative Humidity 10% to 90% RH, Non-Condensing Operating Humidity Range 10% TO 90% RH, NON-CONDENSING Storage Humidity Range 10% TO 90% RH, NON-CONDENSING Features & specifications Recommended Category Cable Cate Labeled Ports Yes STANDARDS & COMPLIANCE	Side A - Connector 1	110 IDC; KRONE IDC
PHYSICAL Color White Material of Construction PANEL: SPCC, PLASTIC FRAME: ABS+PC, UL94V-0 Rack Height 2U Shipping Dimensions (hwd / in.) 1.77 x 20.08 x 3.78 Shipping Weight (kg) 1.00 Unit Dimensions (hwd / in.) 1.730 x 18.890 x 4.380 Unit Dimensions (hwd / om) 4.4 x 47.98 x 11.13 Rack Units 2 Panel Style Punchdown ENVIRONMENTAL Operating Temperature Range 14° to 154°F (-10° to 60°C) Storage Temperature Range -40° to 154°F (-40° to 68°C) Relative Humidity 10% to 90% RH, Non-Condensing Operating Humidity Range 10% TO 90% RH, NON-CONDENSING Storage Humidity Range 10% TO 90% RH, NON-CONDENSING FEATURES & SPECIFICATIONS Recommended Category Cable Cat6 Labeled Ports Yes STANDARDS & COMPLIANCE Product Certifications UL 94; UL Listed; cUL Listed	Side B - Connector 1	(48) RJ45 (FEMALE)
Color White Material of Construction PANEL: SPCC, PLASTIC FRAME: ABS+PC, UL94V-0 Rack Height 2U Shipping Dimensions (hwd / in.) 1.77 x 20.08 x 3.78 Shipping Weight (kg) 1.00 Unit Dimensions (hwd / om) 1.730 x 18.890 x 4.380 Unit Dimensions (hwd / om) 4.4 x 47.98 x 11.13 Rack Units 2 Panel Style Punchdown ENVIRONMENTAL Operating Temperature Range 14" to 140°F (-10° to 60°C) Storage Temperature Range 40° to 154°F (-40° to 68°C) Relative Humidity 10% to 90% RH, Non-Condensing Operating Humidity Range 10% TO 90% RH, NON-CONDENSING Storage Humidity Range 10% TO 90% RH, NON-CONDENSING FEATURES & SPECIFICATIONS Recommended Category Cable Cat6 Labeled Ports Yes STANDARDS & COMPLIANCE Product Certifications UL 94; UL Listed; cUL Listed	PoE Type	Type 4 High-Power (100W, IEEE 802.3bt)
Material of Construction PANEL: SPCC, PLASTIC FRAME: ABS+PC, UL94V-0 Rack Height 2U Shipping Dimensions (hwd / in.) 1.77 x 20.08 x 3.78 Shipping Weight (kg) 1.00 Unit Dimensions (hwd / in.) 1.730 x 18.890 x 4.380 Unit Dimensions (hwd / cm) 4.4 x 47.98 x 11.13 Rack Units 2 Panel Style Punchdown ENVIRONMENTAL Operating Temperature Range 14° to 140°F (-10° to 60°C) Storage Temperature Range -40° to 154°F (-40° to 68°C) Relative Humidity 10% to 90% RH, Non-Condensing Operating Humidity Range 10% TO 90% RH, NON-CONDENSING Storage Humidity Range 10% TO 90% RH, NON-CONDENSING FEATURES & SPECIFICATIONS Recommended Category Cable Cat6 Labeled Ports Yes STANDARDS & COMPLIANCE Product Certifications UL 94; UL Listed; cUL Listed	PHYSICAL	
Rack Height 2U Shipping Dimensions (hwd / in.) 1.77 x 20.08 x 3.78 Shipping Weight (kg) 1.00 Unit Dimensions (hwd / in.) 1.730 x 18.890 x 4.380 Unit Dimensions (hwd / cm) 4.4 x 47.98 x 11.13 Rack Units 2 Panel Style Punchdown ENVIRONMENTAL Operating Temperature Range 14° to 140°F (-10° to 60°C) Storage Temperature Range 40° to 154°F (-40° to 68°C) Relative Humidity 10% to 90% RH, Non-Condensing Operating Humidity Range 10% TO 90% RH, NON-CONDENSING Storage Humidity Range 10% TO 90% RH, NON-CONDENSING FEATURES & SPECIFICATIONS Recommended Category Cable Cat6 Labeled Ports Yes STANDARDS & COMPLIANCE Product Certifications UL 94; UL Listed; cUL Listed	Color	White
Shipping Dimensions (hwd / in.) 1.77 x 20.08 x 3.78 Shipping Weight (kg) 1.00 Unit Dimensions (hwd / in.) 1.730 x 18.890 x 4.380 Unit Dimensions (hwd / cm) 4.4 x 47.98 x 11.13 Rack Units 2 Panel Style Punchdown ENVIRONMENTAL Operating Temperature Range 14° to 140°F (-10° to 60°C) Storage Temperature Range 40° to 154°F (-40° to 68°C) Relative Humidity 10% to 90% RH, Non-Condensing Operating Humidity Range 10% TO 90% RH, NON-CONDENSING Storage Humidity Range 10% TO 90% RH, NON-CONDENSING FEATURES & SPECIFICATIONS Recommended Category Cable Cat6 Labeled Ports Yes STANDARDS & COMPLIANCE Product Certifications UL 94; UL Listed; cUL Listed	Material of Construction	PANEL: SPCC, PLASTIC FRAME: ABS+PC, UL94V-0
Shipping Weight (kg) Unit Dimensions (hwd / in.) 1.730 x 18.890 x 4.380 Unit Dimensions (hwd / cm) 4.4 x 47.98 x 11.13 Rack Units 2 Panel Style Punchdown ENVIRONMENTAL Operating Temperature Range 14° to 140°F (-10° to 60°C) Storage Temperature Range -40° to 154°F (-40° to 68°C) Relative Humidity 10% to 90% RH, Non-Condensing Operating Humidity Range 10% TO 90% RH, NON-CONDENSING Storage Humidity Range 10% TO 90% RH, NON-CONDENSING FEATURES & SPECIFICATIONS Recommended Category Cable Labeled Ports Yes STANDARDS & COMPLIANCE Product Certifications UL 94; UL Listed; cUL Listed	Rack Height	2U
Unit Dimensions (hwd / in.) 1.730 x 18.890 x 4.380 Unit Dimensions (hwd / cm) 4.4 x 47.98 x 11.13 Rack Units 2 Panel Style Punchdown ENVIRONMENTAL Operating Temperature Range 14° to 140°F (-10° to 60°C) Storage Temperature Range -40° to 154°F (-40° to 68°C) Relative Humidity 10% to 90% RH, Non-Condensing Operating Humidity Range 10% TO 90% RH, NON-CONDENSING Storage Humidity Range 10% TO 90% RH, NON-CONDENSING FEATURES & SPECIFICATIONS Recommended Category Cable Cat6 Labeled Ports Yes STANDARDS & COMPLIANCE Product Certifications UL 94; UL Listed; cUL Listed	Shipping Dimensions (hwd / in.)	1.77 x 20.08 x 3.78
Unit Dimensions (hwd / cm) 4.4 x 47.98 x 11.13 Rack Units 2 Panel Style Punchdown ENVIRONMENTAL Operating Temperature Range 14° to 140°F (-10° to 60°C) Storage Temperature Range -40° to 154°F (-40° to 68°C) Relative Humidity 10% to 90% RH, Non-Condensing Operating Humidity Range 10% TO 90% RH, NON-CONDENSING Storage Humidity Range 10% TO 90% RH, NON-CONDENSING FEATURES & SPECIFICATIONS Recommended Category Cable Labeled Ports Yes STANDARDS & COMPLIANCE Product Certifications UL 94; UL Listed; cUL Listed	Shipping Weight (kg)	1.00
Rack Units 2 Panel Style Punchdown ENVIRONMENTAL Operating Temperature Range 14° to 140°F (-10° to 60°C) Storage Temperature Range -40° to 154°F (-40° to 68°C) Relative Humidity 10% to 90% RH, Non-Condensing Operating Humidity Range 10% TO 90% RH, NON-CONDENSING Storage Humidity Range 10% TO 90% RH, NON-CONDENSING FEATURES & SPECIFICATIONS Recommended Category Cable Cat6 Labeled Ports Yes STANDARDS & COMPLIANCE Product Certifications UL 94; UL Listed; cUL Listed	Unit Dimensions (hwd / in.)	1.730 x 18.890 x 4.380
Panel Style Punchdown ENVIRONMENTAL Operating Temperature Range 14° to 140°F (-10° to 60°C) Storage Temperature Range -40° to 154°F (-40° to 68°C) Relative Humidity 10% to 90% RH, Non-Condensing Operating Humidity Range 10% TO 90% RH, NON-CONDENSING Storage Humidity Range 10% TO 90% RH, NON-CONDENSING FEATURES & SPECIFICATIONS Recommended Category Cable Cat6 Labeled Ports Yes STANDARDS & COMPLIANCE Product Certifications UL 94; UL Listed; cUL Listed	Unit Dimensions (hwd / cm)	4.4 x 47.98 x 11.13
ENVIRONMENTAL Operating Temperature Range 14° to 140°F (-10° to 60°C) Storage Temperature Range -40° to 154°F (-40° to 68°C) Relative Humidity 10% to 90% RH, Non-Condensing Operating Humidity Range 10% TO 90% RH, NON-CONDENSING Storage Humidity Range 10% TO 90% RH, NON-CONDENSING FEATURES & SPECIFICATIONS Recommended Category Cable Cat6 Labeled Ports Yes STANDARDS & COMPLIANCE Product Certifications UL 94; UL Listed; cUL Listed	Rack Units	2
Operating Temperature Range 14° to 140°F (-10° to 60°C) Storage Temperature Range -40° to 154°F (-40° to 68°C) Relative Humidity 10% to 90% RH, Non-Condensing Operating Humidity Range 10% TO 90% RH, NON-CONDENSING Storage Humidity Range 10% TO 90% RH, NON-CONDENSING FEATURES & SPECIFICATIONS Recommended Category Cable Cat6 Labeled Ports Yes STANDARDS & COMPLIANCE Product Certifications UL 94; UL Listed; cUL Listed	Panel Style	Punchdown
Storage Temperature Range -40° to 154°F (-40° to 68°C) Relative Humidity 10% to 90% RH, Non-Condensing Operating Humidity Range 10% TO 90% RH, NON-CONDENSING Storage Humidity Range 10% TO 90% RH, NON-CONDENSING FEATURES & SPECIFICATIONS Recommended Category Cable Cat6 Labeled Ports Yes STANDARDS & COMPLIANCE Product Certifications UL 94; UL Listed; cUL Listed	ENVIRONMENTAL	
Relative Humidity 10% to 90% RH, Non-Condensing Operating Humidity Range 10% TO 90% RH, NON-CONDENSING Storage Humidity Range 10% TO 90% RH, NON-CONDENSING FEATURES & SPECIFICATIONS Recommended Category Cable Cat6 Labeled Ports Yes STANDARDS & COMPLIANCE Product Certifications UL 94; UL Listed; cUL Listed	Operating Temperature Range	14° to 140°F (-10° to 60°C)
Operating Humidity Range 10% TO 90% RH, NON-CONDENSING Storage Humidity Range 10% TO 90% RH, NON-CONDENSING FEATURES & SPECIFICATIONS Recommended Category Cable Cat6 Labeled Ports Yes STANDARDS & COMPLIANCE Product Certifications UL 94; UL Listed; cUL Listed	Storage Temperature Range	-40° to 154°F (-40° to 68°C)
Storage Humidity Range 10% TO 90% RH, NON-CONDENSING FEATURES & SPECIFICATIONS Recommended Category Cable Cat6 Labeled Ports Yes STANDARDS & COMPLIANCE Product Certifications UL 94; UL Listed; cUL Listed	Relative Humidity	10% to 90% RH, Non-Condensing
FEATURES & SPECIFICATIONS Recommended Category Cable Cat6 Labeled Ports Yes STANDARDS & COMPLIANCE Product Certifications UL 94; UL Listed; cUL Listed	Operating Humidity Range	10% TO 90% RH, NON-CONDENSING
Recommended Category Cable Labeled Ports Yes STANDARDS & COMPLIANCE Product Certifications UL 94; UL Listed; cUL Listed	Storage Humidity Range	10% TO 90% RH, NON-CONDENSING
Labeled Ports Yes STANDARDS & COMPLIANCE Product Certifications UL 94; UL Listed; cUL Listed	FEATURES & SPECIFICATIONS	
STANDARDS & COMPLIANCE Product Certifications UL 94; UL Listed; cUL Listed	Recommended Category Cable	Cat6
Product Certifications UL 94; UL Listed; cUL Listed	Labeled Ports	Yes
	STANDARDS & COMPLIANCE	
Product Compliance RoHS; CE (Europe); Trade Agreements Act (TAA)	Product Certifications	UL 94; UL Listed; cUL Listed
	Product Compliance	RoHS; CE (Europe); Trade Agreements Act (TAA)





WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	Lifetime limited warranty

1000 Eaton Boulevard Cleveland, OH 44122 United States https://tripplite.eaton.com © 2024 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Tripp Lite:

N252-P48-WH