



DC Power Supply for N785-CH12 Media Converter Chassis, 75W

MODEL NUMBER: N785-CH75W-DC











Highlights

- Supplies DC power to a media converter installation using N785-CH12
- Multiple power supplies provide primary and redundant power to prevent downtime

System Requirements

N785-CH12 Media Converter Chassis

Package Includes

N785-CH75W-DC 75W DC Power Supply

75W DC power supply provides primary or redundant power to your media converter installation.

Features

Powers Your N785-CH12 12-Port Media Converter Chassis

This 75-watt DC power supply works with the N785-CH12 media converter chassis to provide primary or redundant power. The N785-CH12 comes with a pre-installed AC power supply, but you can swap it out for the N785-CH75W-DC if you prefer DC power. This DC power supply can be used with any DC power source up to 48V 3A. A second DC power supply is also recommended to provide redundant power that helps prevent unwanted and expensive downtime. **Note**: Only one type of power supply should be used with the N785-CH12. Do not mix DC and AC power supplies.

Specifications

| OVERVIEW | |
|---|--------------------------|
| UPC Code | 037332267078 |
| Accessory Type | Power Supply |
| Accessory Class | Networking Accessories |
| INPUT | |
| AC Power Adapter Plug(s) | NEMA 5-15P North America |
| AC Power Adapter Input Specs (V / Hz / A) | 48V / 3A |
| AC Power Adapter Output Specs (V / A) | 12V / 6.5A |
| AC Power Adapter Cord Length (ft.) | 6 |
| AC Power Adapter Cord Length (m) | 1.83 |
| POWER | |





| Power Source Type | AC Adapter | |
|--|---|--|
| | | |
| PHYSICAL | | |
| Power Cord Color | Black | |
| Unit Dimensions (hwd / in.) | 5.240 x 2.320 x 9.060 | |
| Unit Dimensions (hwd / cm) | 13.3 x 5.9 x 23.0 | |
| Unit Packaging Type | Вох | |
| ENVIRONMENTAL | | |
| Operating Temperature Range | 32° to 122°F (0° to 50°C) | |
| Storage Temperature Range | 14° to 158°F (-10° to 70°C) | |
| Operating Humidity Range | 10% to 90% | |
| Storage Humidity Range | 5% to 95% | |
| FEATURES & SPECIFICATIONS | | |
| IP68 Rated | No | |
| IP20 Rated | No | |
| Auto MDIX Support | No | |
| STANDARDS & COMPLIANCE | | |
| External Power Supply Certifications | CE; FCC; RoHS | |
| Product Compliance | RoHS; CE (Europe); REACH; FCC (USA); Trade Agreements Act (TAA) | |
| WARRANTY & SUPPORT | | |
| Product Warranty Period (Worldwide) | 3-year limited warranty | |

1000 Eaton Boulevard Cleveland, OH 44122 United States https://tripplite.eaton.com © 2024 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Tripp Lite:

N785-CH75W-DC