



Protect It! 6-Outlet Surge Protector, 4 USB Ports, 6 ft. Cord, 1080 Joules, Diagnostic LED, Black Housing

MODEL NUMBER: TLP66USBR











6-outlet surge suppressor safeguards your computer, printer, router and other small home electronics against surges, spikes and line noise.

Description

Recommended for your home or office workstation, the TLP66USBR Protect It!® 6-Outlet Surge Suppressor features a surge protection rating of 1080 joules to defend your sensitive electronic components against strong surges and spikes.

Because residential power outlets have three wires—hot line (H), neutral (N) and ground (G)—the TLP66USBR protects all three, covering the two protection modes: full normal mode (H-N) and common mode (N-G/H-G). It also filters out electromagnetic interference (EMI) and radio frequency interference (RFI) that can disrupt your electronics and inflict hardware damage or data loss.

This surge protector features six NEMA 5-15R outlets, two of which are spaced to accept bulky transformers without blocking adjacent outlets. A retractable USB charger with 4.5-foot (1.4-meter) cord clamps to your desk or other work surface for easy access. Its four USB-A ports share 3.4 amps for charging connected mobile devices, such as tablets and smartphones.

An integrated 15A circuit breaker protects all outlets and automatically shuts down connected equipment in case of overload. The lighted on/off switch provides one-touch control over connected equipment. The six-foot (1.8-meter) AC power cord with NEMA 5-15P plug reaches nearby outlets to fit easily into your workstation or home theater setup.

Features

1080-Joule Surge Protection for Home or Office Electronics Protects your computer, printer, scanner, router, modem and other small home electronics against surges and spikes Recommended for desktop, network or home electronics applications requiring AC line protection Full normal mode (H-N) and common mode (N-G/H-G) line surge suppression Filters out disruptive EMI/RFI line noise that can cause equipment damage or data loss Exceeds IEEE 587 Category A and B surge suppression specifications

6 Outlets Accept Wide Range of Electronic Devices6 NEMA 5-15R AC outlets accept most computers and peripherals2 outlets specially spaced for bulky transformers without blocking other outlets4 USB ports with 3.4A shared

Premium Safety FeaturesLighted on/off switch provides one-touch control over connected equipmentAutomatic shutoff permanently cuts power to outlets if protection circuit is incapacitated, preventing equipment damage and indicating replacement is requiredDiagnostic LED confirms protection status at a glanceConforms to current UL 1449 3rd Edition safety standards

Fits Effortlessly Into Your Workstation6 ft. AC power cord with NEMA 5-15P plug reaches nearby

Highlights

- 6 NEMA 5-15R outlets for connecting equipment
- 4 USB ports with 3.4A shared for charging
- 1080-joule surge protection rating against surges and spikes
- Filters out EMI/RFI line noise that threatens connected hardware
- 6 ft. AC power cord with NEMA 5-15P plug

Package Includes

- TLP66USBR Protect It! 6-Outlet Surge Protector with USB Charger, Black Housing
- Owner's manual





 $outlets Clip-on\ or\ on\text{-}site\ USB\ charger\ with\ 4.5\ ft.\ retractable\ extender\ cordBlack\ plastic\ housing\ designed\ for\ long\ life$

Backed by Ultimate Lifetime Insurance\$50,000 Ultimate Lifetime Insurance covers any connected components damaged by power surge (U.S., Canada and Puerto Rico only)

Specifications

OVERVIEW		
UPC Code	037332210135	
Product Type	Surge Protector	
Charging Form Factor	Strip	
Device Compatibility	Phone; Tablet; Amazon Kindle	
INPUT		
Nominal Input Voltage(s) Supported	120V AC	
Recommended Electrical Service	120V (110-125V)	
Input Plug Features	Right Angle (36D)	
Input Cord Gauge Type	14 gauge; SJT	
Input Cord Gauge (AWG)	14	
Voltage Compatibility (VAC)	120	
Maximum Surge Amps	36000	
Input Plug Type	NEMA 5-15P	
Input Cord Details	SJT	
Input Cord Length (ft.)	6	
Right-Angle Plug	No	
Input Cord Length (m)	1.83	
Integrated Cord Clip	No	
OUTPUT		
Frequency Compatibility	60 Hz	
Output Receptacles	(6) 5-15R	
Circuit Breaker (amps)	15	
Transformer Accommodation	(4) Yes	
Right-Angle Outlets	Yes	
USER INTERFACE, ALERTS & CONTROLS		
Diagnostic LED(s)	Yes	
Switches	Combination AC circuit breaker and 2 position on/off power switch	





CHARGING Number of Charging Ports	de (H-N) and common mode (N-G / H-G) line suppression	
Number of Charging Ports 4 Total Charging Watts 17 Charging Method USB Charging Port Type USB A (FEMALE) Charging Ports / Amps (4) 3.4A Overcharge Protection No SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 1080 AC Suppression Response Time < 1 ns Protection Modes Includes full normal modes UL1449 Let Through Rating 400V EMI / RFI Filtering Yes Automatic Shut-Off Yes DATALINE SURGE SUPPRESSION Cable (Coax) Protection No Network (Ethernet) Protection No Telephone/DSL Protection No PHYSICAL Material of Construction Plastic Power Cord Color Black	de (H-N) and common mode (N-G / H-G) line suppression	
Total Charging Watts Charging Method USB Charging Port Type USB A (FEMALE) Charging Ports / Amps (4) 3.4A Overcharge Protection No SURGE / NOISE SUPPRESSION AC Suppression Joule Rating AC Suppression Response Time Protection Modes UL1449 Let Through Rating Automatic Shut-Off Yes DATALINE SURGE SUPPRESSION Cable (Coax) Protection No Network (Ethernet) Protection Telephone/DSL Protection No PHYSICAL Material of Construction Plastic Power Cord Color Black	de (H-N) and common mode (N-G / H-G) line suppression	
Charging Method USB Charging Port Type USB A (FEMALE) Charging Ports / Amps (4) 3.4A Overcharge Protection No SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 1080 AC Suppression Response Time Protection Modes Includes full normal modes UL1449 Let Through Rating Automatic Shut-Off Yes DATALINE SURGE SUPPRESSION Cable (Coax) Protection No Network (Ethernet) Protection Telephone/DSL Protection No PHYSICAL Material of Construction Plastic Power Cord Color Black	de (H-N) and common mode (N-G / H-G) line suppression	
Charging Port Type Charging Ports / Amps (4) 3.4A Overcharge Protection No SURGE / NOISE SUPPRESSION AC Suppression Joule Rating AC Suppression Response Time Protection Modes UL1449 Let Through Rating Automatic Shut-Off PATALINE SURGE SUPPRESSION Cable (Coax) Protection No Network (Ethernet) Protection No PHYSICAL Material of Construction Power Cord Color No (4) 3.4A (4) 3.4A (4) 3.4A (5) 3.4A (6) 3.4A (6) 3.4A (7) 3.4A (7) 40 (8) 3.4A (9) 4 (9) 3.4A (9) 4 (9) 4 (9) 4 (9) 4 (9) 5 (9) 6 (9) 6 (9) 7 (9) 7 (9) 7 (9) 8 (9) 8 (9) 9 (9	de (H-N) and common mode (N-G / H-G) line suppression	
Charging Ports / Amps (4) 3.4A Overcharge Protection No SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 1080 AC Suppression Response Time < 1 ns Protection Modes Includes full normal modes UL1449 Let Through Rating 400V EMI / RFI Filtering Yes Automatic Shut-Off Yes DATALINE SURGE SUPPRESSION Cable (Coax) Protection No Network (Ethernet) Protection No Telephone/DSL Protection No PHYSICAL Material of Construction Plastic Power Cord Color Black	de (H-N) and common mode (N-G / H-G) line suppression	
Overcharge Protection No SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 1080 AC Suppression Response Time < 1 ns Protection Modes Includes full normal modes UL1449 Let Through Rating 400V EMI / RFI Filtering Yes Automatic Shut-Off Yes DATALINE SURGE SUPPRESSION Cable (Coax) Protection No Network (Ethernet) Protection No Telephone/DSL Protection No PHYSICAL Material of Construction Plastic Power Cord Color Black	de (H-N) and common mode (N-G / H-G) line suppression	
SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 1080 AC Suppression Response Time < 1 ns Protection Modes Includes full normal modes UL1449 Let Through Rating 400V EMI / RFI Filtering Yes Automatic Shut-Off Yes DATALINE SURGE SUPPRESSION Cable (Coax) Protection No Network (Ethernet) Protection No Telephone/DSL Protection No PHYSICAL Material of Construction Plastic Power Cord Color Black	de (H-N) and common mode (N-G / H-G) line suppression	
AC Suppression Joule Rating 1080 AC Suppression Response Time < 1 ns Protection Modes Includes full normal modes UL1449 Let Through Rating 400V EMI / RFI Filtering Yes Automatic Shut-Off Yes DATALINE SURGE SUPPRESSION Cable (Coax) Protection No Network (Ethernet) Protection No Telephone/DSL Protection No PHYSICAL Material of Construction Plastic Power Cord Color Black	de (H-N) and common mode (N-G / H-G) line suppression	
AC Suppression Response Time < 1 ns Protection Modes Includes full normal modes UL1449 Let Through Rating 400V EMI / RFI Filtering Yes Automatic Shut-Off Yes DATALINE SURGE SUPPRESSION Cable (Coax) Protection No Network (Ethernet) Protection No Telephone/DSL Protection No PHYSICAL Material of Construction Plastic Power Cord Color Black	de (H-N) and common mode (N-G / H-G) line suppression	
Protection Modes UL1449 Let Through Rating EMI / RFI Filtering Automatic Shut-Off PATALINE SURGE SUPPRESSION Cable (Coax) Protection No Network (Ethernet) Protection No PHYSICAL Material of Construction Plastic Power Cord Color Includes full normal modes Automatic Surge suppression Yes No No No Plastic Plastic Black	de (H-N) and common mode (N-G / H-G) line suppression	
UL1449 Let Through Rating 400V EMI / RFI Filtering Yes Automatic Shut-Off Yes DATALINE SURGE SUPPRESSION Cable (Coax) Protection No Network (Ethernet) Protection No Telephone/DSL Protection No PHYSICAL Material of Construction Plastic Power Cord Color Black	de (H-N) and common mode (N-G / H-G) line suppression	
EMI / RFI Filtering Yes Automatic Shut-Off Yes DATALINE SURGE SUPPRESSION Cable (Coax) Protection No Network (Ethernet) Protection No Telephone/DSL Protection No PHYSICAL Material of Construction Plastic Power Cord Color Black		
Automatic Shut-Off Yes DATALINE SURGE SUPPRESSION Cable (Coax) Protection No Network (Ethernet) Protection No Telephone/DSL Protection No PHYSICAL Material of Construction Plastic Power Cord Color Black		
DATALINE SURGE SUPPRESSION Cable (Coax) Protection No Network (Ethernet) Protection No Telephone/DSL Protection No PHYSICAL Material of Construction Plastic Power Cord Color Black		
Cable (Coax) Protection No Network (Ethernet) Protection No Telephone/DSL Protection No PHYSICAL Material of Construction Plastic Power Cord Color Black		
Cable (Coax) Protection No Network (Ethernet) Protection No Telephone/DSL Protection No PHYSICAL Material of Construction Plastic Power Cord Color Black		
Network (Ethernet) Protection No Telephone/DSL Protection No PHYSICAL Material of Construction Plastic Power Cord Color Black		
Telephone/DSL Protection No PHYSICAL Material of Construction Plastic Power Cord Color Black		
PHYSICAL Material of Construction Plastic Power Cord Color Black		
Material of Construction Plastic Power Cord Color Black		
Power Cord Color Black	PHYSICAL	
Housing Color Black		
·		
Mounting Holes or Slots No		
Receptacle Color Black		
Shipping Dimensions (hwd / in.) 9.65 x 6.69 x 1.77		
Shipping Dimensions (hwd / cm) 24.51 x 16.99 x 4.50		
Shipping Weight (lbs.) 1.91		
Shipping Weight (kg) 0.87		
Unit Dimensions (hwd / in.) 8.300 x 3.600 x 1.400		
Unit Dimensions (hwd / cm) 24 x 17 x 4.6		
Unit Weight (lbs.) 1.8		
Unit Weight (kg) 0.82		





Input Cord Color	Black	
FEATURES & SPECIFICATIONS		
Rotatable Outlets	No	
Antimicrobial	No	
GaN Technology	No	
STANDARDS & COMPLIANCE		
Product Certifications	CAN/CSA-C22.2 No. 269.3 (Canada); CAN/CSA-C22.2 No. 308 (Canada); cUL Listed; NOM (Mexico); UL 1449; UL 1363; UL Listed	
Product Compliance	RoHS	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	Lifetime limited warranty	
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$50,000 Ultimate Lifetime Insurance	

1000 Eaton Boulevard Cleveland, OH 44122 United States https://tripplite.eaton.com © 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark. All other trademarks are the property of their respective owners.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Tripp Lite:

TLP66USBR