



USB-A to USB-C Cable, Right-Angle USB-C, USB 2.0, (M/M), 3 ft. (0.91 m)

MODEL NUMBER: U038-003-CRA











USB-A to C cable connects a smartphone or other USB-C device to the USB-A port on your computer, wall charger or car charger.

Features

USB Type-A to USB Type-C Cable Connects a USB-C Mobile Device to Your ComputerThis three-foot right-angle USB-C cable allows you to connect a device with a USB-C or Thunderbolt 3 port to a USB-enabled computer, charger, hard drive, hub or other peripheral for the purpose of charging, powering, syncing or transferring data. It is compatible with any device with a USB-C or Thunderbolt 3 port, including tablets, smartphones, MacBooks, Ultrabooks and Chromebooks.

Transfers Data and Charges Devices at USB 2.0 SpeedsThe USB-A to C cable supports USB 2.0 data transfer speeds up to 480 Mbps. The cable is backward compatible with previous USB generations, allowing you to use it with older equipment.

Reversible USB-C Connector Attaches in Either DirectionUnlike traditional USB cables that connect in only one direction, the reversible USB-C male connector plugs into a USB-C or Thunderbolt 3 port in either direction for a fumble-free connection every time.

Right-Angle USB-C Plug Makes Connecting in Tight Spaces EasierThe space-saving right-angle USB-C plug is easy to install in confined spaces, such as behind your computer desk or workstation. The right-angle construction also relieves strain on the cable and connector and prevents the cable from bending awkwardly.

Highlights

- Right-angle USB-C plug permits easier connection in confined or hard-to-reach spaces
- Supports USB 2.0 speeds up to 480 Mbps to ensure efficient data transfers
- Reversible USB-C plug connects in either direction for immediate no-fuss use
- USB-A to USB-C cable compatible with all USB-A, USB-C and Thunderbolt 3 devices

Applications

- Charge and sync a USB-C mobile device from a USB-A wall charger up to 3 ft. away
- Connect a printer or scanner to a desktop computer's hard-toreach rear USB-C port
- Transfer data between an external hard drive or flash drive and your computer or laptop

System Requirements

- Device with a USB-C or Thunderbolt 3 port
- Device with a USB-A port

Package Includes

 U038-003-CRA USB Type-A to Type-C Cable, M/M, 3 ft.

Specifications

OVERVIEW	
UPC Code	037332214119
Technology	USB 2.0 (High Speed)
Cable Type	Passive
CONNECTIONS	





Side 8 - Connector 1 USB A (MALE) - RIGHT ANGLE Connector Plating Nickel Connector Plating Gold Connector Style Angled PHYSICAL Material of Construction PVC Cable Jacket Color Black Black Cable Jacket Rating VW-1 Cable Jacket Rating VW-1 Cable Length (It.) 3 Cable Length (It.) 3 Cable Length (Im.) 36 Shipping Dimensions (Itwd / Im.) 2.90 x 7.00 x 0.50 Shipping Dimensions (Itwd / Im.) 2.266 x 17.78 x 1.27 Shipping Weight (Ibs.) 0.06 Shipping Weight (Ityl) 0.03 Unit Packaging Type Polybeg ENVIRONMENTAL Operating Temperature Range 32*10 113*F (IV* to 45*C) Storage Temperature Range 32*10 113*F (IV* to 45*C) Storage Humidity Range 10% to 85% R.H., Non-Condensing Storage Humidity Range 5% to 90% R.H., Non-Condensing Storage Humidity Range 5% to 90% R.H., Non-Condensing Standards & Compliance		
Connector Plating Nickel Contact Plating Gold Connector Style Angled PHYSICAL Material of Construction PVC Cable Jacket Color Black Cable Jacket Rating VW-1 Cable Jacket Rating VW-1 Cable Cuter Diameter (OD) 3.0 mm Cable Length (It.) 3 Cable Length (In.) 36 Shipping Dimensions (hwd / In.) 9.00 x 7.00 x 0.50 Shipping Dimensions (hwd / cm) 22.86 x 17.78 x 1.27 Shipping Weight (Ibs.) 0.06 Shipping Weight (Kg) 0.03 Unit Packaging Type Polybag ENVIRONMENTAL Operating Temperature Range 32° to 113°F (0° to 45°C) Storage Temperature Range 40° to 158°F (-40° to 70°C) Operating Humidity Range 10% to 85% RH, Non-Condensing FEATURES & SPECIFICATIONS USB 3.0 (up to 480 Mbps) STANDARDS & COMPLIANCE Product Compliance ROHS: CE (Europe): REACH: FCC (USA)	Side A - Connector 1	USB A (MALE)
Contact Plating Gold PHYSICAL Material of Construction PVC Cable Jacket Color Black Cable Jacket Rating VW-1 Cable Length (Rt) 3 Cable Length (Rt) 3 Cable Length (m) 0.91 Cable Length (m) 36 Shipping Dimensions (hwd / cm) 2.86 x 17.78 x 1.27 Shipping Dimensions (hwd / cm) 2.86 x 17.78 x 1.27 Shipping Weight (bs.) 0.06 Shipping Weight (kg) 0.03 Unit Packaging Type Polybag ENVIRONMENTAL Operating Temperature Range 32° to 113°F (0° to 45°C) Storage Temperature Range 40° to 158°F (-40" to 70°C) Operating Humidity Range 10% to 85% RH, Non-Condensing Storage Humidity Range 5% to 90% RH, Non-Condensing FEATURES & SPECIFICATIONS USB 2.0 (up to 480 Mbps) STANDARDS & COMPLIANCE Product Compliance ROHS; CE (Europe); REACH; FCC (USA)	Side B - Connector 1	USB C (MALE) - RIGHT ANGLE
Physical	Connector Plating	Nickel
### PHYSICAL Material of Construction	Contact Plating	Gold
Material of Construction	Connector Style	Angled
Cable Jacket Color Black Cable Jacket Rating VW-1 Cable Cuter Diameter (OD) 3.0 mm Cable Length (ft.) 3 Cable Length (m) 0.91 Cable Length (in.) 36 Shipping Dimensions (hwd / in.) 9.00 x 7.00 x 0.50 Shipping Dimensions (hwd / cm) 22.86 x 17.78 x 1.27 Shipping Weight (lbs.) 0.06 Shipping Weight (kg) 0.03 Unit Packaging Type Polybag ENVIRONMENTAL Operating Temperature Range 32° to 113°F (0° to 45°C) Storage Temperature Range 40° to 158°F (-40° to 70°C) Operating Humidity Range 10% to 85% RH, Non-Condensing Storage Humidity Range 5% to 90% RH, Non-Condensing FEATURES & SPECIFICATIONS USB Specification USB 2.0 (up to 480 Mbps) STANDARDS & COMPLIANCE Product Compliance RoHS; CE (Europe); REACH; FCC (USA)	PHYSICAL	
Cable Jacket Rating VW-1 Cable Cuter Diameter (OD) 3.0 mm Cable Length (ft.) 3 Cable Length (m) 0.91 Cable Length (in.) 36 Shipping Dimensions (hwd / in.) 9.00 x 7.00 x 0.50 Shipping Dimensions (hwd / in.) 22.86 x 17.78 x 1.27 Shipping Weight (fbs.) 0.06 Shipping Weight (kg) 0.03 Unit Packaging Type Polybag ENVIRONMENTAL Operating Temperature Range 32° to 113°F (0° to 45°C) Storage Temperature Range -40° to 158°F (-40° to 70°C) Operating Humidity Range 10% to 85% RH, Non-Condensing Storage Humidity Range 5% to 90% RH, Non-Condensing FEATURES & SPECIFICATIONS USB Specification USB 2.0 (up to 480 Mbps) STANDARDS & COMPLIANCE WARRANTY & SUPPORT Product Warranty Period 145 miles in surveyers.	Material of Construction	PVC
Cable Outer Diameter (OD) 3.0 mm Cable Length (fit.) 3 Cable Length (m) 0.91 Cable Length (in.) 36 Shipping Dimensions (hwd / in.) 9.00 x 7.00 x 0.50 Shipping Dimensions (hwd / cm) 22.86 x 17.78 x 1.27 Shipping Weight (lbs.) 0.06 Shipping Weight (kg) 0.03 Unit Packaging Type Polybag ENVIRONMENTAL Operating Temperature Range 32" to 113"F (0" to 45"C) Storage Temperature Range 40" to 158"F (-40" to 70"C) Operating Humidity Range 10% to 85% RH, Non-Condensing Storage Humidity Range 5% to 90% RH, Non-Condensing FEATURES & SPECIFICATIONS USB Specification USB 2.0 (up to 480 Mbps) STANDARDS & COMPLIANCE Product Compliance RoHS; CE (Europe); REACH; FCC (USA)	Cable Jacket Color	Black
Cable Length (ft.) 3 Cable Length (m) 0.91 Cable Length (in.) 36 Shipping Dimensions (hwd / in.) 9.00 x 7.00 x 0.50 Shipping Dimensions (hwd / om) 22.86 x 17.78 x 1.27 Shipping Weight (lbs.) 0.06 Shipping Weight (kg) 0.03 Unit Packaging Type Polybag ENVIRONMENTAL Operating Temperature Range 32° to 113°F (0° to 45°C) Storage Temperature Range 4-40° to 158°F (-40° to 70°C) Operating Humidity Range 10% to 85% RH, Non-Condensing Storage Humidity Range 5% to 90% RH, Non-Condensing FEATURES & SPECIFICATIONS USB 2.0 (up to 480 Mbps) STANDARDS & COMPLIANCE Product Compliance ROHS; CE (Europe); REACH; FCC (USA)	Cable Jacket Rating	VW-1
Cable Length (m) Cable Length (in.) 36 Shipping Dimensions (hwd / in.) 9.00 x 7.00 x 0.50 Shipping Dimensions (hwd / cm) Shipping Weight (lbs.) 0.06 Shipping Weight (kg) 0.03 Unit Packaging Type Polybag ENVIRONMENTAL Operating Temperature Range 32° to 113°F (0° to 45°C) Storage Temperature Range 40° to 158°F (-40° to 70°C) Operating Humidity Range 10% to 85% RH, Non-Condensing Storage Humidity Range 5% to 90% RH, Non-Condensing FEATURES & SPECIFICATIONS USB 2.0 (up to 480 Mbps) STANDARDS & COMPLIANCE Product Compliance RoHS; CE (Europe); REACH; FCC (USA)	Cable Outer Diameter (OD)	3.0 mm
Cable Length (in.) Shipping Dimensions (hwd / in.) 9.00 x 7.00 x 0.50 Shipping Dimensions (hwd / cm) 22.86 x 17.78 x 1.27 Shipping Weight (lbs.) 0.06 Shipping Weight (kg) 0.03 Unit Packaging Type Polybag ENVIRONMENTAL Operating Temperature Range 32° to 113°F (0° to 45°C) Storage Temperature Range 40° to 158°F (-40° to 70°C) Operating Humidity Range 10% to 85% RH, Non-Condensing Storage Humidity Range 5% to 90% RH, Non-Condensing FEATURES & SPECIFICATIONS USB 2.0 (up to 480 Mbps) STANDARDS & COMPLIANCE Product Compliance RoHS; CE (Europe); REACH; FCC (USA)	Cable Length (ft.)	3
Shipping Dimensions (hwd / in.) Shipping Dimensions (hwd / cm) 22.86 x 17.78 x 1.27 Shipping Weight (lbs.) 0.06 Shipping Weight (kg) Unit Packaging Type Polybag ENVIRONMENTAL Operating Temperature Range 32° to 113°F (0° to 45°C) Storage Temperature Range 40° to 158°F (-40° to 70°C) Operating Humidity Range 10% to 85% RH, Non-Condensing Storage Humidity Range FEATURES & SPECIFICATIONS USB 2.0 (up to 480 Mbps) STANDARDS & COMPLIANCE Product Compliance RoHS; CE (Europe): REACH; FCC (USA)	Cable Length (m)	0.91
Shipping Dimensions (hwd / cm) 22.86 x 17.78 x 1.27 Shipping Weight (lbs.) 0.06 Shipping Weight (kg) 0.03 Unit Packaging Type Polybag ENVIRONMENTAL Operating Temperature Range 32° to 113°F (0° to 45°C) Storage Temperature Range -40° to 158°F (-40° to 70°C) Operating Humidity Range 10% to 85% RH, Non-Condensing Storage Humidity Range 5% to 90% RH, Non-Condensing FEATURES & SPECIFICATIONS USB 2.0 (up to 480 Mbps) STANDARDS & COMPLIANCE Product Compliance RoHS; CE (Europe); REACH; FCC (USA)	Cable Length (in.)	36
Shipping Weight (lbs.) Shipping Weight (kg) Unit Packaging Type Polybag ENVIRONMENTAL Operating Temperature Range 32° to 113°F (0° to 45°C) Storage Temperature Range -40° to 158°F (-40° to 70°C) Operating Humidity Range 10% to 85% RH, Non-Condensing Storage Humidity Range 5% to 90% RH, Non-Condensing FEATURES & SPECIFICATIONS USB 2.0 (up to 480 Mbps) STANDARDS & COMPLIANCE Product Compliance RoHS; CE (Europe); REACH; FCC (USA)	Shipping Dimensions (hwd / in.)	9.00 x 7.00 x 0.50
Shipping Weight (kg) 0.03 Unit Packaging Type Polybag ENVIRONMENTAL Operating Temperature Range 32° to 113°F (0° to 45°C) Storage Temperature Range -40° to 158°F (-40° to 70°C) Operating Humidity Range 10% to 85% RH, Non-Condensing Storage Humidity Range 5% to 90% RH, Non-Condensing FEATURES & SPECIFICATIONS USB 2.0 (up to 480 Mbps) STANDARDS & COMPLIANCE Product Compliance RoHS; CE (Europe); REACH; FCC (USA) WARRANTY & SUPPORT	Shipping Dimensions (hwd / cm)	22.86 x 17.78 x 1.27
Unit Packaging Type Polybag ENVIRONMENTAL Operating Temperature Range 32° to 113°F (0° to 45°C) Storage Temperature Range -40° to 158°F (-40° to 70°C) Operating Humidity Range 10% to 85% RH, Non-Condensing Storage Humidity Range 5% to 90% RH, Non-Condensing FEATURES & SPECIFICATIONS USB 2.0 (up to 480 Mbps) STANDARDS & COMPLIANCE Product Compliance RoHS; CE (Europe); REACH; FCC (USA) WARRANTY & SUPPORT	Shipping Weight (lbs.)	0.06
ENVIRONMENTAL Operating Temperature Range 32° to 113°F (0° to 45°C) Storage Temperature Range -40° to 158°F (-40° to 70°C) Operating Humidity Range 10% to 85% RH, Non-Condensing Storage Humidity Range 5% to 90% RH, Non-Condensing FEATURES & SPECIFICATIONS USB Specification USB 2.0 (up to 480 Mbps) STANDARDS & COMPLIANCE Product Compliance RoHS; CE (Europe); REACH; FCC (USA) WARRANTY & SUPPORT	Shipping Weight (kg)	0.03
Operating Temperature Range 32° to 113°F (0° to 45°C) Storage Temperature Range -40° to 158°F (-40° to 70°C) Operating Humidity Range 10% to 85% RH, Non-Condensing Storage Humidity Range 5% to 90% RH, Non-Condensing FEATURES & SPECIFICATIONS USB Specification USB 2.0 (up to 480 Mbps) STANDARDS & COMPLIANCE Product Compliance RoHS; CE (Europe); REACH; FCC (USA)	Unit Packaging Type	Polybag
Storage Temperature Range -40° to 158°F (-40° to 70°C) Operating Humidity Range 10% to 85% RH, Non-Condensing Storage Humidity Range 5% to 90% RH, Non-Condensing FEATURES & SPECIFICATIONS USB Specification USB 2.0 (up to 480 Mbps) STANDARDS & COMPLIANCE Product Compliance RoHS; CE (Europe); REACH; FCC (USA) WARRANTY & SUPPORT Product Warranty Period Lifetime limited warranty	ENVIRONMENTAL	
Operating Humidity Range 10% to 85% RH, Non-Condensing Storage Humidity Range 5% to 90% RH, Non-Condensing FEATURES & SPECIFICATIONS USB Specification USB 2.0 (up to 480 Mbps) STANDARDS & COMPLIANCE Product Compliance RoHS; CE (Europe); REACH; FCC (USA) WARRANTY & SUPPORT Product Warranty Period Lifetime limited warranty	Operating Temperature Range	32° to 113°F (0° to 45°C)
Storage Humidity Range 5% to 90% RH, Non-Condensing FEATURES & SPECIFICATIONS USB Specification USB 2.0 (up to 480 Mbps) STANDARDS & COMPLIANCE Product Compliance RoHS; CE (Europe); REACH; FCC (USA) WARRANTY & SUPPORT Product Warranty Period Lifetime limited warranty	Storage Temperature Range	-40° to 158°F (-40° to 70°C)
FEATURES & SPECIFICATIONS USB Specification USB 2.0 (up to 480 Mbps) STANDARDS & COMPLIANCE Product Compliance RoHS; CE (Europe); REACH; FCC (USA) WARRANTY & SUPPORT Product Warranty Period Lifetime limited warranty	Operating Humidity Range	10% to 85% RH, Non-Condensing
USB Specification USB 2.0 (up to 480 Mbps) STANDARDS & COMPLIANCE Product Compliance RoHS; CE (Europe); REACH; FCC (USA) WARRANTY & SUPPORT Product Warranty Period Lifetime limited warranty	Storage Humidity Range	5% to 90% RH, Non-Condensing
STANDARDS & COMPLIANCE Product Compliance RoHS; CE (Europe); REACH; FCC (USA) WARRANTY & SUPPORT Product Warranty Period Lifetime limited warranty	FEATURES & SPECIFICATIONS	
Product Compliance RoHS; CE (Europe); REACH; FCC (USA) WARRANTY & SUPPORT Product Warranty Period Lifetime limited warranty	USB Specification	USB 2.0 (up to 480 Mbps)
WARRANTY & SUPPORT Product Warranty Period Lifetime limited warranty	STANDARDS & COMPLIANCE	
Product Warranty Period Lifetime limited warranty	Product Compliance	RoHS; CE (Europe); REACH; FCC (USA)
Product Warranty Period (Worldwide) Lifetime limited warranty	WARRANTY & SUPPORT	
	Product Warranty Period (Worldwide)	Lifetime limited warranty





1000 Eaton Boulevard Cleveland, OH 44122 United States https://tripplite.eaton.com © 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark. All other trademarks are the property of their respective owners.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Tripp Lite:

U038-003-CRA