



#### **Device Drivers**

A driver CD-ROM is no longer included with this product. The latest drivers for Windows, macOS, Android, Chrome OS and Ubuntu are available from the DisplayLink website. Please visit <u>https://www.displaylink.com/downloads</u>.

## USB-C Dock, Dual Display - 5K 60 Hz DP, 4K 60 Hz HDMI, USB 3.x (5Gbps), USB-A/C Hub, GbE, 85W PD Charging, EU/UK Power Adapters

### MODEL NUMBER: U442-DOCK21BINT



USB-C dock with DisplayLink technology and 14 ports lets you mirror or extend video from your laptop or PC across 2 monitors simultaneously.

#### **Features**

#### USB-C Docking Station Turns Your Device's USB or Thunderbolt 3/4 Port into 14 New Ports

This universal USB-C dock with PD Charging expands the potential of your Windows laptop, Chromebook, smartphone or PC's USB-A, USB-C, Thunderbolt 3 or Thunderbolt 4 port. Connect the docking station using the included USB-C cable, and add 14 ports to your device:(2) 4K HDMI(2) 4K DisplayPortRJ45 Gigabit Ethernet(4) USB 3.2 Gen 1USB 3.2 Gen 1 chargingUSB-C PD ChargingUSB-C data(2) 3.5 mm stereo

#### Transmits Crystal-Clear True 5K/4K Video and Digital Audio with 4:4:4 Color

The HDMI and DisplayPort (DP) outputs support true 4K resolutions up to 4096 x 2160 at 60 Hz with 4:4:4 chroma subsampling for top-level PC gaming or using your HDTV as a PC monitor. When both DP outputs are connected to one DP monitor, that monitor will support 5K video up to 5120 x 2880 at 60 Hz.

#### DisplayLink Technology Allows Connection of Multiple Displays

By downloading and installing the proper DisplayLink drivers to your host device, you may connect two external displays simultaneously. This allows you to display the image from the host computer on both monitors, extend your host desktop across both with different windows open on each, or combine all into one large display as a video wall. Connect multiple monitors (dual 4K @ 60 Hz DP; dual 4K @ 60 Hz HDMI; or 4K @ 60 Hz DP and 4K @ 60 Hz HDMI) in Extended and Mirror modes. *Note: Mac OS laptops or computers will only extend to one monitor. The others will be mirrored.* 

#### USB Hub Ports Connect Keyboards, Thumb Drives and Other Peripherals

One USB-C and five USB-A ports accept USB peripherals, such as flash drives, mice, keyboards and printers. All support fast USB 3.2 Gen 1 data transfer rates up to 5 Gbps and are backward compatible with USB 2.0 and USB 1.1 devices. One USB-A port also supports 5V 1.5A (7.5W) of power dedicated to fast-charging your mobile device. *Note: Host must support USB OTG (On-the-Go).* 

#### Highlights

- Supports 5K @ 60 Hz on one DisplayPort monitor (when connected to both DP ports)
- Extends/mirrors 4K @ 60 Hz across 2 DP, 2 HDMI or HDMI/DP monitors simultaneously
- Supports 20V 4.25A (85W) power output for fast-charging large-capacity mobile devices
- Connects you to a wired 10/100/1000 Ethernet network when no Wi-Fi is available
- USB-C and USB-A hub ports allow connection of flash drives and other peripherals

#### **Applications**

- Extend or mirror your laptop or PC monitor on multiple displays to aid in multitasking and increase productivity
- Transfer data to and from a USB flash drive or external hard drive
- Access a wired Ethernet network in a location with no or spotty Wi-Fi
- Charge your notebook or laptop through the USB-C PD Charging port
- Connect a microphone/headset to record a podcast or listen to music

#### **System Requirements**

- Source device with USB-A, USB-C, Thunderbolt 3 or Thunderbolt 4 port and DisplayLink drivers installed
- Display devices with HDMI and/or DisplayPort input
- Windows or macOS operating system

#### **Package Includes**

- U442-DOCK21BINT USB-C Dock, Dual Display, Black
- USB-C cable, 1 m
- USB-C to USB-A adapter
- External power supply (Input: 100-240V, 50/60 Hz, 1.8A; Output: 20V 6.75A)
- (2) International power adapters (BS 1363 U.K., CEE 7/7 Schuko EU)





#### PD Charging Port Charges the Connected Notebook, Tablet or Other Device

Connect your host device to the USB-C Power Delivery port, which supports PD 2.0 charging of connected PD Charging-compliant devices, such as laptops, Kindles, iPads and Android smartphones, up to 20V 4.25A (85W). The included power supply, when plugged into an AC outlet, provides the charging power.

#### Accesses a Wired Gigabit Ethernet Network

The RJ45 port offers access to a Gigabit Ethernet network when Wi-Fi is unavailable or when a wired connection offers faster speeds. Connect using a UTP cable (sold separately), and enjoy true 10/100/1000 Mbps Ethernet speeds for fast data transfers.

#### **Connects Speakers, Microphone and Other Audio Equipment**

Two 3.5 mm mini stereo jacks are convenient for connecting speakers, headphones and/or a microphone to your workstation. You can listen to music or record the latest episode of your podcast.

#### Anti-Theft Lock Protects the USB-C Docking Station When You Aren't Around

Connect a user-supplied computer/laptop security cable lock (not included) to this K-lock port to protect your source device against theft.

# **Specifications**

| OVERVIEW                       |   |  |
|--------------------------------|---|--|
| UPC Code                       | 037332272027  |  |
| Product Type                   | Docking Station   |  |
| Technology                     | Cat5/5e; Cat6; DisplayPort; HDMI; USB 3.x   |  |
| Host Connector                 | USB A (MALE); USB C (MALE)  |  |
| VIDEO                          |   |  |
| Video Input                    | USB C (FEMALE)  |  |
| Video Output                   | DISPLAYPORT (FEMALE); HDMI (FEMALE)   |  |
| Number of Monitors Supported   | 2   |  |
| Video Ports                    | (2) DISPLAYPORT (FEMALE); (2) HDMI (FEMALE)   |  |
| Video Ports Details            | HDMI 2.0; DisplayPort 1.2   |  |
| Resolutions Supported          | DisplayPort (Single): 4K 60Hz (4096 x 2160)DisplayPort (Dual): 5K 60Hz (5120 x 2880)HDMI (Dual & Single): 4K 60Hz (4096 x 2160) |  |
| Supported Resolutions          | 1280x720 (720p); 1920x1080 (1080p); 3840x2160 (4K); 5120x2880 (5K)  |  |
| Max Supported Video Resolution | Dual DP: 5120 x 2880@60Hz; Single DP: 4096 x 2160@60Hz; Dual/Single HDMI: 4096 x 2160@60Hz                                      |  |
| Extended Mode                  | Yes   |  |
| Extended Mode Details          | 2x DisplayPort (5K 60Hz)2x HDMI (4K 60Hz )1x DisplayPort (4K 60Hz) + 1x HDMI (4K 60Hz)  |  |
| Mirror Mode                    | Yes   |  |
| Mirror Mode Details            | 2x DisplayPort (5K 60Hz)2x HDMI (4K 60Hz )1x DisplayPort (4K 60Hz) + 1x HDMI (4K 60Hz)  |  |
| HDR Support                    | No  |  |
| 3D Video Supported             | Yes   |  |
| DisplayPort Alt Mode           | No  |  |

Owner's manual





| AUDIO   |  |  |
|---|--|--|
| Audio Ports                                     | (2) 3.5MM (FEMALE)   |  |
| Audio Ports Details                             | Separate 3.5 mm mini stereo jacks for speakers and microphone      |  |
| Audio Specification                             | 2.1 Channel Surround Sound, TRRS                                   |  |
| DATA  |  |  |
| Data Ports                                      | (5) USB A (FEMALE); (1) USB C (FEMALE)                             |  |
| Data Ports Details                              | (5) USB-A - USB 3.2 Gen 1 (5 Gbps); USB-C - USB 3.2 Gen 1 (5 Gbps) |  |
| NETWORK   |  |  |
| Network Ports                                   | RJ45 (FEMALE)  |  |
| INPUT   |  |  |
| AC Power Adapter Plug(s)                        | BS 1363 UK; CEE 7/7 Schuko   |  |
| AC Power Adapter Input Specs (V /<br>Hz / A)    | 100-240V / 50/60 Hz / 1.8A   |  |
| AC Power Adapter Output Specs (V<br>/ A)        | 20V / 6.75A  |  |
| AC Power Adapter Cord Length (ft.)              | 6  |  |
| AC Power Adapter Cord Length (m)                | 1.83   |  |
| Voltage Compatibility (VAC)                     | 100; 110; 120; 125; 127; 200; 208; 220; 230; 240                   |  |
| Input Plug Type                                 | BS1363; CEE 7/7 Schuko   |  |
| Input Cord Length (ft.)                         | 1.52   |  |
| Input Cord Length (m)                           | 0.46   |  |
| Bus Powered                                     | No   |  |
| BATTERY   |  |  |
| Battery Charging (5V/1.5A Port)                 | Yes  |  |
| POWER   |  |  |
| AC Adapter                                      | Yes  |  |
| DC Barrel Plug                                  | OD: 5.5 x 2.5 x 10mm, Positive Pin, Negative Sleeve                |  |
| Power Consumption (Watts)                       | 15.00  |  |
| Output Volt/Amp (from external<br>power supply) | 20V/6.75A  |  |
| USB Power Delivery (PD) Charging<br>Support     | Yes  |  |
| USB Power Delivery (PD) Charging Specification  | 2.0  |  |
| CONNECTIONS                                     |  |  |





| Number of Ports             | 15  |
|-----------------------------|---|
| Ports                       | 1   |
| Ports Detail                |   |
|                             | RJ45 port supports true 10/100/1000 Mbps (Gigabit) network speeds   |
| Dock Connectors             | USB-C, USB-C PD Charging, (4) USB-A 3.2 Gen1, USB-A 3.2 Gen1 BC 1.2, (2) DisplayPort, (2) HDMI, (2) 3.5mm, RJ45   |
| Side A - Connector 1        | USB C (FEMALE)  |
| Side B - Connector 1        | (2) HDMI (FEMALE)   |
| Side B - Connector 2        | (2) DISPLAYPORT (FEMALE)  |
| Side B - Connector 3        | RJ45 (FEMALE)   |
| Side B - Connector 4        | (5) USB A (FEMALE)  |
| Side B - Connector 5        | USB C (FEMALE)  |
| Side B - Connector 6        | (2) 3.5MM (FEMALE)  |
|                             |   |
| USER INTERFACE, ALERTS & CO |   |
| LED Indicators              | Power (Blue), USB Connection (Green), RJ45 (x1 Green = Power, x1 Orange = Data)   |
| CHARGING                    |   |
| Number of Charging Ports    | 6   |
| Total Charging Watts        | 85  |
| Charging Port Type          | (5) USB A (FEMALE); USB C (FEMALE)  |
| Charging Ports              | 2.4A Quick Charge; USB-A: 5V 1.5A (7.5W); USB-C: 85W Power Delivery (PD 3.0)  |
| Charging Ports Details      | (4) USB-A ports support 5V/0.9A (4.5W) charging(1) USB-A port supports 5V/1.5A (7.5W) charging and Apple Charging 5V/2.4A (12A)(1) USB-C port supports 5V/1.5A (7.5W) chargingCharge host with PD 2.0 charging (5/9/15V, 3A; 20V/4.25A) up to 85W |
| Charging Ports / Amps       | (4) 0.9A; (2) 1.5A; 2.4A  |
| PHYSICAL                    |   |
| Color                       | Black   |
| Material of Construction    | PC+ABS  |
| Cable Jacket Rating         | VW-1  |
| Cable Outer Diameter (OD)   | 5.0mm   |
| Cable Length (ft.)          | 3.28  |
| Cable Length (m)            | 1.00  |
| Total Number of Ports       | 15  |
| Unit Packaging Type         | Box   |
| Unit Weight (Ibs.)          | 0.86  |
| Unit Weight (kg)            | 0.39  |
| ENVIRONMENTAL               |   |





| Operating Temperature Range              | 32° to 104°F (0° to 40°C)   |  |  |
|--|---|--|--|
| Storage Temperature Range                | -4° to 158°F (-20° to 70°C)   |  |  |
| Relative Humidity                        | 20% to 80% RH, Non-Condensing   |  |  |
| Operating Humidity Range                 | 20% to 80% RH, Non-Condensing   |  |  |
| Storage Humidity Range                   | 20% to 80% RH, Non-Condensing   |  |  |
| Power Provided to Connected<br>Device(s) | USB-C PD 2.0 Port: 20/15/9/5V@4.25A (85W), (x4) USB3.2-A Ports: 5V/0.9A (4.5W), USB3.2-A Charging Port: 5V/1.5A (7.5W); USB-C: 5V/1.5A (7.5W) |  |  |
| COMMUNICATIONS                           |   |  |  |
| Network Compatibility                    | 1 Gbps (Gigabit)  |  |  |
| FEATURES & SPECIFICATIONS                |   |  |  |
| USB Hub Ports                            | Yes   |  |  |
| Number of USB Hub Ports                  | 5   |  |  |
| USB Specification                        | USB 3.0 (up to 5 Gbps); USB 3.1 Gen 1 (up to 5 Gbps); USB 3.2 Gen 1 (up to 5 Gbps)  |  |  |
| Data Transfer Rate                       | 1 Gbps; 10 Mbps; 100 Mbps; 5 Gbps   |  |  |
| Multi-Resolution Support                 | Yes   |  |  |
| Ethernet Support                         | Yes   |  |  |
| UASP Support                             | No  |  |  |
| Auto MDIX Support                        | Yes   |  |  |
| Full Duplex Support                      | Yes   |  |  |
| Suspend Mode Support                     | Yes   |  |  |
| Remote Wakeup Support                    | Yes   |  |  |
| Displayport Specification                | 1.2   |  |  |
| Driver Required                          | Yes   |  |  |
| Recommended Category Cable               | Cat6 Cables   |  |  |
| STANDARDS & COMPLIANCE                   |   |  |  |
| TAA Compliant Option                     | Ν   |  |  |
| External Power Supply Certifications     | BSMI; CE; GS; PSE; RCM; TUV; WEEE; cUL  |  |  |
| Product Certifications                   | NOM (Mexico)  |  |  |
| Product Compliance                       | CE (Europe); FCC (USA); REACH; RoHS; UKCA; WEEE   |  |  |
| WARRANTY & SUPPORT                       |   |  |  |
| Product Warranty Period<br>(Worldwide)   | 1-year limited warranty   |  |  |





1000 Eaton Boulevard Cleveland, OH 44122 United States https://tripplite.eaton.com © 2024 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.

# **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Tripp Lite:

U442-DOCK21BINT