



# USB-C Multiport Adapter (M/3xF) - 4K HDMI, DVI, VGA, HDCP, White

## MODEL NUMBER: U444-06N-HDV4K











All-in-one converter/adapter connects a USB-C or Thunderbolt™ 3 port to an HDMI, DVI or VGA display without the need to carry separate adapters. Designed for MacBook®, Google Chromebook Pixel™ and other USB-C computers.

#### **Description**

No more carrying around separate adapters for various monitors, projectors and televisions. The U444-06N-HDV4K USB-C to HDMI/DVI/VGA All-in-One Converter Adapter connects your laptop or tablet's USB Type-C or Thunderbolt 3 port to an HDMI, DVI or VGA display. The simple all-in-one solution for displaying content on a larger screen, the U444-06N-HDV4K is ideal for use in trade shows, conference rooms, classrooms, lecture halls and anywhere else you might give a presentation.

The all-in-one unit contains separate female HDMI, DVI and HD15 ports. USB DisplayPort Alternate Mode allows audio/video signals to pass through your source device's USB-C or Thunderbolt 3 port. It supports video resolutions up to 3840 x 2160 (4K x 2K) at 30 Hz (HDMI); 1920 x 1080 (1080p) at 60 Hz (DVI); and 1920 x 1200, including 1080p (HD15) at 60 Hz. It also supports 36-bit Deep Color (12 bits per channel), 7.1-channel surround sound audio (HDMI) and HDCP 1.4.

The U444-06N-HDV4K is specifically designed for use with MacBook, Google Chromebook Pixel and all other laptops, tablets and devices equipped with a female USB-C or Thunderbolt 3 port. It's completely plug-and-play with no software, drivers or external power supply required. With its small size and built-in cable, the U444-06N-HDV4K is recommended for stowing in your laptop bag and carrying to school, the office or the latest trade show.

#### **Features**

### Connects Your USB-C or Thunderbolt Laptop or Tablet to a VGA, DVI or HDMI Display

- Supports USB DisplayPort Alternate Mode for transmitting A/V signal via USB-C or Thunderbolt 3 port
- · Recommended for trade shows, classrooms, lecture halls and other presentation venues

#### Provides Crystal-Clear, Colorful Video Images

- HDMI port supports video resolutions up to 3840 x 2160 (4K x 2K) @ 30 Hz
- DVI port supports video resolutions up to 1920 x 1080 @ 60 Hz
- HD15 port supports video resolutions up to 1920 x 1200 @ 60 Hz
- Supports 36-bit Deep Color (12 bits per channel)

### **Up-To-Date Technical Features**

HDMI port supports 7.1-channel surround sound audio

### **Highlights**

- Separate DVI, HD15 and HDMI female connectors
- HDMI port supports 4K x 2K video resolutions @ 30 Hz
- Supports USB DisplayPort Alternate Mode
- Plug and play—no software, drivers or power supply needed
- Low-profile design for easy carrying in laptop bag or briefcase

#### **System Requirements**

- Source device with USB-C or Thunderbolt 3 output that supports USB DisplayPort Alternate Mode
- Display device with HDMI, DVI or VGA input

### **Package Includes**

- U444-06N-HDV4K USB-C to HDMI/DVI/VGA All-in-One Converter Adapter, 6 in.
- · Owner's manual





- Supports 300 MHz/3 Gbps per channel bandwidth (9 Gbps total)
- HDCP 1.4-compatible

### Plug-and-Play Convenience

- No software, drivers or external power supply required
- Low-profile design for easy carrying in laptop bag or briefcase

# **Specifications**

_		
OVERVIEW		
UPC Code	037332203571	
Product Type	Multiport Adapter	
Technology	DVI; HDMI; VGA/SVGA	
Host Connector	USB C (MALE)	
VIDEO		
Video Input	USB C (MALE)	
Video Output	HD15 (FEMALE); HDMI (FEMALE)	
Number of Monitors Supported	1	
Video Ports	HDMI (FEMALE); DVI-I DUAL LINK (FEMALE); HD15 (FEMALE)	
Video Ports Details	HDMI 1.4; HDCP 1.4	
Resolutions Supported	HDMI: 4K 30Hz (3840 x 2160) DVI: 1080P 60Hz (1920 x 1080) VGA: 1920 x 1200 60Hz	
Supported Resolutions	1280x720 (720p); 1920x1080 (1080p); 1920x1200; 2560x1600; 3840x2160 (4K)	
Max Supported Video Resolution	HDMI: 3840 X 2160 (4K X 2K) @ 30HZ, VGA: 1920 x 1200 (1080p) @ 60Hz, DVI: 1920 x 1080 (1080p) @ 60Hz	
Extended Mode	Yes	
Mirror Mode	Yes	
Max Supported Color Depth	24-bit True Color	
HDR Support	No	
3D Video Supported	Yes	
EDID Support	No	
DisplayPort Alt Mode	Yes	
INPUT		
Built-In Cable Length (ft.)	0.328	
Built-In Cable Length (m)	0.1	
Built-In Cable Length (in.)	3.94	
Built-In Cable Length (cm)	10	
Bus Powered	Yes	





Product Length (ft.) 0.4  Product Length (m) 0.5  BATTERY  Battery Charging (5V/1.5A Port) No.5  POWER	5.24
Product Length (ft.) 0.9 Product Length (m) 0.9  BATTERY  Battery Charging (5V/1.5A Port) No.9  POWER	1.5 1.15
Product Length (m) 0.  BATTERY  Battery Charging (5V/1.5A Port) No.  POWER	lo lo
BATTERY  Battery Charging (5V/1.5A Port)  POWER	lo
Battery Charging (5V/1.5A Port)  POWER	
POWER	
-	.80
Power Consumption (Watts)	.80
. S.roi Sonoamption (vvatto)	
CONNECTIONS	
Number of Ports 3	
Side A - Connector 1	JSB C (MALE)
Side B - Connector 1	OVI-I DUAL-LINK (FEMALE) (WIRED TO DVI-D SINGLE-LINK)
Side B - Connector 2	ID15 (FEMALE)
Side B - Connector 3	IDMI (FEMALE)
Connector Plating Ni	lickel
PHYSICAL	
Color	Vhite
Material of Construction P\	PVC, ABS
Cable Jacket Rating VV	/W-1
Cable Outer Diameter (OD) 3.9	.9mm
Wire Gauge (AWG) 28	8+34
Shipping Dimensions (hwd / in.) 0.9	.91 x 5.51 x 3.94
Shipping Dimensions (hwd / cm) 2.3	.31 x 14.00 x 10.01
Shipping Weight (lbs.) 0.	.15
Shipping Weight (kg) 0.0	.07
Unit Dimensions (hwd / in.) 0.0	.600 x 3.300 x 1.800
Unit Packaging Type Bo	3ox
Unit Weight (lbs.) 0.	.12
Unit Weight (kg) 0.0	.05
ENVIRONMENTAL	
Operating Temperature Range 32	2° to 113°F (0° to 45°C)
Storage Temperature Range 14	4° to 158°F (-10° to 70°C)
BTUs 6.	.1 BTU/Hr





Operating Humidity Range	10% to 85% RH, Non-Condensing	
Storage Humidity Range	5% to 90% RH, Non- Condensing	
FEATURES & SPECIFICATIONS		
USB Hub Ports	No	
Number of USB Hub Ports	0	
USB Specification	USB 3.0 (up to 5 Gbps); USB 3.1 Gen 1 (up to 5 Gbps); USB 3.2 Gen 1 (up to 5 Gbps)	
UASP Support	No	
Auto MDIX Support	No	
Full Duplex Support	No	
Suspend Mode Support	No	
Remote Wakeup Support	No	
HDCP Specification	1.4	
Driver Required	No	
STANDARDS & COMPLIANCE		
TAA Compliant Option	N	
Product Compliance	RoHS; CE (Europe); REACH; FCC (USA)	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	3-year limited warranty	

1000 Eaton Boulevard Cleveland, OH 44122 United States https://tripplite.eaton.com © 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark. All other trademarks are the property of their respective owners.

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

# Tripp Lite:

U444-06N-HDV4K