



BZT5250H series

Low-current voltage regulator diodes

Rev. 1 — 18 July 2024

Product data sheet

1. General description

General-purpose Zener diodes in an SOD123F small and flat lead Surface-Mounted Device (SMD) plastic package.

2. Features and benefits

- Total power dissipation: ≤ 830 mW
- Two tolerance series: ± 2 % and approximately ± 5 %
- Working voltage range: nominal 1.8 V to 51 V (E24 range)
- Specified at a low test current (50 μ A), ideal for low bias and portable battery-powered applications
- Small plastic package suitable for surface-mounted design
- BZT5250H-B11 to -C51: Intentional minor rise of leakage current for optimized fast switching and noise reduction [\[AN90031\]](#)

3. Applications

- Low-current general regulation functions

4. Quick reference data

Table 1. Quick reference data

Symbol	Parameter	Conditions		Min	Typ	Max	Unit
V_F	forward voltage	$I_F = 10$ mA	[1]	-	-	0.9	V
P_{tot}	total power dissipation	$T_{amb} \leq 25$ °C	[2]	-	-	375	mW
			[3]	-	-	830	mW



[1] Pulse test: $t_p \leq 300$ μ s; $\delta \leq 0.02$.

[2] Device mounted on an FR4 Printed-Circuit Board (PCB), single-sided copper, tin-plated and standard footprint.

[3] Device mounted on an FR4 PCB, single-sided copper, tin-plated, mounting pad for cathode 1 cm².

5. Pinning information

Table 2. Pinning

Pin	Symbol	Description		Simplified outline	Graphic symbol
1	K	cathode	[1]		 006aaa152
2	A	anode			

[1] The marking bar indicates the cathode.

6. Ordering information

Table 3. Ordering information

Type number	Package		
	Name	Description	Version
BZT5250H series	-	plastic, surface-mounted package; 2 leads; 2.6 mm x 1.6 mm x 1.1 mm body	SOD123F

7. Marking

Table 4. Marking Codes

Type number	Marking code	Type number	Marking code	Type number	Marking code	Type number	Marking code
BZT5250H-B1V8	U9	BZT5250H-B10	W9	BZT5250H-C1V8	X3	BZT5250H-C10	XM
BZT5250H-B2V0	V1	BZT5250H-B11	WA	BZT5250H-C2V0	X4	BZT5250H-C11	XN
BZT5250H-B2V2	V2	BZT5250H-B12	WB	BZT5250H-C2V2	X5	BZT5250H-C12	XP
BZT5250H-B2V4	V3	BZT5250H-B13	WC	BZT5250H-C2V4	X6	BZT5250H-C13	XQ
BZT5250H-B2V7	V4	BZT5250H-B15	WD	BZT5250H-C2V7	X7	BZT5250H-C15	XR
BZT5250H-B3V0	V5	BZT5250H-B16	WF	BZT5250H-C3V0	X8	BZT5250H-C16	XS
BZT5250H-B3V3	V6	BZT5250H-B18	WH	BZT5250H-C3V3	X9	BZT5250H-C18	XT
BZT5250H-B3V6	V7	BZT5250H-B20	WJ	BZT5250H-C3V6	XA	BZT5250H-C20	XU
BZT5250H-B3V9	V8	BZT5250H-B22	WL	BZT5250H-C3V9	XB	BZT5250H-C22	XV
BZT5250H-B4V3	V9	BZT5250H-B24	WN	BZT5250H-C4V3	XC	BZT5250H-C24	Y1
BZT5250H-B4V7	W1	BZT5250H-B27	WQ	BZT5250H-C4V7	XD	BZT5250H-C27	Y5
BZT5250H-B5V1	W2	BZT5250H-B30	WS	BZT5250H-C5V1	XE	BZT5250H-C30	Y6
BZT5250H-B5V6	W3	BZT5250H-B33	WU	BZT5250H-C5V6	XF	BZT5250H-C33	Y7
BZT5250H-B6V2	W4	BZT5250H-B36	WV	BZT5250H-C6V2	XG	BZT5250H-C36	Y8
BZT5250H-B6V8	W5	BZT5250H-B39	23	BZT5250H-C6V8	XH	BZT5250H-C39	Y9
BZT5250H-B7V5	W6	BZT5250H-B43	WX	BZT5250H-C7V5	XJ	BZT5250H-C43	Z2
BZT5250H-B8V2	W7	BZT5250H-B47	WY	BZT5250H-C8V2	XK	BZT5250H-C47	ZQ
BZT5250H-B9V1	W8	BZT5250H-B51	X2	BZT5250H-C9V1	XL	BZT5250H-C51	ZX

8. Limiting values

Table 5. Limiting values
In accordance with the Absolute Maximum Rating System (IEC 60134).

Symbol	Parameter	Conditions	Min	Max	Unit
I _F	forward current		-	200	mA
P _{ZSM}	non-repetitive peak reverse power dissipation	t _p = 100 μs; square wave; T _j = 25 °C; prior to surge	-	40	W
P _{tot}	total power dissipation	T _{amb} ≤ 25 °C	[1] -	375	mW
			[2] -	830	mW
T _j	junction temperature		-	150	°C
T _{amb}	ambient temperature		-55	+150	°C
T _{stg}	storage temperature		-65	+150	°C

[1] Device mounted on an FR4 PCB, single-sided copper, tin-plated and standard footprint.
[2] Device mounted on an FR4 PCB, single-sided copper, tin-plated, mounting pad for cathode 1 cm².

9. Thermal characteristics

Table 6. Thermal characteristics

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
R _{th(j-a)}	thermal resistance from junction to ambient	in free air	[1] -	-	330	K/W
			[2] -	-	150	K/W
R _{th(j-sp)}	thermal resistance from junction to solder point		[3] -	-	70	K/W

[1] Device mounted on an FR4 PCB, single-sided copper, tin-plated and standard footprint.
[2] Device mounted on an FR4 PCB, single-sided copper, tin-plated, mounting pad for cathode 1 cm².
[3] Soldering point of cathode tab.

10. Characteristics

Table 7. Electrical characteristics
T_j = 25 °C unless otherwise specified.

Symbol	Parameter	Conditions	Max	Unit
V _F	forward voltage	I _F = 10 mA	[1] 0.9	V

[1] Pulse test: t_p ≤ 300 μs; δ ≤ 0.02

Table 8. Electrical characteristics per type: BZT5250H-B1V8 to BZT5250H-C36

T_j = 25 °C unless otherwise specified.



BZT5250H-xxx	Sel.	Working voltage V _Z (V)		Differential resistance r _{diff} (Ω)		Reverse current I _R (μA)		Temperature coefficient S _Z (mV/K)		Diode capacitance C _d (pF)
		I _Z = 50 μA		I _Z = 1 mA	I _Z = 5 mA			I _Z = 5 mA		f = 1 MHz V _R = 0 V
		Min	Max	Max	Max	Max	V _R (V)	Min	Max	Max
1V8	B	1.76	1.84	600	100	7.5	1.0	-3.5	0	220
	C	1.71	1.89							
2V0	B	1.96	2.04	600	100	7	1.0	-3.5	0	220
	C	1.88	2.12							
2V2	B	2.15	2.25	600	100	4	1.0	-3.5	0	210
	C	2.09	2.31							
2V4	B	2.35	2.45	600	100	2	1.0	-3.5	0	200
	C	2.28	2.52							
2V7	B	2.65	2.75	600	100	1	1.0	-3.5	0	190
	C	2.565	2.835							
3V0	B	2.94	3.06	600	100	0.8	1.0	-3.5	0.2	170
	C	2.85	3.15							
3V3	B	3.23	3.37	600	100	7.5	1.5	-3.5	1.2	160
	C	3.13	3.47							
3V6	B	3.53	3.67	600	95	7.5	2.0	-3.5	1.2	160
	C	3.42	3.78							
3V9	B	3.82	3.98	600	95	5.0	2.0	-2.7	2.5	150
	C	3.70	4.10							
4V3	B	4.21	4.39	600	95	4.0	2.0	-2.7	2.5	150
	C	4.09	4.52							
4V7	B	4.61	4.79	600	80	5.0	3.0	-2.7	2.5	140
	C	4.47	4.94							
5V1	B	5.00	5.20	500	60	5.0	3.0	-2.0	3.7	130
	C	4.85	5.36							
5V6	B	5.49	5.71	400	40	2.0	4.0	-2.0	3.7	120
	C	5.32	5.88							
6V2	B	6.08	6.32	160	10	1.0	5.0	0.4	4.5	110
	C	5.89	6.51							
6V8	B	6.66	6.94	80	15	0.1	5.1	1.2	4.5	100
	C	6.46	7.14							
7V5	B	7.35	7.65	80	15	0.1	5.7	2.5	5.3	150
	C	7.13	7.88							
8V2	B	8.04	8.36	80	15	0.1	6.2	3.2	6.2	150
	C	7.79	8.61							
9V1	B	8.92	9.28	100	15	0.1	6.9	3.8	7.0	150
	C	8.65	9.56							
10	B	9.80	10.20	150	20	0.1	7.6	4.5	8.0	90
	C	9.50	10.50							

BZT5250H- xxx	Sel.	Working voltage V _Z (V)		Differential resistance r _{diff} (Ω)		Reverse current I _R (μA)		Temperature coefficient S _Z (mV/K)		Diode capacitance C _d (pF)
		I _Z = 50 μA		I _Z = 1 mA	I _Z = 5 mA			I _Z = 5 mA		f = 1 MHz V _R = 0 V
		Min	Max	Max	Max	Max	V _R (V)	Min	Max	Max
11	B	10.80	11.20	150	20	0.05	8.4	5.4	9.0	85
	C	10.45	11.55							
12	B	11.80	12.20	150	25	0.05	9.1	6.0	10	85
	C	11.40	12.60							
13	B	12.70	13.30	170	30	0.05	9.8	7.0	11	80
	C	12.35	13.65							
15	B	14.70	15.30	200	30	0.05	11.4	9.2	13	75
	C	14.25	15.75							
16	B	15.70	16.30	200	40	0.05	12.1	10.4	14	75
	C	15.20	16.80							
18	B	17.60	18.40	225	45	0.05	13.6	12.4	16	70
	C	17.10	18.90							
20	B	19.60	20.40	225	55	0.05	15.2	14.4	18	60
	C	19.00	21.00							
22	B	21.60	22.40	250	55	0.05	16.7	16.4	20	60
	C	20.90	23.10							
24	B	23.50	24.50	250	70	0.05	18.2	18.4	22	55
	C	22.80	25.20							
27	B	26.50	27.50	300	80	0.05	20.4	21.4	25.3	50
	C	25.65	28.35							
30	B	29.40	30.60	300	80	0.05	22.8	24.4	29.4	50
	C	28.50	31.50							
33	B	32.30	33.70	325	80	0.05	25.0	27.4	33.4	45
	C	31.35	34.65							
36	B	35.30	36.70	350	90	0.05	27.3	30.4	37.4	45
	C	34.20	37.80							

Table 9. Electrical characteristics per type: BZT5250H-B39 to BZT5250H-C51

T_j = 25 °C unless otherwise specified.

BZT5250H-xxx	Sel.	Working voltage V _Z (V)		Differential resistance r _{diff} (Ω)		Reverse current I _R (μA)		Temperature coefficient S _Z (mV/K)		Diode capacitance C _d (pF)
		I _Z = 50 μA		I _Z = 0.5 mA	I _Z = 2 mA			I _Z = 2 mA		f = 1 MHz V _R = 0 V
		Min	Max	Max	Max	Max	V _R (V)	Min	Max	Max
39	B	38.20	39.80	350	130	0.05	29.6	33.4	41.2	45
	C	37.05	40.95							
43	B	42.10	43.90	375	150	0.05	32.6	37.6	46.6	40
	C	40.85	45.15							
47	B	46.10	47.90	375	170	0.05	32.9	42.0	51.8	40
	C	44.00	50.00							
51	B	50.00	52.00	400	180	0.05	35.7	46.6	57.2	40
	C	48.00	54.00							






Fig. 3. Forward current as a function of forward voltage; typical values (BZT5250H-B/C6V8)




Fig. 4. Forward current as a function of forward voltage; typical values (BZT5250H-B/C7V5)




Fig. 5. Reverse current as a function of reverse voltage; typical values (BZT5250H-B/C1V8 to BZT5250H-B/C6V8)




Fig. 6. Reverse current as a function of reverse voltage; typical values (BZT5250H-B/C7V5 to BZT5250H-B/C10)




Fig. 7. Reverse current as a function of reverse voltage; typical values (BZT5250H-B/C11 to BZT5250H-B/C36)




Fig. 8. Reverse current as a function of reverse voltage; typical values (BZT5250H-B/C39 to BZT5250H-B/C51)

11. Package outline




Fig. 9. Package outline SOD123F

12. Soldering




Fig. 10. Reflow soldering footprint SOD123F

13. Revision history

Table 10. Revision history

Document ID	Release date	Data sheet status	Change notice	Supersedes
BZT5250H_SER v.1	20240718	Product data sheet	-	-

14. Legal information

Data sheet status

Document status [1][2]	Product status [3]	Definition
Objective [short] data sheet	Development	This document contains data from the objective specification for product development.
Preliminary [short] data sheet	Qualification	This document contains data from the preliminary specification.
Product [short] data sheet	Production	This document contains the product specification.

- [1] Please consult the most recently issued document before initiating or completing a design.
- [2] The term 'short data sheet' is explained in section "Definitions".
- [3] The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the internet at <https://www.nexperia.com>.

Definitions

Draft — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. Nexperia does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

Short data sheet — A short data sheet is an extract from a full data sheet with the same product type number(s) and title. A short data sheet is intended for quick reference only and should not be relied upon to contain detailed and full information. For detailed and full information see the relevant full data sheet, which is available on request via the local Nexperia sales office. In case of any inconsistency or conflict with the short data sheet, the full data sheet shall prevail.

Product specification — The information and data provided in a Product data sheet shall define the specification of the product as agreed between Nexperia and its customer, unless Nexperia and customer have explicitly agreed otherwise in writing. In no event however, shall an agreement be valid in which the Nexperia product is deemed to offer functions and qualities beyond those described in the Product data sheet.

Disclaimers

Limited warranty and liability — Information in this document is believed to be accurate and reliable. However, Nexperia does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information. Nexperia takes no responsibility for the content in this document if provided by an information source outside of Nexperia.

In no event shall Nexperia be liable for any indirect, incidental, punitive, special or consequential damages (including - without limitation - lost profits, lost savings, business interruption, costs related to the removal or replacement of any products or rework charges) whether or not such damages are based on tort (including negligence), warranty, breach of contract or any other legal theory.

Notwithstanding any damages that customer might incur for any reason whatsoever, Nexperia's aggregate and cumulative liability towards customer for the products described herein shall be limited in accordance with the Terms and conditions of commercial sale of Nexperia.

Right to make changes — Nexperia reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

Suitability for use — Nexperia products are not designed, authorized or warranted to be suitable for use in life support, life-critical or safety-critical systems or equipment, nor in applications where failure or malfunction of an Nexperia product can reasonably be expected to result in personal

injury, death or severe property or environmental damage. Nexperia and its suppliers accept no liability for inclusion and/or use of Nexperia products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

Quick reference data — The Quick reference data is an extract of the product data given in the Limiting values and Characteristics sections of this document, and as such is not complete, exhaustive or legally binding.

Applications — Applications that are described herein for any of these products are for illustrative purposes only. Nexperia makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Customers are responsible for the design and operation of their applications and products using Nexperia products, and Nexperia accepts no liability for any assistance with applications or customer product design. It is customer's sole responsibility to determine whether the Nexperia product is suitable and fit for the customer's applications and products planned, as well as for the planned application and use of customer's third party customer(s). Customers should provide appropriate design and operating safeguards to minimize the risks associated with their applications and products.

Nexperia does not accept any liability related to any default, damage, costs or problem which is based on any weakness or default in the customer's applications or products, or the application or use by customer's third party customer(s). Customer is responsible for doing all necessary testing for the customer's applications and products using Nexperia products in order to avoid a default of the applications and the products or of the application or use by customer's third party customer(s). Nexperia does not accept any liability in this respect.

Limiting values — Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) will cause permanent damage to the device. Limiting values are stress ratings only and (proper) operation of the device at these or any other conditions above those given in the Recommended operating conditions section (if present) or the Characteristics sections of this document is not warranted. Constant or repeated exposure to limiting values will permanently and irreversibly affect the quality and reliability of the device.

Terms and conditions of commercial sale — Nexperia products are sold subject to the general terms and conditions of commercial sale, as published at <http://www.nexperia.com/profile/terms>, unless otherwise agreed in a valid written individual agreement. In case an individual agreement is concluded only the terms and conditions of the respective agreement shall apply. Nexperia hereby expressly objects to applying the customer's general terms and conditions with regard to the purchase of Nexperia products by customer.

No offer to sell or license — Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

Export control — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from competent authorities.

Non-automotive qualified products — Unless this data sheet expressly states that this specific Nexperia product is automotive qualified, the product is not suitable for automotive use. It is neither qualified nor tested in accordance with automotive testing or application requirements. Nexperia accepts no liability for inclusion and/or use of non-automotive qualified products in automotive equipment or applications.

In the event that customer uses the product for design-in and use in automotive applications to automotive specifications and standards, customer (a) shall use the product without Nexperia's warranty of the product for such automotive applications, use and specifications, and (b) whenever customer uses the product for automotive applications beyond Nexperia's specifications such use shall be solely at customer's own risk, and (c) customer fully indemnifies Nexperia for any liability, damages or failed product claims resulting from customer design and use of the product for automotive applications beyond Nexperia's standard warranty and Nexperia's product specifications.

Translations — A non-English (translated) version of a document is for reference only. The English version shall prevail in case of any discrepancy between the translated and English versions.

Trademarks

Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.

Contents

1. General description..... 1

2. Features and benefits..... 1

3. Applications..... 1

4. Quick reference data..... 1

5. Pinning information.....2

6. Ordering information.....2

7. Marking.....2

8. Limiting values..... 3

9. Thermal characteristics..... 3

10. Characteristics..... 3

11. Package outline..... 8

12. Soldering..... 9

13. Revision history..... 10

14. Legal information..... 11

© Nexperia B.V. 2024. All rights reserved

For more information, please visit: <http://www.nexperia.com>

For sales office addresses, please send an email to: salesaddresses@nexperia.com

Date of release: 18 July 2024

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Nexperia:](#)

[BZT5250H-C3V0X](#) [BZT5250H-C5V1X](#) [BZT5250H-C15X](#) [BZT5250H-B3V6X](#) [BZT5250H-B6V2X](#) [BZT5250H-B2V7X](#)
[BZT5250H-C27X](#) [BZT5250H-B18X](#) [BZT5250H-B30X](#) [BZT5250H-B6V8X](#) [BZT5250H-B9V1X](#) [BZT5250H-B11X](#)
[BZT5250H-B12X](#) [BZT5250H-B36X](#) [BZT5250H-C3V6X](#) [BZT5250H-C18X](#) [BZT5250H-C22X](#) [BZT5250H-C4V3X](#)
[BZT5250H-B24X](#) [BZT5250H-C20X](#) [BZT5250H-B10X](#) [BZT5250H-B47X](#) [BZT5250H-C3V3X](#) [BZT5250H-C1V8X](#)
[BZT5250H-C3V9X](#) [BZT5250H-C2V0X](#) [BZT5250H-B3V3X](#) [BZT5250H-C12X](#) [BZT5250H-C36X](#) [BZT5250H-B22X](#)
[BZT5250H-B4V3X](#) [BZT5250H-B4V7X](#) [BZT5250H-C43X](#) [BZT5250H-C47X](#) [BZT5250H-B2V0X](#) [BZT5250H-B51X](#)
[BZT5250H-B5V1X](#) [BZT5250H-C24X](#) [BZT5250H-B2V2X](#) [BZT5250H-C2V7X](#) [BZT5250H-C7V5X](#) [BZT5250H-B13X](#)
[BZT5250H-B15X](#) [BZT5250H-B3V0X](#) [BZT5250H-C10X](#) [BZT5250H-C11X](#) [BZT5250H-C33X](#) [BZT5250H-B1V8X](#)
[BZT5250H-C16X](#) [BZT5250H-C2V4X](#) [BZT5250H-C5V6X](#) [BZT5250H-B27X](#) [BZT5250H-C4V7X](#) [BZT5250H-B33X](#)
[BZT5250H-B20X](#) [BZT5250H-B43X](#) [BZT5250H-B7V5X](#) [BZT5250H-C2V2X](#) [BZT5250H-C6V2X](#) [BZT5250H-C8V2X](#)
[BZT5250H-C9V1X](#) [BZT5250H-B5V6X](#) [BZT5250H-C39X](#) [BZT5250H-C51X](#) [BZT5250H-B16X](#) [BZT5250H-B2V4X](#)
[BZT5250H-C13X](#) [BZT5250H-B39X](#) [BZT5250H-B8V2X](#) [BZT5250H-C30X](#) [BZT5250H-C6V8X](#)